

2021 CORDLESS CATALOG



Nothing but **HEAVY DUTY**."

Milwaukee



 \bigcirc

 \bigcirc

 \bigcirc



milwaukeetool.com



THE OWNER OF THE OWNER OWNER OF THE OWNER OF THE OWNER OW

DEDICATION TO THE TRADES

Since the company began in 1924, Milwaukee Tool has led the industry in both durability and performance. With an unwavering commitment to the trades, MILWAUKEE[®] continues to lead with a focus on providing innovative, cordless, trade-specific solutions. MILWAUKEE® is dedicated to delivering a steady stream of advanced solutions for the trades that offer increased productivity and unmatched durability.

GAME-CHANGING SOLUTIONS

At MILWAUKEE[®] the phrase "good enough" doesn't exist in our vocabulary. Our goal is to solve problems in ways that have never been done before. The result: tools and equipment that offer unmatched levels of performance, productivity and durability.

BUILT ON THE BEST FOUNDATION



REDLITHIUM[™] BATTERIES



MILWAUKEE® HIGH PERFORMANCE MOTORS



and productivity.

THE WORLD LEADER **IN CORDLESS INNOVATION**







SYSTEM





They last longer, think faster and work harder than all other professional LITHIUM-ION batteries. Built to withstand even the harshest environments, REDLITHIUM[™] Batteries deliver more work over the life of the battery, no matter what the job.

Highly advanced motor technology boosts efficiency, generating more power from a compact power source. That means the ultimate performance, durability and run-time comes in a smaller, lighter package.

An advanced combination of hardware and software, REDLINK[™] Intelligence enables full-circle communication between our batteries and tools, allowing for unmatched levels of performance, protection



Instead of making assumptions about what users need, we set out to deliver disruptive innovation by getting out on the jobsite, alongside trade professionals, to understand their challenges - the frustrations, needs, and previous limitations. We set out to completely rethink a solution with new-to-world technology and unparalleled levels of design and engineering. Whether it's bringing cordless power to traditionally corded or gas products and manual activities, or advances to fundamental tools and equipment, we are dedicated to improving workplace productivity and safety.



M18[™] FORCE LOGIC[™] Press Tool w/ ONE-KEY[™]

THE SMALLEST. MOST **INTELLIGENT PRESS TOOL**

The M18[™] FORCE LOGIC[™] Press Tool w/ ONE-KEY[™] is the industry's smallest, most intelligent press tool. With an in-line design and brushless motor, it achieves more run-time per charge and faster cycle times while being significantly smaller and nearly 20% lighter than the leading competitor. The M18[™] FORCE LOGIC[™] Press Tool w/ ONE-KEY[™] and compatible jaws are designed to work with over 20 unique fitting systems offering 1/2" to 4" capacity. With the addition of ONE-KEY[™] compatibility, the press tool automatically logs and wirelessly uploads connection data from every press made with the tool which can be passed onto key stakeholders through customizable reports.



M12 FUEL[™] 3/8" Digital Torgue Wrench w/ ONE-KEY™

50% FASTER

ELIVERS TORQUE FASTER, MORE ACCURACY PRODUCTIVE ир то +/- 2%

The M12 FUEL[™] Digital Torque Wrench w/ ONE-KEY[™] is the industry's first torque wrench with a motor, delivering increased productivity, precise torgue accuracy, and user demanded reporting functionality. The torgue wrench delivers up to 50% faster installation time, replacing the hand tool or two tool installation process and providing accuracy within 2% for torgue critical fasteners. This battery powered torque wrench is equipped with MILWAUKEE[®] ONE-KEY[™], giving you the power to record all the fasteners and produce a downloadable report via ONE-KEY[™].



M18 FUEL[™] 8-1/4" Table Saw w/ ONE-KEY[™]





The world's first 18V table saw, the M18 FUEL[™] 8-1/4" Table Saw w/ ONE-KEY[™] generates the power of a 15 amp corded saw. With a rip capacity up to 24-1/2" and a vertical capacity up to 2-1/2" to tackle 2x dimensional lumber, this saw boasts the impressive capacity that users have come to expect on a traditional corded table saw. Equipped with ONE-KEY[™], users can also easily track, manage, and secure the table saw through the ONE-KEY[™] app on their phone.

M18[™] FORCE LOGIC[™] 10 Ton Knockout Tool

THE EASIEST WAY TO PUNCH

The MILWAUKEE® Knockout System makes every step in the hole making process both faster and easier. The EXACT[™] Punches and Dies are set up separate from the tool for extreme ease of use, utilizing a quick-connect alignment system that allows users to snap the tool onto the punches and dies without fighting against its weight and pull the trigger to punch the hole with ease.





200 BOLTS PER CHARGE HOSES

Our M18 FUEL™ 1" D-Handle Extended Anvil High Torque Impact Wrench w/ ONE-KEY™ is engineered for the performance, run-time, and unmatched portability heavy duty technicians demand. The POWERSTATE™ Brushless Motor delivers up to 2,000 ft-lbs of nut-busting torque and 1,900 ft-lbs of fastening torque, enabling you to complete the most demanding applications. With the run-time for up to 120 lug nut removals and installations on a single HIGH OUTPUT™ HD12.0 Battery, this portable impact wrench provides unmatched performance. Lug Nut Mode, which can be enabled through the ONE-KEY[™] app, prevents the over-torque of lug nuts by automatically shutting off the tool, providing more control. The REDLINK PLUS™ Intelligence ensures you achieve maximum performance and protects the High Torque Impact Wrench against overloads, over-heating, and over-discharge.



MX FUEL[™] 14" Cut-Off Saw

INSTANT START ZERO EMISSIONS



The MX FUEL™ 14" Cut-Off Saw delivers instant starts and zero emissions while providing you with no gas headaches, fastest cuts from start to finish, and can cut 6 ft of concrete or 72 cuts in #5 rebar per charge. By providing a 5" cut depth and eliminating the hassle of pull starts, the MX FUEL[™] 14" Cut-Off Saw helps you maximize your productivity in every application. The MX FUEL™ REDLITHIUM[™] Battery Pack provides instant power with less noise and vibration, and zero emissions for a safer workspace indoors or outdoors.



З

TRADE-FOCUSED SOLUTIONS





The M18 FUEL[™] Pipe Threader w/ ONE-KEY[™] revolutionizes pipe threading. Featuring AUTOSTOP[™] kickback control, the tool protects against severe kickback. This, combined with the integrated side-grip for easier thread starts, delivers unrivaled tool control. The world's first cordless pipe threader threads faster than corded alternatives and delivers unmatched productivity.



M18[™] FORCE LOGIC[™] 10.000 PSI Hydraulic Pump

THE EASIEST WAY **TO POWER HYDRAULICS**

The M18[™] FORCE LOGIC[™] 10,000 PSI Hydraulic Pump is designed to be fully compatible with all existing 10,000 PSI rated hydraulic hoses and heads. Delivering the easiest set-up, at up to 80% smaller and up to 75 lbs lighter than gas units, the pump can easily be carried by a single person. Delivering 3X the flow rate of competitive cordless pumps; 24-second cycle times and up to 60 presses on a single battery on 1590 ACSR connectors, the pump provides gas-like performance.



THE WORLD LEADER IN CORDLESS INNOVATION

800

4

2

Milwaukee Tool is committed to driving unrivaled performance and productivity for the professional trades through our groundbreaking developments in cordless technology.

Our leadership in cordless innovation has helped to shape the industry. We were the first to introduce LITHIUM-ION technology to power tools, and have achieved significant leaps forward in advanced motors, the most intelligent electronics, and connected tools. This leadership allows us to continue providing a steady stream of solutions that exceed the demands

REDLITHIUM BATTERIES

CELL TECHNOLOGY

of the trades.

Not all batteries are created equal. In our world-class battery lab, battery cells are engineered to deliver the highest performing packs on the jobsite.

PACK CONSTRUCTION

Unique patented designs protect every REDLITHIUM[™] Battery, safeguarding your investment through drops, weather exposure, and harsh environments.

ROBUST ELECTRONICS

Innovative communication systems monitor cells, providing temperature and overload protection, while optimizing performance for every tool and battery combination.





POWERSTATE BRUSHLESS MOTORS

HIGH PERFORMANCE

MILWAUKEE's high performance POWERSTATE[™] Brushless Motors contain top-grade rare earth magnets and greater copper content, delivering more power and torque for superior application performance.

PURPOSE BUILT

Each motor is uniquely engineered for the demands of the tool.

Motor-optimization ensures the perfect combination of performance, portability and productivity.

POWERSTATE[™] BRUSHLESS MOTORS



LIGHT APPLICATIONS

LONGER MORE MORE MOTOR LIFE POWER RUN-TIME

REDLINK[®] INTELLIGENCE

DURABILITY

Best-in-class thermal and overload monitoring protects tools in extreme jobsite conditions.

PRODUCTIVITY

Advanced communication features, such as DRIVE CONTROL[™], allow users to guickly move from light to heavy applications with the touch of a button.

FULL SYSTEM COMPATIBILITY

With industry-leading intelligence connecting every battery, tool and charger. MILWAUKEE's M18[™] System has upheld full forward and backward compatibility for over a decade.

2007

2 TOOLS

UNMATCHED OPTIMIZED **PROTECTION PERFORMANCE PRODUCTIVITY**





ONE

Get more out of your tools and equipment than ever before with integrated tool tracking, security and customization. ONE-KEY™ combines smarter tools with the industry's only free-to-use inventory management program.









THE WORLD LEADER IN CORDLESS INNOVATION



PORTABLE PRODUCTIVITY. TRADE FOCUSED. SYSTEM WIDE.

Pages 9 - 36



PERFORMANCE DRIVEN. TRADE FOCUSED. SYSTEM WIDE.

Pages 37 - 82



EQUIPMENT REDEFINED. TRADE FOCUSED. SYSTEM WIDE.

Pages 83 - 94





performance





SMART TOOLS & EQUIPMENT

WIRELESSLY

DIGITAL PLATFORM FOR **TOOLS & EQUIPMENT**



0

Track your tools 9 and equipment location from anywhere

Lock and disable remotelv

See pages 18, 22, 41, 43, 45-49, 53, 55, 61 - 64, 67 - 69, 71, 75, 77, 89 - 94 for ONE-KEY[™] Compatible Tools and Equipment









8













ALL M12" TOOLS FIT M12 BATTERIES 125+ TOOLS



DRIVEN TO OUTPERFORM.

M12 FUEL[™] is engineered for the most demanding tradesmen in the world. M12 FUEL[™] delivers unrivaled performance in a compact structure and features three MILWAUKEE[®] exclusive innovations – the POWERSTATE[™] Brushless Motor, REDLITHIUM[™] Battery Pack and REDLINK PLUS[™] Intelligence Hardware and Software - that deliver unmatched power, run-time and durability.

Simply put, M12 FUEL[™] is best-in-class, full-circle technology that drives, protects and powers your cordless tools beyond the rest.







POWERSTATE[™] BRUSHLESS MOTOR

- MILWAUKEE[®] Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Up to 10X Longer Motor Life





REDLINK PLUS[™] INTELLIGENCE

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with
- Overload Protection Increases Tool Life Built-In Fuel Gauge Displays Remaining Charge





M12 FUEL

1/2" Hammer Drill/Driver Kit 2504-22 (2504-20 Tool-Only)

Specifications:			
Peak Torque	350 in-lbs		
RPM	0 – 1,700		
BPM	0 – 25,500		
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck		
Length / Weight	6.6" / 2.3 lbs		

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack. (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

M12[™] 3/8[∥] Hammer **Drill/Driver Kit**

2408-22 (2408-20 Tool-Only) Specifications:

эþ	eu		Ca	lioi	э.
		-			~

Peak Torque	275 in-Ibs
RPM	0 - 400 / 0 - 1,500
BPM	0 – 22,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.5" / 2.7 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12 FUEL 1/2" Drill/Driver Kit 2503-22 (2503-20 Tool-Only)

Creation

Specifications:			
Peak Torque	350 in-Ibs		
RPM	0 – 1,700		
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck		
Length / Weight	6.6" / 2.3 lbs		

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

MIZELEL Installation **Drill/Driver Kit** 2505-22 (2505-20 Tool-Only)

Specifications:

Attachments	3/8" Metal Chuck, 1/4" Hex, Offset and Right A	ngle
RPM (2-Mode)	0 - 400 / 0 - 1,600	
Max Torque	300 in-lbs	

Length / Weight 5.1" / 2.0 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, (4) Attachments (3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle), Belt Clip, Charger, Compartmentalized Contractor Bag

M12[™] 3/8[″] **Drill/Driver Kit**

2407-22 (2407-20 Tool-Only) Creatificati

Specifications:	
-----------------	--

Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.4" / 2.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



RPM	0 - 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

100 in-lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

M12 FUEL 1/4" Hex 2-Speed Screwdriver Kit 2402-22 (2402-20 Tool-Only) Specifications:			
	Peak Torque	325 in-Ibs	
	RPM	0 - 450 / 0 - 1,700	
	Chuck Type	1/4" Hex Quick Change	
	Length / Weight	6.6" / 2.0 lbs	
	RPM Chuck Type	0 – 450 / 0 – 1,700 1/4" Hex Quick Change	

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
Chuck Type	1/4" Hex Quick Change

Length / Weight 6.8" / 1.8 lbs Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12 [™] 1/4 [™] 1 Screwdriv 2401-22 (2401-20 To	er Kit
Specification	is:
Peak Torque	175 in-lbs
RPM	0 - 500

Chuck Type	1/4" Hex Quick Change	
Length / Weight	6.5" / 2.0 lbs	

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case



	Fastening Torque	1,300 in-lbs
	IPM	0 - 4,000
	RPM	0 – 3,300
	Chuck Type	1/4" Hex Quick Change
	Length / Weight	5.1" / 1.8 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs. Belt Clip, Charger, Carrying Case





M12 FUEL **SURGE[™] 1/4[®] Hex Hydraulic Driver Kit** 2551-22 (2551-20 Tool-Only)

Specifications:

•	
Sustained Fastening Torque	450 ft-lbs
IPM	0-3,400
RPM	0-3,200
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.2" / 2.4 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Contractor Bag

M12[™] 1/4[¶] Hex Impact **Driver Kit**

2462-22 (2462-20 Tool-Only) Specifications: Eastoning Torque

Fastening Torque	1,000 in-lbs
IPM	0 - 3,300
RPM	0 - 2,500
Chuck Type	1/4" Hex
Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Hex Right Angle **Impact Driver Kit**

2467-21 (2467-20 Tool-Only) **Specifications:**

specifications:		
Fastening Torque	600 in-lbs	
IPM	0 - 3,300	
RPM	0 - 2,450	
Chuck Type	1/4" Hex	
Head Profile	1.4"	
Weight	2.6 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

MZFUEL

1/2" Stubby Impact Wrench Kit 2555-22, 2555P-22 (2555-20 Tool-Only)

Specifications:

specifications:	
Peak Torque	250 ft-lbs
IPM	0 - 3,200
RPM	0 - 2,700
Anvil Type	1/2" Friction Ring
Length / Weight	4.9" / 2.1 lbs

Includes: 2555-22 1/2" Stubby Impact Wrench; 2555P-22 1/2" Stubby Impact Wrench w/ Pin Detent; All Kits Include: (1) M12™ REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



















M12FUEL

3/8" Stubby Impact Wrench Kit 2554-22 (2554-20 Tool-Only)

Specifications:

•	
Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12FUEL

1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only) **Encoifications**

specifications:		
Peak Torque	100 ft-lbs	
IPM	0 - 4,300	
RPM	0-3,200	
Anvil Type	1/4" Friction Ring	



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

5.1" / 1.8 lbs

M12 FUEL

Length / Weight

3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

Peak Torque	117 ft-lbs
IPM	0 – 3,500
RPM (2-Mode)	0 - 1,200 / 0 - 2,650
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.4 lbs



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8[¶] Impact Wrench Kit

2463-22 (2463-20 Tool-Only)

Peak Torque	100 ft-lbs
IPM	0 - 3,300
RPM	0 – 2,500
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.3 lbs



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Impact Wrench Kit

2461-22 (2461-20 Tool-Only) Specifications:

specifications:		
Peak Torque	38 ft-lbs	
IPM	0-3,800	
RPM	0 – 2,500	
Anvil Type	1/4" Friction Ring	
Length / Weight	6.0" / 2.1 lbs	









M2FUEL

1/2" Right Angle Impact Wrench w/ Friction Ring Kit 2565-22 (2565-20 Tool-Only)

Specifications:

opeenioationei	
Peak Torque	220 ft-lbs
IPM / RPM	0 - 3,600 / 0 - 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessory: 49-16-2564 M12 FUEL[™] Right Angle Impact Wrench Rubber Boot

M2 CLEL 1/2" Right Angle Impact Wrench w/ Pin Detent Kit

2565P-22 (2565P-20 Tool-Only)

Specifications:	
Peak Torque	220 ft-lbs
IPM / RPM	0 - 3,600 / 0 - 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessory:

49-16-2564 M12 FUEL[™] Right Angle Impact Wrench Rubber Boot



M12 EUEL 3/8" Right Angle Impact Wrench W/ Friction Ring Kit

1	2304-22 (2304-20 1001-01	iiy)
;	Specifications:	
	Peak Torque	220 ft-lbs
	IPM / RPM	0-3,600/0-3,000
	Head Profile	2.2"
	Length / Weight	14.2" / 3.2 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessory:

49-16-2564 M12 FUEL[™] Right Angle Impact Wrench Rubber Boot

M12]=U=U 1/2∥ Ratchet Kit

2558-22 (2558-20 Tool-Only)

Эр	eci	TICa	τιοΓ	IS:
-				

15

F	00 (1 1)
Fastening Torque	60 ft-lbs
RPM	0 – 175
Anvil Type	1/2" Ball Detent
Head Profile	1.1"
Length / Weight	12.5" / 3.1 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessory: 49-16-2558 M12 FUEL[™] 1/2[™] Ratchet Rubber Boot

M2 FUEL 3/8" Ratchet Kit

2557-22 (2557-20 Tool-Only) Specifications:

55 ft-lbs
0 – 200
3/8" Ball Detent
1.1"
11.8" / 2.8 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessory:

49-16-2557 M12 FUEL[™] 3/8" Ratchet Rubber Boot

M12 ELE 3/8" Extended Reach Ratchet Kit 2560-21 (2560-20 Tool-Only)

Specifications:

specifications.	
Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	15.1" / 3.1 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Charger, Contractor Bag

Related Accessory: 49-16-2560 M12 FUEL[™] 3/8" Extended Reach Ratchet Rubber Boot

1/4" Extended Reach Ratchet Kit 2559-21 (2559-20 Tool-Only)

Specifications:

-	
Fastening Torque	40 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.76"
Length / Weight	14.4" / 2.3 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Charger, Contractor Bag

Related Accessory: 49-16-2559 M12 FUEL[™] 1/4" Extended Reach Ratchet Rubber Boot

MIZFUEL

3/8" High Speed Ratchet Kit 2567-22 (2567-20 Tool-Only) Specifications:

Length / Weight	11.1" / 2.1 lbs
Head Profile	0.75"
Anvil Type	3/8" Ball Detent
RPM	0 – 450
Fastening Torque	35 ft-lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs,

Charger, Carrying Case Related Accessories:

49-16-2567 M12 FUEL[™] High Speed Ratchet Rubber Boot 49-09-2567 3/8" High Speed Ratchet Tall Shift Knob Assembly





M12 CUEL 1/4" High Speed Ratchet Kit

2566-22 (2566-20 Tool-Only) **Specifications:**

•	
Fastening Torque	35 ft-lbs
RPM	0 – 450
Anvil Type	1/4" Ball Detent
Head Profile	0.75"
Length / Weight	11.1" / 2.1 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Carrying Case Related Accessories: 49-16-2567 M12 FUEL[™] High Speed Ratchet Rubber Boot 49-09-2566 1/4" High Speed Ratchet Tall Shift Knob Assembly

M12[™] 3/8[■] Ratchet Kit

2457-21 (2457-20 Tool-Only) Specifications:

-	
Fastening Torque	35 ft-lbs
RPM	0 – 250
Anvil Type	3/8" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 3/8" – 1/4" Adapter, Charger, Soft Carrying Case

M12[™] 1/4[¶] Ratchet Kit

2456-21 (2456-20 Tool-Only) Specifications:

Fastening Torque	30 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case



M12[™] Rivet Tool Kit 2550-22 (2550-20 Tool-Only)

Specifications: Pull Force 2,000 lbs Stroke Length 0.8" Rivet Sizes 3/32" - 3/16" Rivet Material Aluminum, Steel and Stainless Steel Length / Weight 6.5" (without mandrel collector) / 4.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, (4) Nose Pieces (3/32[™], 1/8[™], 5/32[™], 3/16[™]), Belt Hook, Charger, Contractor Bag









MEFUEL

5/8" SDS Plus Rotary Hammer Kit

Specifications:

RPM	0 - 900
BPM	0-6,200
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	10.0" / 3.9 lbs



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Charger, Carrying Case Related Accessory:

2509-22 M12[™] HAMMERVAC[™] Universal Dust Extractor Kit



M12[™] 1/2[®] SDS Plus Rotary Hammer Kit

SDS

2412-22XC (2412-20 Tool-Only)

opcomoutions	7105
RPM	0 - 800
BPM	0 – 5,350
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	9.0" / 3.9 lbs



Includes: (2) M12[™] REDLITHIUM[™] XC3.0 Battery Packs, Charger, Carrying Case Related Accessory:

2509-22 M12[™] HAMMERVAC[™] Universal Dust Extractor Kit

M12[™] HAMMERVAC[™] **Universal Dust** CERTIFIED Extractor TABLE 1 OSHA HEPA 2509-22 (2509-20 Tool-Only) Specifications: Universal Handle Compatible with Major Brands of SDS Plus System Rotary Hammers and AC and DC Hammer Drills Replaceable Filters 99.97% of Debris Certified HEPA Filter 0.3 Microns and Above AUTOPULSE™ Filter Cleaning Mechanism achieves Table 1 OSHA Compliance Self-Powered by No Cords or Hoses for M12[™] REDLITHÍUM[™] Maximum Portability Battery Pack 3-Mode Switch Yes (Auto-On and Auto-Off w/ Delay) 1-1/4" Max Diameter

Includes: Small Diameter Nozzle, Large Diameter Nozzle; 2509-22 (2) M12[™] REDLITHIUM[™] CP2.0 Batteries, Charger, Contractor Bag Related Accessories: 49-90-2302 M12[™] HAMMERVAC[™] Universal Dust Extractor Nozzle 49-90-2343 M12[™] HAMMERVAC[™] Universal Dust Extractor Dust Box, Filter 49-90-2016 3 pk Fleece Dust Bags

8"



Max Depth





M12[™] Palm Nailer Kit 2458-21 (2458-20 Tool-Only) Creationer

specifications:		
Impact Energy	2.2 ft-lbs (3.0 J)	
BPM	0 – 2,700	
Collet Capacity	6D – 16D	
Head Profile	3/4"	
Magnetic Tip	Yes	
Weight	3.4 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hand Strap, Charger, Soft Carrying Case



M12[™] 23 Gauge Pin Nailer Kit 2540-21 (2540-20 Tool-Only)

Specifications:

Specifications:		
Nail Diameter	23 Gauge	
Nail Size	1/2" – 1-3/8"	
Magazine Capacity	120 Nails	
Magazine Loading	Side Load	
Firing Modes	Sequential	
Length / Weight	8.7" / 3.8 lbs	
Includes: (1) M12 [™] F Reversible Belt Clip, Jam		

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Reversible Belt Clip, Jam Clearing Guide, Hex Wrench, Secondary Tip, Charger, Contractor Bag

M12[™] 3/8[¶] Crown Stapler Kit

2447-21 (2447-20 Tool-Only) 5

Specifications:	
Staple Crown Size	3/8" Flat Crown
Staple Length	1/4" – 9/16"
Staple Type	T-50
Length / Weight	7.3" / 3.0 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Contractor Bag

T-50

M12 FUEL

1/4" Right Angle Die Grinder Kit 2485-22 (2485-20 Tool-Only)

Specifications:

Power Output	0.3 HP
RPM	0 – 24,500
Collet Size	1/4"
Accessory Size	2"
Height / Length	8.7" / 4.5"
Weight	1.7 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, (2) Wrenches, Charger, Carrying Case

Related Accessories: 49-16-2485 M12 FUEL[™] 1/4" Right Angle Die Grinder Rubber Boot **48-07-2486** 1/4" Cut-Off Wheel Arbor 48-66-2486 1/8" Collet & Nut Kit 49-94-2000 2" Metal Cut-Off Wheel



M12FUEL 1/4" Straight Die Grinder Kit 2486-22 (2486-20 Tool-Only)

S

Specifications:	
Power Output	0.3 HP
RPM	0 - 21,000
Collet Size	1/4"
Accessory Size	2"
Height / Length	2" / 11"
Weight	1.6 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, (2) Wrenches, Charger, Carrying Case **Related Accessories:** 48-07-2486 1/4" Cut-Off Wheel Arbor 48-66-2486 1/8" Collet & Nut Kit 49-94-2000 2" Metal Cut-Off Wheel





M12FUEL **1/2" Digital Torque Wrench** w/ ONE-KEY[™] Kit 2466-22 (2466-20 Tool-Only) **Specifications:** Torque Range 12.5 - 150 ft-lbs RPM 0 - 100 CW: +/-2% of Full Scale / CCW: +/-3% of Full Scale Tool Accuracy (Range: 20% - 100% of Full Scale) Ratcheting Angle 4.5° Anvil Size 1/2" Ball Detent Measuring Units ft-lbs, in-lbs, Nm, kg-cm

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Certificate of Calibration, Charger, Carrying Case

23.5" / 5.7 lbs

Length / Weight



M12 FUEL **3/8" Digital Torque Wrench** w/ ONE-KEY[™] Kit

2465-22 (2465-20 Tool-Only) **Specifications:**

-	
Torque Range	10 – 100 ft-lbs
RPM	0 - 100
Tool Accuracy	CW: +/-2% of Full Scale / CCW: +/-3% of Full Scale (Range: 20% – 100% of Full Scale)
Ratcheting Angle	4.5°
Anvil Size	3/8" Ball Detent
Measuring Units	ft-lbs, in-lbs, Nm, kg-cm
Length / Weight	23.3" / 5.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Certificate of Calibration, Charger, Carrying Case













M12[™] Spot Polisher Kit 2438-22X, 2438-22 (2438-20 Tool-Only)

Specifications:

-	
Polishing RPM	0 – 2
Sanding RPM	0 – 8
Length / Weight	5.1" /

2,800 3,300 / 2.4 lbs



Includes: 2438-22X (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; 2438-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; All Kits Include: 5 Pc Accessory Pack, Side Handle, Charger, Soft Carrying Case



Low Speed Tire Buffer Kit

2409-22 (2409-20 Tool-Only) tions:

	Specificat
7	

DRIVE CONTROL™	2-Mode
Collet	7/16" Quick Change
RPM (Buffing)	0 - 2,500
RPM (Drilling)	0 - 1,200
Length / Weight	10.1" / 1.8 lbs



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery, Quick Change Adapter, Charger, Carrying Case **Related Accessories**: **49-93-2410** 2" Flared Contour Buffing Wheel **49-93-2409** 2-1/2" Flared Contour Buffing Wheel



RPM 3,600 Bevel Capacity 50° Cut Capacity 1-5/8" at 90°; 1-1/8" at 45°	M12 FUEL 5-3/8" Circ 2530-21XC (2530-20 Specification	Cular Saw Tool-Only)	Kit	
Cut Capacity 1-5/8" at 90°; 1-1/8" at 45°	RPM	3,600	12.000	
	Bevel Capacity	50°		
	Cut Capacity	1-5/8" at 90°; 1-	-1/8" at 45°	
Arbor 10 mm	Arbor	10 mm		
Blade Guards Aluminum	Blade Guards	Aluminum		
Weight 6.2 lbs	Weight	6.2 lbs		

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Circular Saw Blade, Wrench, Charger, Contractor Bag





M12 FUEL HACKZALL® One-Handed **Reciprocating Saw Kit**

2520-21XC (2520-20 Tool-Only) Specifications

÷	specifications:		and the second
	SPM	0 – 3,000	
	Stroke Length	5/8"	
	Keyless Blade Clamp	QUIK-LOK [™] (Accepts all SAWZALL [®] Blades))
	Length / Weight	13.3" / 4.1 lbs	

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack. Charger, Contractor Bag

M12[™] HACKZALL[®] One-Handed **Reciprocating Saw Kit**

2420-22, 2420-21		
Specificatio		
SPM	0-3,000	
Stroke Length	1/2"	• •

Keyless QUIK-LOK™ Blade Clamp (Accepts all SAWZALL® Blades) 11.0" / 2.6 lbs Length / Weight

Includes: 2420-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; **2420-21** (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Charger, Contractor Bag

M12[™] High Performance Jig Saw Kit

2445-21 (2445-20 Tool-Only)				
Specifications:				
SPM	0 – 2,800			
Stroke Length	3/4"			
Bevel Capacity	45° (Positive Locks at 90° and 45°)			
Blade Clamp	QUIK-LOK [™] T-Shank			

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Anti-Splintering Insert, Non-Marring Shoe, Charger, Contractor Bag

M12	FU	IEL.
0		

Length / Weight

Oscillating M	ulti-Tool Kit	-
2526-21XC (2526-20 Too	I-Only)	
Specifications:		-
Speed Settings	12	
OPM	10,000 - 20,000	
Oscillation Angle	3.9°	

8.8" / 4.2 lbs

Ì			(5) 0
	Length / Weight	13" / 3.2 lbs	
	LED Light	Yes	
	Tool-Free Accessory Change	Yes	

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (5) Sanding Sheets, (1) Sanding Pad, (1) Wood Cutting Blade, Charger, Contractor Bag

M12[™] Oscillating Multi-Tool Kit

2/26-22 2/26-21	(2426-20 Tool-Only)
2420-22, 2420-21	(2+20-20 1001-0111y)

Specifications:

opeeniealienei			
Speed Settings	12	8	
OPM	5,000 - 20,000		
Length / Weight	10.9" / 2.1 lbs		

Includes: 2426-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; 2426-21 (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Charger, Contractor Bag

M12 FUEL HATCHET[™] 6" Pruning Saw Kit 2527-21 (2527-20 Tool-Only) Specifications: 6' Bar Length Chain Gauge .043" Chain Pitch 3/8" Low Profile



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, 6" Oregon® Bar & Chain, Scrench, Scabbard, Charger Related Accessories:

49-16-2732 6" Saw Chain 49-16-2733 6" Guide Bar



MIZELEL **Compact Band Saw Kit**

2529-21XC (2529-20 Tool-Only) Specifications:			
	SFPM	0 – 570	
	Blade Size	30-9/16"	
	Cut Capacity	2-1/2" x 2-1/2"	
	LED Light	Yes	
	Hang Hook	Yes	
	Reamer Attachment	Yes	

Compatibility

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, 12/14 TPI Compact Extreme Thin Metal Band Saw Blade, Charger, Contractor Bag Related Accessories:

49-90-2029 Compact Band Saw Reamer Attachment **48-39-0630** 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk 48-39-0631 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk 48-39-0635 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk 48-39-0636 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk 48-39-0637 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk 48-39-0639 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk



Sub Composi	
Sub-Compact Saw Kit	•

2429-21XC (2429-20 Tool-Only) Specifications:

opeenieationei		COMPLIANCE
SFPM	280	OSHA
Blade Size	27"	SOLUTION
Cut Capacity	1-5/8" x 1-5/8"	Meets OSHA Guarding
Length / Weight	11.0" / 6.7 lbs	Requirements. Suitabl for One-Handed Use.

Includes: (1) M12[™] REDLITHIUM[™] XC3.0 Battery Pack, 18 TPI Sub-Compact Portable Band Saw Blade, Charger, Carrying Case **Related Accessories: 48-39-0572** 18 TPI Sub-Compact Portable Band Saw Blades (3 pk) **48-39-0711** 12/14 TPI Extreme Metal Sub-Compact Portable

M12 FUEL **3"** Compact Cut-Off Tool Kit

2522-21XC (2522-20 Tool-Only)

Specifications:

Band Saw Blades (3 pk)

Blade Size	3"
RPM	20,000
Arbor Size	3/8"
Cut Depth	0.64"
Blade Rotation	Reversible
Length / Weight	8.9" / 2.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Dust Accessory Shoe, (3) Accessory Blades (Metal Cut-Off, Carbide Abrasive, Diamond Tile), Blade Wrench, Charger, Contractor Bag

M12[™] Rotary Tool Kit

2460-21 (2460-20 Tool-Only)



Speed Settings	6
RPM	5,000 - 32,000
Collet	1/8", Universal
Length / Weight	9.5" / 1.3 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, (5) Cutting Wheels, Mandrel, Wrench, Charger, Soft Carrying Case **Related Accessory:** 49-94-1500 5 Pc Reinforced Cut-Off Wheels

M12[™] 10 oz Caulk & **Adhesive Gun Kit**

2441-21 (2441-20 Tool-Only) Specifications

400 lbs
0 – 29
6
Yes
4.1 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 10 oz Carriage, M12[™] 10 oz Plunger Rod and Piston Assembly, Charger

M12[™] 20 oz Aluminum Barrel Sausage **Style Caulk & Adhesive Gun Kit**

400 lbs	
0 – 29	
6	- 1
Yes	-
4.9 lbs	
	0 – 29 6 Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M12[™] 20 oz Plunger Rod and Piston Assembly, Nozzle, Charger

PORTABLE PRODUCTIVITY M12



M12[™] Quart Caulk & Adhesive Gun Kit 2444-21

Specifications:

-	
Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.5 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Quart Carriage, M12[™] Quart Plunger Rod and Piston Assembly, Charger



Caulk Gun Accessories

Compatible with 2441-21, 2442-21, 2444-21
31-12-0700 Caulk Gun Nozzle – Black
48-08-0900 M12 [™] 10 oz Caulk and Adhesive Gun Conversion Kit
48-08-0905 M12 [™] 20 oz Aluminum Barrel Sausage Style
Caulk and Adhesive Gun Conversion Kit
48-08-0910 M12 [™] Quart Caulk and Adhesive Gun Conversion Kit
48-08-1091 20 oz Aluminum Barrel Kit
48-08-1096 20 oz Clear Barrel Kit

M12[™] Grease Gun Kit

2446-21XC (2446-20 Tool-Only)

Specifications:

Output Pressure	Over 8,000 PSI	
Run-Time	Up to 7 Grease Cartridges Per Charge	
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction	
Air Bleeder Valve	Yes	and the second se
Weight	7.2 lbs	

Includes: (1) M12[™] REDLITHIUM[™] XC3.0 Battery Pack. 36" Flex Hose with Spring Guard, Grease Coupler, Charger, Carrying Case

M12[™] Soldering Iron Kit

2488-21 (2488-20 Tool-Only)



Specifications:

Max Temperature	750°F
Heat Output	90 Watts
Heat-Up Time	18 Seconds
Heat Indicator	Yes
Interchangeable Tips	Chisel and Point
Length / Weight	11.6" / 0.9 lbs



Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Chisel Tip, Pointed Tip, Charger, Carrying Case

M12[™] Cable Stapler Kit

2448-21 (2448-20 Tool-Only)

Specifications:

Firing Mode	Sequential
Magazine Capacity	45
Magazine Loading	Front Load
Run-Time	1,200 Staplers per Charge on M12™ CP2.0 Battery
Length / Weight	6.5" / 5.0 lbs



Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Charger, Carrying Case Related Accessory: MNM1-600 1" Insulated Cable Staples





M12[™] Cable Stripper Kit

2435CU-21S, 2435AL-21, 2435X-21 (2435-20 Tool-Only) **Specifications:**

Variable Speed Trigger	Yes	
Tool Free Depth Gauge	Yes	
Compatible Bushing Types	Industry Standard Quick-Change	
Dimensions (L x W x H)	8.6" x 2.8" x 11.5"	
Weight	3.6 lbs	

Includes: 2435CU-21S 1/0 AWG - 750 MCM Cu THHN / XHHW Bushings; 2435AL-21 1/0 AWG - 750 MCM AI THHN / XHHW Bushings; 2435X-21 1/0 AWG - 500 MCM Cu RHW / RHH / USE Bushings; All Kits Include: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Reference Available Bushings on Pg. 66



M12[™] 600 MCM Cable Cutter Kit

2472-21XC (2472-20 Tool-Only)

Specifications:		0
Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable	
Jaw Opening	1-7/16"	
Two-Speed	Yes	-
Length / Weight	10.5" / 6.7 lbs	

Includes: (1) M12[™] REDLITHIUM[™] XC3.0 Battery Pack,

Charger, Carrying Case Related Accessory: 48-44-0410 M12[™] 600 MCM Cable Cutter Blade

M12[™] Plastic Pipe Shear Kit

2470-21 (2470-20 Tool-Only)

Length / Weight

Specifications:	. 27	
Cut Capacity	Up to 2" Schedule 80 PVC	
Torque	1,900 in-lbs	
Blade	3 mm Reinforced Stainless Steel	

14.4" / 4.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger Carrying Case Related Accessory: Pipe Shear Blade 48-44-0405 M12"

M12[™] Copper Tubing **Cutter Kit**

2471-22, 2471-21 (247	1-20 Tool-Only)	
Specifications		
Cut Capacity	3/8" – 1" (1/2" – 1-1/8" O.D.)	
Tubing Type	M, L and K Copper	
RPM	500	
Length / Weight	14.0" / 3.2 lbs	

Includes: 2471-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; 2471-21 (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Charger, Carrying Case **Related Accessory:** 48-38-0010 Copper Cutter Wheel (2 pk)



MIZELEL ProPEX® Expander Kit w/ 1/2" - 1" RAPID SEAL **ProPEX® Expander Heads** 2532-22 (2532-20 Tool-Only)

Specifications:

Capacity	3/8" – 1"
Auto Rotate	Built-In
Trigger	Dual Actuating
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	4.5 lbs

Includes: (3) ProPEX[®] Expander Heads w/ RAPID SEAL™ (1/2", 3/4", 1"), ProPEX® Expander Cone Grease, Carrying Case; 2532-22 (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger **Related Accessories:**

49-16-2414 1/2" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2415 5/8" ProPEX® Expander Head w/ RAPID SEAL" 49-16-2416 3/4" ProPEX® Expander Head w/ RAPID SEAL" 49-16-2418 1" ProPEX® Expander Head w/ RAPID SEAL"

M12TM ProPEX[®] Expansion Tool Kit

2432-22 (2432-20 Tool-Only)

Spec	ifica	tions:
------	-------	--------

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™ / Uponor
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs

Includes: (3) ProPEX® Expansion Heads (1/2", 3/4", 1"),

ProPEX® Tool Cone Grease, Carrying Case; 2432-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger **Related Accessories:** 49-08-2400 ProPEX® Expander Cone Grease 49-16-2403 3/8" ProPEX® Expansion Head 49-16-2404 1/2" ProPEX® Expansion Head 49-16-2405 5/8" ProPEX® Expansion Head 49-16-2406 3/4" ProPEX® Expansion Head 49-16-2408 1" ProPEX® Expansion Head

M12[™] PEX Expansion Tool Kit 2474-22

Specifications

Specifications:		
Capacity	3/8" – 1"	
Auto-Rotate	Built-In	
Head Compatibility	3/8" – 1" M12™	
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"	
Weight	5.0 lbs	

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, (3) PEX Expansion Heads (1/2", 3/4", 1"), PEX Tool Cone Grease, Charger, Carrying Case

Related Accessories:

49-16-2424 1/2" PEX Expander Head 49-16-2426 3/4" PEX Expander Head 49-16-2428 1" PEX Expander Head 49-08-2402 PEX Tool Grease



M12[™] TRAPSNAKE[™] 6¹ Toilet Auger Kit



Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Cable, Charger **Related Accessories:** 48-53-2576 TRAPSNAKE[™] 6' Toilet Auger Replacement Cable

48-22-2576 TRAPSNAKE™ Toilet Auger Case

M12" TRAPSNAKE" 4' Urinal Auger Kit

2574-21 (2574-20 Tool-Only)

Specifications: RPM 0 - 500Cable Lock Yes Cable Size 4' x 3/8 Cable Head Bulb Replacement Cables Available Weight 6.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Cable, Charger **Related Accessories:**

48-53-2577 TRAPSNAKE™ 4' Urinal Auger Replacement Cable 48-22-2577 TRAPSNAKE™ Urinal Auger Case



M12[™] TRAPSNAKE[™]



Includes: (1) M12[™] REDLITHIUM[™] CP1 5 Battery Pack Charger **Related Accessories:** 49-16-2576 TRAPSNAKE[™] 6' Toilet Auger 49-16-2574 TRAPSNAKE[™] 4' Urinal Auger

49-16-2573 TRAPSNAKE[™] 25' Auger w/ CABLE DRIVE[™]











TRADE FOCUSED M12



M12[™] Pipeline Locator Kit 2580-21 **Specifications:** Sonde Frequencies 512Hz, 640Hz, 8,192kHz, 33kHz, 83kHz

33kHz, 83kHz Line Trace Power Frequency 50Hx, 60Hz 10kHz – 22.7kHz Bandwidth Radio Frequency Display Type 4.3" Color LCD Display Water & Dust Rating IP65

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack. Charger, Carrying Case







571-21 (2571-20 Tool	-Only)
Specifications:	
Max Drain Line Capacity	1-1/4" – 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs

Charger, 5 Gallon Storage Bucket **Related Accessories:** 48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD[™] Plating 48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD[™] Plating 48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD[™] Plating 48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD[™] Plating

M12[™] AIRSNAKE[™]

Length / Weight



Drain Cleaning Air Gun Kit 2572B-21, (2572B-20 Tool-Only) **Specifications:** Max Drain Line 1" – 4", Capacity Up to 35 Automatic Yes Pressure Loading Variable Pressure 0 – 50 PSI Variable Yes Pressure Dial LED Light Yes

Includes: 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charge All Kits Include: 2572B-20: 1" - 2" Drain Plug, - 3" Drain Plug, 3" - 4" Drain Plug, Drain Shroud Attachment, Toilet Seal Attachment, 10" Extension, (3) Straight Connectors, 15° Offset Connector, Carrying Case

20.8" / 7.1 lbs







M12" FORCE LOGIC" **Press Tool Kit** 2473-22 (2473-20 No Jaw Kit) oti

Specifications:	
Capacity	1/2" – 1-1/2" Varies by Material
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Length / Weight	12.8" / 3.8 lbs

Includes: 2473-22 (3) Jaws (1/2", 3/4", 1"); 2473-20 (No Jaws Included): All Kits Include: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Charger, Carrying Case **Related Accessories:** 49-16-2450 1/2" CTS-V Press Jaw 49-16-2451 3/4" CTS-V Press Jaw 49-16-2452 1" CTS-V Press Jaw 49-16-2453 1-1/4" CTS-V Press Jaw 49-16-2450B 1/2" IPS-P Press Jaw 49-16-2451B 3/4" IPS-P Press Jaw 49-16-2452B 1" IPS-P Press Jaw 49-16-2451C 1/2" PEX-Crimp Press Jaw **49-16-2453C** 3/4" PEX-Crimp Press Jaw 49-16-2454C 1" PEX-Crimp Press Jaw 49-16-2455C 1-1/4" PEX-Crimp Press Jaw 49-16-2456C 1-1/2" PEX-Crimp Press Jaw 49-16-2496B 1/2"-1" IPS-P Press Jaw Kit

M12[™] No-Hub Driver Kit

2455-22 (2455-20 Tool-Only) Specifications:

Specifications:	
Torque Settings (3-Mode)	60 in-lbs / 80 in-lbs / Drill
RPM	0 – 750
Chuck Type	1/4" Hex
Calibration Interval	25,000 Cycles (LED Indicator)
Weight	2.7 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, (3) SHOCKWAVE Impact Duty[™] Nut Drivers (1/4", 5/16", 3/8"), Charger, Carrying Case

M12[™] M-SPECTOR FLEX[™] 3 ft Inspection Camera Cable w/ PIVOTVIEW™ Kit 2317-21

Spe	cifica	ations:	

specifications.	
Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Head Movement	Up to 270° PIVOTVIEW™ Camera
Cable Length	3 ft
Wireless Distance	Up to 15 ft

23 SD Card USP Coble Cl Cl C CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case

M12[™] M-SPECTOR FLEX[™] 9 ft Inspection **Camera Cable Kit** 2316-21 Specifications: 3.5" High-Resolution LCD Screen Size Camera Resolution 640 x 480 Camera Head Diameter 12.5 mm (0.49") Cable Length 9 ft Wireless Distance Up to 15 ft Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case

M12[™] M-SPECTOR FLEX[™] **3 ft Inspection Camera** Cable Kit

Specifications:

2315-21

Cable Length

Wireless Distance

3.5" High-Resolution LCD Screen Size 640 x 480 Camera Resolution

Camera Head Diameter 12.5 mm (0.49") 3 ft Up to 15 ft

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case

M-SPECTOR FLEX[™] Inspection Camera Accessories

Compatible with 2317-21, 2316-21, 2315-21 48-53-0155 M-SPECTOR FLEX[™] 3 ft Inspection Camera Cable w/ PIVOTVIEW™ 48-53-0151 M-SPECTOR FLEX[™] 9 ft Inspection Camera Cable 48-53-0150 M-SPECTOR FLEX[™] 3 ft Inspection Camera Cable



M12[™] M-SPECTOR 360[™] **Rotating Inspection** Scope Kit **Specifications:**

2.7" High-Resolution LCD Screen Size **Display Resolution** 320 x 240 Camera Head Diameter 9 mm (0.35") Cable Length 3 ft LED Brightness 4 LEDs, 5 Settings

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Contractor Bag

	ECTOR 360™ og Inspection
2314-21	
Specifications	\$I
Screen Size	2.7" High-Resolution LCD

Display Resolution 320 x 240 Camera Head Diameter 9 mm (0.35") Cable Length 9 ft

LED Brightness 4 LEDs, 5 Settings

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Contractor Bag

M-SPECTOR 360[™] Rotating Inspection Scope Accessories Compatible with 2313-21, 2314-21

48-53-0112 3 Pc Accessory (Includes Hook, Magnet, Mirror Attachments) 48-53-0113 Pipe Guide Accessory



M12[™] 12:1 Infrared TEMP-GUN[™]

2278-20 Tool-Only

Distance-to-Spot Ratio	12:1
Temperature Range	-22°F – 1,022°F (-30°C – 550°C)
Basic Accuracy	+/-1.8%
Max/Min/Avg/Dif	Yes
High/Low Alerts	Yes
Emissivity	Fixed, .95
Drop Test	6 ft

Battery and Charger Sold Separately

M12[™] Green Laser Kit -**360° 3-Plane** 3632-21

Specifications:	
Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Target, Charger, Carrying Case



M12[™] Green Laser Kit -**Cross Line & Plumb Points** 2600 01 (2600 00 T- -! O

3622-21 (3622-20 Tool-0	Only)
Specifications: Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) M12[™] REDLITHIUM[™] CP3.0 Battery Pack, Target, Charger, Carrying Case



USB Rechargeable Green Laser -Cross Line & Plumb Points 3522-21



Specifications:

Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m



Includes: (1) REDLITHIUM[™] USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Riser, Carrying Case

USB Rechargeable Green Laser -Cross Line 3521-21



Specifications:

-	
Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m



Includes: (1) REDLITHIUM[™] USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case

USB Rechargeable Green Laser -3-Point 3510-21

Specifications

specifications.	1
Working Range	150 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m



Includes: (1) REDLITHIUM[™] USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case

Laser Accessories

Compatible with 3632-21, 3622-21, 3522-21, 3521-21, 3510-21 48-35-1211 165' Laser Line Detector

- 48-35-1411 72" Laser Tripod
- 48-35-1311 360° Laser Bracket
- 48-35-1111 Responsive Laser Alignment Target
- 48-35-1313 Laser Track Clip





M12[™] ROVER[™] Service & Repair Flood Light w/ USB Charging

Specifications	1	1
Lumens	700 / 250	
Modes	High, Low	
Run-Time (w/ M12™ XC4.0 Battery)	8 hr / 24 hr	
Water & Dust Rating	IP54	
USB Charger	2.1A USB Charging Port for External Devices	
Battery and Charger So	ld Separately	- Y

•	
s: 🖡	
1,350 / 600	
High, Low	
FINISHGUARD [™] to Resist Wear & Provide Lasting Protection	
48" Collapsed, 78" Fully Extended / 2.2 lbs	
	High, Low FINISHGUARD [™] to Resist Wear & Provide Lasting Protection 48" Collapsed, 78" Fully

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Charger

M12[™] Metal Flashlight Kit

2355-21 (2355-20 Tool-Only) -

Specifications:		
Lumens	800 / 325 / 800	
Modes	High, Medium, Strobe	
Beam Distance	375 yd / 343 m	
Beam Focus	Slide, Spot/Flood	
Water & Dust Rating	IP54	
Structure	6000 Series Aluminum, Type II Anodize Finish	
Length / Weight	9.0" / 1.2 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Lanyard, Charger

M12[™] Spot Light

2353-20 Tool-Only Specifications:	
Lumens 750 / 400 / 750	
Modes High, Low, Strobe	
Beam Distance 700 yd / 640 m	
Water & Dust Rating IP54	
Length / Weight 6.1" / 1.4 lbs	

Battery and Charger Sold Separately

Includes: Lanyard

M12[™] Trouble Light w/ USB Charging 2362-20 Tool-Only

Specifications:

-		
Lumens	400 / 200 / 40 / 400	
Modes	High, Medium, Low, Strobe	
Run-Time	Up to 67 Hours	
Beam Pattern	Adjustable Task – Area	155
Water & Dust Rating	IPX4	
Hands-Free	2 Hooks for Hanging	•
USB Charger	2.1A USB Charging Port for External Devices	
Length / Weight	10.5" / 1.0 lb	Y V
Battery and Charger Sol	d Separately	USB

M12[™] ROVER[™] Mounting Flood Light 2364-20 Tool-Only

Specifications

Specifications:		193
Lumens	1,000 / 400 / 200	
Modes	High, Medium, Low	
Hands-Free	Integrated Magnet, Spring Loaded Clamp	
Water & Dust Rating	IP54	
Length / Weight	7.5" / 2.2 lbs	

Battery and Charger Sold Separately



M12 [™] Under 2126-21 (2126-20 Tool Specifications:	-Only)	
Lumens	1,200 / 800 / 600	
Modes	High, Medium, Low	
Water & Dust Rating	IP54	
Mounting	Magnetic Base	
Battery and Charger Sold Separately		

Includes: 2126-21 M12[™] Underbody Light, (1) M12[™] REDLITHIUM[™]

XC4.0 Battery Pack, Charger; 2126-20 M12™ Underbody Light

M12[™] Stick Light

2351-20 Tool-Only

Specifications:

Lumens	220
Hands-Free	Multi-Position Stainless Steel Hook
Water & Dust Rating	IP54
Length / Weight	9.3" / 0.6 lbs

Battery and Charger Sold Separately

Related Accessory:

49-24-2351 M12™ Stick Light Magnet Holds light to metal surfaces for hands-free use



100 Lumens Hands-Free Integrated Magnet 90° Head Rotation

Battery and Charger Sold Separately



M12[™] Heated TOUGHSHELL[™] **Jacket Kit**

Black 204B-21 (S - 3X)*, 204B-20 Jacket-Only 204B Gray 204G-21 (S - 3X)*, 204G-20 Jacket-Only 204G Red 204R-21 (S - 3X)*, 204R-20 Jacket-Only Blue 204BL-21 (S - 3X)*, 204BL-20 Jacket-Only Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 12 Hours
Battery Pocket	Battery Pass-Thru, Front or Back Pocket
Outer Material	TOUGHSHELL [™] Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP3.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

M12[™] Women's Heated **SOFTSHELL Jacket Kit**

Black 232B-21 (S - 2X)*, 232B-20 Jacket-Only **Specifications:**

	Heat Zones	3 (Back, Collar, Pockets)	
	Heat Settings	3 (High, Medium, Low)	
	Run-Time	Up to 8 Hours	7
	Outer Material	Polyester SOFTSHELL	
	Wind / Water Resistant	Yes	
1	Washer / Dryer Safe	Yes	

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

M12[™] Heated QUIETSHELL Jacket Kit

Camo 222C-21 (S - 3X)*, 222C-20 Jacket-Only 222C **Specifications:**

Heat Zones	3 (Chest, Back, Pockets)	
Heat Settings	3 (High, Medium, Low)	
Run-Time	Up to 8 Hours	
Outer Material	QUIETSHELL Stretch Polyester	
Wind / Water Resistant	Yes	
Washer / Dryer Safe	Yes	
Realtree EDGE © 2021 of Jordan Out	door Enterprises, Ltd., all rights reserved	

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

25









M12[™] Heated AXIS[™] Layering System w/ HYDROBREAK[™] Rain Shell Kit Black/Gray 203RN-21 (S - 3X)*

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	Polyurethane Laminate / Ripstop Polyester
Waterproof	10K mm
Washer / Dryer Safe	Yes



Includes: HYDROBREAK[™] Rain Shell, M12[™] Heated AXIS[™] Jacket, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source







M12 [™] Heated AXIS [™] Layeri	ng System
w/ GRIDIRON [™] Work Shell	Kit
Black 255B-21 (S – 3X)*	255B

Specifications: Heat Zones 3 (Chest, Back, Shoulders) Heat Settings 3 (High, Medium, Low) Run-Time Up to 8 Hours Outer Material GRIDIRON[™] Ripstop Polyester Insulation 60G Body / 40G Sleeve Washer / Dryer Safe Yes



Includes: GRIDIRON[™] Work Shell, M12[™] Heated AXIS[™] Jacket, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source





M12[™] Heated AXIS[™] **Jacket Kit**

Black 203B-21 (S - 3X)*, 203B-20 Jacket-Only Olive Green 203OG-21 (S - 3X)*, 203OG-20 Jacket-Only **Specifications:**

Heat Zones	3 (Chest, Back, Shoulders)	
Heat Settings	3 (High, Medium, Low)	
Run-Time	Up to 8 Hours	
Outer Material	AXIS [™] Ripstop Polyester	
Wind / Water Resistant	Yes	
Washer / Dryer Safe	Yes	

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



M12[™] Women's Heated AXIS[™] **Jacket Kit**

Black 233B-21 (S – 2X)*, 233B-20 Jacket-Only			
	Heat Zones	3 (Chest, Back, Shoulders)	
	Heat Settings	3 (High, Medium, Low)	
	Run-Time	Up to 8 Hours	
	Outer Material	AXIS [™] Ripstop Polyester	_
	Wind / Water Resistant	Yes	
	Washer / Dryer Safe	Yes	

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source







Heat Zones 2 (Chest, Back)

Heat Settings 3 (High, Medium, Low) Run-Time Up to 6 Hours Outer Material AXIS[™] Ripstop Polyester Wind / Water Resistant Yes Washer / Dryer Safe Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, M12[™] Battery Holder, Charger

M12[™] Women's Heated AXIS[™] Vest Kit

Black 333B-21 (S – 2X)*, 333B-20 Vest-Only		
Specifications:		
Heat Zones	2 (Chest, Back)	
Heat Settings	3 (High, Medium, Low)	
Run-Time	Up to 6 Hours	

null-fille	0010010015
Duter Material	AXIS™ Ripstop Polyester
Nind / Water Resistant	Yes
Nasher / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, M12[™] Battery Holder, Charger

M12[™] Heated Hoodie Kit

Black 302B-21 (S - 3X)*, 302B-20 Hoodie-Only Gray 302G-21 (S - 3X)*, 302G-20 Hoodie-Only Red 302R-21 (S - 3X)*, 302R-20 Hoodie-Only Navy Blue 302BL-21 (S - 3X)*, 302BL-20 Hoodie-Only Specifications:



Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, M12[™] Battery Holder, Charger



USB Rechargeable WORKSKIN[™] Heated Base Layer Kit 405B-21 (S - 3X)*

Specifications:

Heat Zones	2 (Chest, Back)	
Heat Settings	2 (High, Low)	
Run-Time	Up to 3 Hours	
Material	WORKSKIN [™] Midweight Fabric Construction	
Washer / Dryer Safe	Yes	

Includes: (2) REDLITHIUM[™] USB 3.0 Batteries, USB Charger/Controller, Heavy Duty Cord and Wall Plug

USB Rechargeable Heated Gloves Kit

561-21 (M - XL)* Specifications

specifications.		1000
Heat Zones	2 (Fingers, Back of Hand)	
Heat Settings	3 (High, Medium, Low)	
Run-Time	Up to 6 Hours	POWERED
Material	GRIDIRON [™] Ripstop Polyester	REDL
Wind / Water Resistant	Yes	RE

Includes: (2) REDLITHIUM[™] USB Batteries, (2) USB Charger/Controllers, Heavy Duty Cord and Wall Plug

M18[™] / M12[™] Wireless **Jobsite Speaker** 2891-20 Tool-Only **Specifications:** Modes Bluetooth®, AUX (Cable Not Included) 🚯 🛙 Blu Bluetooth® Range 100 ft USB Charging Port 2.1A USB Charging Port for External Devices Battery and Charger

Sold Separately Includes: AC Adapter



M12[™] Radio + Charger

2951-20 Tool-Only **Specifications:** AM, FM, Bluetooth® Modes Bluetooth® Range 100 ft 2.1A USB Charging Port for USB Charging Port External Devices



Includes: AC Adapter, (2) AAA Batteries



M12[™] Wireless Jobsite Speaker

External Devices

2592-20 Tool-Only S

Battery and Charger Sold Separately

Specifications:	
Modes	Bluetooth [®] , AUX (Cable Not Included)
Bluetooth [®] Range	30 ft
USB Charging Port	2.1A USB Charging Port for



Battery and Charger Sold Separately



TRADE FOCUSED M12

M12[™] Compact Inflator Kit

2475-21XC (2475-20 Tool-Only) Specifications:

-	
PSI Rating	0 – 120 PSI
Hose Length	26"
Gauge Accuracy	+/- 3%
Duty Cycle	50% at 10 Minutes On and 10 Minutes Off
Height / Weight	7.5" / 2.2 lbs



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (4) Attachments (Ball Inflation Needle, Presta Chuck, Inflator Nozzle, Schrader Chuck), Charger



M12 [™] Comp	act Spot	Blower
0852-20 Tool-Only		
Specifications	51	
Air Volume	175 CFM	
Air Velocity	110 MPH	
Length (without 10" extensio	15" n)	
Height	8.5"	
Width	4.7"	

Battery and Charger Sold Separately

Includes: Extension Nozzle, Rubber Nozzle, Wide Sweeping Nozzle

3.3 lbs

	M12 FUEL 1.6 Gallon	Wet/Dry Vacuum	n Kit
	0960-21 (0960-20 To Specification		
_	Air Volume	45 CFM	
ietooth	Suction (H ₂ 0)	42"	
	Run-Time	Up to 26 Min	

Weight













כ	BY

5' Flexible Hose; **0960-21:** (1) M12[™] REDLITHIUM[™] XC6.0 Battery Pack, Charger **Related Accessories:** 49-90-1900 HEPA Filter 49-90-2015 Foam Wet Filter 49-90-2017 1-1/4" Round Brush Tool 49-90-2018 Vacuum Power Tool Adapter



M12 [™] Compac	et Vacuum	
0850-20 Tool-Only		
Specifications:		
Air Volume	33 CFM	
Suction (H ₂ 0)	15"	
Run-Time (w/ M12™ XC4.0 Battery)	Up to 29 mins	
Inlet Diameter	1-1/4"	
Weight	2.3 lbs	

Battery and Charger Sold Separately

Includes: Utility Nozzle, Extension Wand, Crevice Tool, Filter Assembly **Related Accessory:** 49-90-1950 Filter





M12[™] Power Source

49-24-2310	
Specifications:	1
USB Charging Port	2.1A USB Charging Port for External Devices
On-Board Fuel Gauge	Yes
Powered By	All M12 [™] Batteries

Battery Sold Separately

Powers all MILWAUKEE[®] M12[™] Heated Gear

Related Accessory: 48-59-1201 M12™ Compact Charger and Power Source

M12[™] REDLITHIUM[™] XC4.0 **System Starter Kit** 48-59-2440

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Charger

M12[™] REDLITHIUM[™] CP2.0 **System Starter Kit** 48-59-2420

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Charger



M12 [™] Four Bay Sequential Ch		THE HILL
48-59-1204		
Specifications:		196
Compatibility	All M12 [™] Batteries	-
Charge Sequence	Sequential (First In, First Charged)	
Integrated Hang-Holes	Yes	
Skip Button	Manually Designate which Battery Charges First	
On-Board Indicator Light	Yes	
Cell Voltage Monitoring	Yes	

Batteries Sold Separately

M18[™] & M12[™] Rapid Charge Station

48-59-1807 Specifications:

•	specifications:			
	Compatibility	All M18 [™] and M12	™ Batteries	
	Charge Sequence	Charges 3 Batter	ies Simultaneously	Leve
	Charge Speed	Charges Individua up to 40% Faster		
	Capacity	Holds (3) M18™ and	d (3) M12™ Batteries	
	Integrated Hang-Holes	Yes		
	Cell Voltage Monitoring	Yes		
	Pass-Through Plug	Yes	1	

M18[™] & M12[™] Rapid Charger

Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faste
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes

M18[™] & M12[™] Multi-Voltage Charger

pecifications:		O To
Compatibility	All M18 [™] and M12 [™] Batteries	
Charge Sequence	Sequential (First In, First Charged)	
Integrated Hang-Holes	Yes	
On-Board Indicator Light	Yes	
Cell Voltage Monitoring	Yes	

M18[™] & M12[™] Vehicle Charger 48-59-1810 **Specifications:**

Compatibility All M18[™] and M12[™] Batteries Charge Sequence Sequential (First In, First Charged) On-Board Indicator Light Yes Cell Voltage Monitoring Yes Batteries Sold Separately

M12[™] Compact Charger and Power Source 48-59-1201 **Specifications:** Compatibility All M12[™] Batteries USB Charging Port 2.1A USB Charging Port for External Devices On-Board Indicator Light Yes Cell Voltage Monitoring Yes Charges By USB Port or AC Outlet Battery Sold Separately

Includes: 3 ft Micro-USB Cable and 2.1A Wall Charger

M12[™] Charger 48-59-2401 **Specifications:** All M12[™] Batteries Compatibility Integrated Hang-Holes Yes On-Board Indicator Light Yes Cell Voltage Monitoring Yes Battery Sold Separately







29 Batteries Sold Separately



30



PERSONAL LIGHTING

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to ADAPT, PERFORM AND SURVIVE. Built to withstand the toughest conditions on and off the jobsite, MILWAUKEE® lights combine the best cordless battery and LED technology delivering convenient, portable solutions that increase productivity and safety.



REDLITHIUM[®]USB

ALL DAY RUN-TIME^{*}

MORE RECHARGES **3X** FASTER CHARGE TIME

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to get maximum performance and user driven innovation with REDLITHIUM™ USB Personal Lights. REDLITHIUM[™] USB lights combine the best in cordless battery and LED technology to deliver High Output with ALL DAY RUN-TIME, More Recharges and 3X Faster Charge Time. Get more from REDLITHIUM" USB with one battery that powers multiple solutions.

POWERED BY





RECHARGEABLE

ALL NEW SUB-COMPACT RECHARGEABLE LIGHTS

Where work makes size critical, MILWAUKEE® Rechargeable Personal Lights leverage a built-in battery and USB charging to deliver high performance output and rechargeable capabilities in the most compact personal lights.



2111-21

REDLITHIUM[™] USB Hard Hat Headlamp Kit

Lumens	475 / 300 / 300, 150, 25
Modes	Spot/Flood, Spot – High, Flood – High/Medium/Low
Water & Dust Rating	IP54
Powered By	REDLITHIUM [™] USB



REDLITHIUM[™] USB Low-Profile Headlamp Kit 2115-21

Lumens	600 / 350 / 125 / 25
Modes	High, Medium, Low, Eco
Battery Position	Rear
Water & Dust Rating	IP54
Powered By	REDLITHIUM [™] USB

Includes: (1) REDLITHIUM[™] USB Battery, 2 ft Heavy Duty USB Cord, (4) Hard Hat Clips

REDLITHIUM[™] USB BEACON[™] Hard Hat Light Kit 2116 04

2116-21	
Lumens	600 / 400, 200, 25 / 400
Modes	Spot/Flood, Flood – High/Medium/Low, Spot – High
BEACON™ Mode	Steady & Blinking
Spot Beam Distance	125 m

Water & Dust Rating IP54 REDLITHIUM[™] USB Powered Bv

Includes: (1) REDLITHIUM[™] USB Battery, 2 ft Heavy Duty USB Cord, (2) Hard Hat Clips





RECHARGEABLE



31





REDLITHIUM[™] USB 1,100L Twist Focus Flashlight

2161-21

Lumens	1,100 / 600 / 100	
Modes	High, Medium, Low	
Spot Beam Distance	175 m	
Beam Focus	Twist Focus, Spot/Flood	
Water & Dust Rating	IP54	
Powered By	REDLITHIUM™ USB	· •





Includes: (1) REDLITHIUM[™] USB 3.0 Battery, 2 ft Heavy Duty USB Cord

800L Compact Flashlight

800 / 100

High, Low

Bullseye Beam

REDLITHIUM[™] USB

150 m

IP54

REDLITHIUM[™] USB



REDLITHIUM[™] USB ROVER[™] Magnetic Flood Light Kit

Includes: (1) REDLITHIUM™ USB Battery Pack,

2112-21

2160-20

Lumens Modes

Beam Focus

Powered By

Spot Beam Distance

Water & Dust Rating

2 ft Heavy Duty USB Cord

Lumens	445 / 100	2
Modes	High, Low	1. S.
Hands-Free	Dual Magnets	
Water & Dust Rating	IP54	
Height	6.0"	POWERED BY
Powered By	REDLITHIUM [™] USB	BECHARGE
		AECHAAGE

Includes: (1) REDLITHIUM[™] USB Battery. 2 ft Heavy Duty USB Cord









Lumens	500 / 400 / 100
Modes	Spot – High, Flood – High, Flood – Low
Spot Beam Distance	155 m
Pivoting Head	110°
Water & Dust Rating	IP54
Height	6.3"
Powered By	REDLITHIUM [™] USB





Powered By Includes: (1) REDLITHIUM[™] USB Battery, 2 ft Heavy Duty USB Cord





REDLITHIUM[™] USB ROVER[™] Pivoting Flood Light Kit 0114 01

2114-21		
Lumens	550 / 250 / 100	
Modes	High, Medium, Low	
Pivoting Head	210°	
Water & Dust Rating	IP54	
Height	4.4"	
Powered By	REDLITHIUM™ USB	RECHAR

Includes: (1) REDLITHIUM[™] USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM[™] USB Utility Hot Stick Light Kit 2119-22

2110 22		
Lumens	350, 100	
Modes	Flood – High/Low	
kV Rating	100kV	0
Water & Dust Rating	IP67	POWERED BY
Height / Length	0.5" / 7.4"	
Powered By	REDLITHIUM [™] USB	RECHARGEABLE

Includes: (2) REDLITHIUM[™] USB Batteries, 2 ft Heavy Duty USB Cord, REDLITHIUM[™] USB Charger & Portable Power Source, 12V DC Vehicle Plug, 2.1A Wall Plug

REDLITHIUM[™] USB3.0 Battery

48-1	1-2131	

Amp Hours	3
Cell Chemistry	LITHIUM-ION
Voltage	4V

l	Startin 1
[■	

REDLITHIUM[™] USB Portable

48-59-2013

Height

2010R

Lumens Modes

Laser

Powered By

Water & Dust Rating

Includes: USB Charging Cable

Cell Chemistry

On-Board Indicator Light

Cell Voltage Monitoring

USB Charging Port

Power Source and Charger Kit

Yes

Yes

3.9"

Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger

250 / 50

IP54

High, Low

LITHIUM-ION

2.1A USB Charging Port

ŵ

USB

for External Devices

Includes: (1) REDLITHIUM[™] USB Battery, REDLITHIUM[™] USB CHARGES

Rechargeable 250L Penlight w/ Laser

Integrated Laser Pointer Built-In-Battery

Rechargeable 500L Every Day Carry Flashlight w/ Magnet 2011B

Lumens	500 / 100 / 10
Modes	High, Medium, Low
Water & Dust Rating	IP67
Hands-Free	Magnetic Mounting
Powered By	Built-In-Battery

REDLITHIUM[™] USB Portable Power Source and Charger 48-59-2012

Cell Chemistry	LITHIUM-ION
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
USB Charging Port	2.1A USB Charging Port for External Devices
Height	3.9"

USB

Includes: REDLITHIUM[™] USB Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger



Rechargeable 450L Magnetic Headlamp and Task Light 2012B

2012R			1
Lumens		500 / 100 / 10	
Modes		High, Medium, Low	
Water & I	Dust Rating	IP67	
Mounting]	Detachable Magnetic Light Head	
Powered	Ву	Built-In-Battery	

Includes: USB Charging Cable

MILWAUKEE® Penlight

2105		
Lumens	100	
Water & Dust Rating	IP67	
Height	5.4"	
Powered By	(2) AAA	

Includes: (2) AAA Batteries

MILWAUKEE® Headlamp

2103 350 / 150 / 25 Lumens Modes High, Medium, Low Impact Rating 2 m IP54 Water & Dust Rating Powered By (3) AAA

Includes: (4) Hard Hat Clips, (3) AAA Batteries

Lumens

Modes

MILWAUKEE® C I, II, III / D 1 Intrinsically Safe Spot/Flood Headlamp 2004hzl



	Medium, Flood Low
Intrinsically Safe Rating	Classes I, II, III / Division 1 Groups A – G
Impact Rating	9 ft
Water & Dust Rating	IP64
Powered By	(3) AAA

Includes: Rubber Strap, Nylon Strap, DUAL LOCK[™] Adhesive, (4) Hard Hat Clips, Hex Wrench, (3) AAA Batteries

33



MILWAUKEE® Spot/Flood Headlamp 2104



Lumens	450 / 350, 150, 25 / 350
Modes	Spot/Flood, Flood – High/Medium/Low, Spot
Spot Beam Distance	100 m
Water & Dust Rating	IP54
Powered By	(3) AAA

Includes: (4) Hard Hat Clips, (3) AAA Batteries

MILWAUKEE® 325L Focusing Flashlight 2107

Lumens	325 / 25
Modes	High, Low
Spot Beam Distance	115 m
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP67
Height	5.0"
Powered By	(3) AAA

Includes: (3) AAA Batteries

2107S Also Available, Includes Holster



ROVER [™] 2108	Magnetic Flood Light
Lumens	300 / 100
Modes	High, Low

IP54

4.8"

(2) AA

r	-	I
		L
٦		I
		I
		I
		I
I		I
I		
٠		
L		
-		

Includes: (2) AA Batteries

Water & Dust Rating

Height

Powered By





34



M12™ COMBO KITS		2 PIECE KITS				4 PIECE KIT		
		2494-22	2497-22	2577-21	2582-22	2596-22	2598-22	2498-24
Kit Tool Total	2	2	2	2	2	2	2	4
M12 FUEL [™] Low Speed Tire Buffer								
M12 FUEL [™] 1/2" Hammer Drill/Driver								
M12 [™] 3/8" Hammer Drill/Driver								
M12 FUEL [™] 1/2" Drill/Driver								
M12 [™] 3/8" Drill/Driver								
M12 FUEL [™] 1/4" Hex Impact Driver								
M12 [™] 1/4" Hex Impact Driver								
M12 FUEL [™] SURGE [™] 1/4" Hex Hydraulic Driver								
M12 [™] HACKZALL [®] Reciprocating Saw								
M12 [™] TRAPSNAKE [™] 6' Toilet Auger								
TRAPSNAKE [™] 4 ¹ Urinal Auger Extension								
M12 [™] Work Light								
Also Includes								
M12 [™] Charger								
M12 [™] REDLITHIUM [™] CP1.5 Battery Pack		2	2	1				2
M12 [™] REDLITHIUM [™] CP2.0 Battery Pack	1				1	1	1	
M12 [™] REDLITHIUM [™] XC4.0 Battery Pack	1				1	1	1	
Carrying Case								
Contractor Bag								



- **RAPID CHARGER**
- Charges All Charges All
 M18[™] and M12[™] Batteries
 Charges Batteries Sequentially (First In, First Charged)

CHARGES PACKS UP TO 40% FASTER

M12[™] REDLITHIUM[™] CP3.0/XC6.0

■ Up to 3X More Run-Time ■ Up to 20% More Power Over 2X More Life M12 **M12**



35







< ,







ALL M18" TOOLS FIT M18[®] BATTERIES 200+ TOOLS



DRIVEN TO OUTPERFORM.

For the first time in power tool history, M18 FUEL[™] products are delivering game-changing corded performance without the cord. The motors on MILWAUKEE[®] M18 FUEL[™] tools are more powerful and energy efficient – outliving any other brand. To add to the revolutionary technology, M18 FUEL[™] possesses the smartest electronics found in any power tool. REDLINK PLUS[™] electronics manage an array of power requirements across 200+ M18[™] tools using one common battery. MILWAUKEE[®] built, the M18[™] Battery delivers cleaner, more consistent power, lasts longer and delivers more run-time in the harshest jobsite conditions.





POWERSTATE[®] BRUSHLESS MOTOR

14

12

This best-in-class brushless motor works harder and lives longer than all leading competitors.

- MILWAUKEE[®] Designed and Built Brushless Motor
- Outperforms All Logding Compatito
- Leading Competitors

 Longer Motor Life



The most advanced system of hardware and software in cordless power tool electronics today.

- Most Advanced Electronic System on the Market for Maximum Performance
 Total System Communication with
- Overload Protection Increases Tool Life





LIT

118

REDLITHIUM[™] XC5.0 BATTERY PACK

M18

PERFORMANCE DRIVEN TRADE FOCUSED SYSTEM WIDE

Compatible with the entire M18[™] System, it delivers more run-time, power and recharges than the competition.

- Most Durable Pack on the Market
- Over 2X More Recharges than Leading Competitor
- Fuel Gauge Displays Remaining Charge
- Operates Below -18°C / 0°F





M18FUEL

1/2" Hammer Drill/Driver w/ ONE-KEY[™] Kit 2806-22 (2806-20 Tool-Only)

2000-22	(2000-20	1001-011
Speci	ficatio	ns:

Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
BPM	0 - 32,000
DRIVE CONTROL™	3-Mode (Customizable)
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18FUEL	
1/2" Hammer Drill/Driver Kit	4
2804-22 (2804-20 Tool-Only)	
Specifications:	

Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
BPM	0 – 32,000
Chuck Type	1/2" All Metal Ratcheting
Lenath / Weiaht	6.9" / 4.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 [™] 1/2" Hammer Drill/Driver Kit 2607-22, 2607-22CT (2607-20 Tool-Only) Specifications:		
Peak Torque	500 in-Ibs	
RPM	0 - 450 / 0 - 1,800	
BPM	0 – 28,800	

Peak RPM BPM Chuck Type

M18FUEL

1/2" Drill/Driver

2805-22 (2805-20 Tool-Only)

Specifications: Peak Torque

w/ ONE-KEY[™] Kit

Length / Weight 7.8" / 4.5 lbs **Includes: 2607-22** (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; **2607-22CT** (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; All Kits Include: Multi-Voltage Charger, Carrying Case

1/2" All Metal Ratcheting



RPM	0 - 550 / 0 - 2,000
DRIVE CONTROL [™]	3-Mode (Customizable)
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

1,200 in-lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 FUEL 1/2" Drill/Driver Kit 2803-22 (2803-20 Tool-Only) Specifications:

specifications.	
Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



Specifications:

Peak Torque	500 in-Ibs
RPM	0 - 500 / 0 - 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.5" / 3.7 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



Specifications:

Peak Torque	500 in-Ibs
RPM	0 - 450 / 0 - 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.3" / 3.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs, Multi-Voltage Charger, Carrying Case

	M18™ 3/8" Right
	Drill/Driver Kit
1000	0615 01 0615 01CT (0615 00

2615-21, 2615-21CT (2615-20 Tool-Only) Specifications:

-		
	Peak Torque	125 in-lbs
	RPM	0 - 1,500
	Clutch Settings	11 Settings plus Drill Mode
	Chuck Type	3/8" Single Sleeve
	Head Profile	3-3/4"
	Weight	4.3 lbs

3/8" Right Angle

Includes: 2615-21 (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack; **2615-21CT** (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Multi-Voltage Charger, Carrying Case

M18 "	Brushle	SS	
1/2"	Hammer	Drill/Driver	Kit
2902-22	(2902-20 Tool-O	nly)	

Specifications:	
Peak Torque	725 in-lbs
RPM	0 - 550 / 0 - 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.0" / 4.6 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC4.0 Battery Packs, Belt Clip, Side Handle, Multi-Voltage Charger, Carrying Case









M18FUEL

Mud Mixer w/ 180° Handle Kit 2810-22 (2810-20 Tool-Only)

Specifications:

RPM	0 – 550
DRIVE CONTROL™	8-Speed Dial
Handle Type	180° Rotating Handle
Chuck Type	1/2" Keyed
Length / Weight	16.6" / 7.7 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Chuck Key, Multi-Voltage Charger, Contractor Bag







M18 FUEL

HOLE HAWG[®] 1/2" Right Angle Drill Kit

2807-22 (2807-20 Tool-Only) Specifications:

opeomoditoria			
RPM	1 – 1,500		
Chuck Type	1/2" All Metal Keyed		
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"		
Built-In LED	Yes		
Length / Weight	15.6" / 7.7 lbs		

Yes

15.6" / 7.1 lbs



Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs, Chuck Key, Key Holder, Top Handle, Rapid Charger, Carrying Case



Built-In LED

Length / Weight

M18 FUE		
HOLE HA w/ QUIK-	WG® Right Angl LOK™	e Drill Kit
2808-22 (2808-2 Specificati	• *	
RPM	1 – 1,500	
Chuck Type	7/16" QUIK-LOK™	REDLITHIUM
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"	HIGH OUTPUT XC60

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs, Top Handle, Rapid Charger, Carrying Case





M18FUEL SUPER HAWG[™] 1/2" **Right Angle Drill Kit**

2809-22 (2809-20 Tool-Only) **Specifications:**

	114
RPM	0 – 1,550
Chuck Type	1/2" All Metal Keyed
Capacity	For Self-Feed Bits up to 4-5/8"; Hole Saws up to 6-1/4"
Length / Weight	20.5" / 14.4 lbs

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs, Top Handle, Side Handle, Chuck Key, Rapid Charger, Contractor Bag



M18FUEL 1-1/2" Magnetic Drill Kit

2787-22HD

Specificatio	ons:	
Capacity	1-1/2" Annular Cutter; 1/2" Twist Bit	
RPM	400 / 690	RED
Magnet	Operates Without Electricity	HIGH O
Dimensions (L x W x H)	13.8" x 7.5" x 15.5"	
Weight	30.5 lbs	

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, Rapid Charger, Carrying Case

1	Hammer v	S Max Rotary ✔/ ONE-KEY [™] K 21HD (2718-20 Tool-Only)	it and a set of the s
	Impact Energy	8.1 ft-lbs	
	RPM	0 - 380	
	BPM	0 – 2,900	SDS MAX
	Clutch	AUTOSTOP [™] E-Clutch	
	Vibration	10 m/s ²	REDLITHIUM
	2-Mode Operation	Rotary Hammer and Hammer Only	HIGH OUTPUT HD120
	Weight	19.7 lbs	

Includes: 2718-22HD (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs; 2718-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™

HD12.0 Battery Pack; All Kits Include: Side Handle, Grease Tube, Rapid Charger, Carrying Case





RPM

BPM



BPM	0 – 3,000	RED
Impact Energy	5.1 ft-lbs	HIGH O
2-Mode Operation	Rotary Hammer and H	Hammer Only
Weight	13.8 lbs	

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Side Handle, Depth Rod, Rapid Charger, Carrying Case



Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, 12V Inverter, Rapid Charger, Carrying Case

30.4 lbs



Impact Energy 3-Mode Operation Rotary Hammer, Hammer Only and Rotation Only Weight 11.2 lbs

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs, HAMMERVAC[™] Dedicated Dust Extractor, Side Handle w/ Depth Gauge, Large Diameter Dust Nozzle, Small Diameter Dust Nozzle, Rapid Charger, Carrying Case



Includes: Replacement Nozzle, HEPA Filter

RPM

BPM



Includes: 2912-22 (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs: 2912-22DE (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Packs, HAMMERVAC[™] Dedicated Dust Extractor, Large Diameter Dust Nozzle, Small Diameter Dust Nozzle;

All Kits Include: Side Handle w/ Depth Rod, Rapid Charger, Carrying Cas





Includes: Replacement Nozzle, HEPA Filter

Capacity

Magnet

Weight

RPM





M18FUEL

1" SDS Plus D-Handle Rotary Hammer Kit

2713-22 (2713-20 Tool-Only)

Specifications:

Capacity	1"
Impact Energy	2.2 ft-lbs
RPM	0 – 1,500
BPM	0-4,400
Length / Weight	16.5" / 8.5 lbs

M18[™] 5/8[■] SDS Plus

Rotary Hammer Kit

0010 00 0010 01 (0010 00 T- -) O--



Includes: 2713-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger All Kits Include: Side Handle, Depth Rod, Carrying Case Related Accessory: 2509-22 M12[™] HAMMERVAC[™] ([™] Universal Dust Extractor



2612-22, 2612-21 (26 Specifications	37	•	TI
RPM	0 – 1,300		
BPM	0 – 7,000		
Impact Energy	1.0 ft-lbs		
2-Mode Operation	Rotary Hammer and	d Rotation Onl	У
Weight	5.5 lbs		



Includes: 2612-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2612-21 (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack; All Kits Include: Side Handle, Depth Rod, Multi-Voltage Charger, Carrying Case Related Accessory: 2509-22 M12[™] HAMMERVAC[™] Universal Dust Extractor

M1	BFUEL			
4'	Concrete	Pencil	Vibrator	Kit

2910-21 (2910-20 Tool-Only)

M18FUEL

-	
VPM	0 – 12,500
Head Diameter	1"
Square Head	Yes
Shaft Length	4 ft
Variable Speed Trigger	Yes
Overload Protection	Yes
Weight	11.1 lbs

DLITHIUM

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Pack, Rapid Charger

E 1	
NCE	



_			ncil Vibrator Kit
)11-21 (2911-20 pecificati	27	
V	- /PM	0 – 12,500	
F	lead Diameter	1"	
S	Square Head	Yes	
S	Shaft Length	8 ft	
	/ariable Speed rigger	Yes	
-	Overload Protection	Yes	HIGH OUTPUT XC60
V	Veight	14.3 lbs	

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Pack, Rapid Charger





M18FUEL 1/4" Hex Impact Driver w/ ONE-KEY[™] Kit

2857-22, 2857-22CT (2857-20 Tool-Only) **Specifications:**

-	
Max Torque	2,000 in-lbs
IPM	0-4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode (Customizable)
Chuck Type	1/4" Hex
Single Hand Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

Includes: 2857-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2857-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL **1/4" Hex Impact Driver Kit**

2853-22, 2853-22CT (2853-20 Tool-Only) Specifications:

Max Torque	2,000 in-lbs
IPM	0 - 4,300
RPM	0 - 3,600
DRIVE CONTROL™	4-Mode
Chuck Type	1/4" Hex
Single-Handed Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

Includes: 2853-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2853-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL SURGE[™] 1/4[™] Hex **Hydraulic Driver Kit**

2760-22, 2760-22CT (2760-20 Tool-Only) Specifications:

Suctained Max To

Sustained Max Torque	450 in-Ibs
IPM	0-4,000
RPM	0-3,000
DRIVE CONTROL™	4-Mode
Length / Weight	5.0" / 3.9 lbs

Includes: 2760-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2760-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18[™] Brushless 1/4[■] Hex **3-Speed Impact Driver**

Specifications:

1,600 in-lbs
0 - 4,200
0 - 3,400
1/4" Hex
3-Mode
5.1" / 2.0 lbs

Battery and Charger Sold Separately

Includes: Belt Clip

M18[™] Compact Brushless 1/4" Hex Impact Driver Kit 2850-22CT (2850-20 Tool-Only)

Specifications:	
Max Torque	1,600 in-lbs
IPM	0 - 4,200
RPM	0 - 3,400
Chuck Type	1/4" Hex
Length / Weight	5.1" / 2.9 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



Specifications: Ma

Max Torque	1,500 in-lbs
IPM	0 - 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



Specifications:

Max Torque	1,500 in-lbs
IPM	0 - 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

Includes: 2657-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2657-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs: All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case





4,500 lbs Pull Force 12.5" / 5.6 lbs Length / Weight Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, (4) Retention Nose Pieces, Nose Piece Wrench, Mandrel Collector, Hanging Ring, Belt Clip,

Multi-Voltage Charger, Contractor Bag **Related Accessories:** 49-16-2660NR Non-Retention Nose Piece 4 pk 49-16-2660EXT 6" Extension 49-16-2660B Protective Boot



M18 FUEL **Drywall Screw Gun Kit** 2866-22, 2866-22CT (2866-20 Tool-Only)

Specifications:		
RPM	0-4,500	
Belt Clip	Yes	
Auto Start Mode	Yes	
Length / Weight	9.0" / 4.1 lbs	

Includes: 2866-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2866-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, PR2 Bit, Multi-Voltage Charger, Contractor Bag

Related Accessory:

49-20-0001 MILWAUKEE® Collated Magazine Screw Capacity: Up to 2"

Compatible with all major screw brands

Related Tool: 2627-22 M18™ Cut Out Tool Kit Pg. 52



M18[™] Right Angle **Impact Driver Kit**

2667-22, 2667-21CT (2667-20 Tool-Only) **Specifications:**

Max Torque (2-Mode)	350 / 675 in-lbs
IPM	0-2,400/0-3,400
RPM	0 - 1,500 / 0 - 2,250
Anvil Type	1/4" Hex
Length / Weight	14.1" / 3.9 lbs

Includes: 2667-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; **2667-21CT** (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18[™] Right Angle Impact Wrench Kit

2668-22, 2668-21CT (2668-20 Tool-Only) alfiaati

Specifications:		
Fastening Torque (2-Mode)	30 / 60 ft-lbs	
Nut-Busting Torque	60 ft-lbs	
IPM	0 - 2,400 / 0 - 3,400	
RPM	0 - 1,500 / 0 - 2,250	
Anvil Type	3/8"	
Length / Weight	14.3" / 3.9 lbs	

Includes: 2668-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2668-21CT (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case





	-

































SYSTEM WIDE M18



M18 FUEL

1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY[™] Kit

2759-22, 2759B-22 (2759-20, 2759B-20 Tool-Only) Specifications:

Fastening Torque	220 ft-lbs
Nut-Busting Torque	220 ft-lbs
IPM	0 - 3,200
RPM	0 - 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	6.1" / 4.2 lbs

Includes: 2759-22 1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™; 2759B-22 1/2" Compact Impact Wrench w/ Friction Ring w/ ONE-KEY™ All Kits Include: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL 1/2" Compact Impact Wrench w/ Friction Ring Kit

2855-22 (2855-20 Tool-Only)

Specifications:

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 - 2,400
DRIVE CONTROL [™]	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18 FUEL 1/2" Compact Impact Wrench w/ Pin Detent Kit

2855P-22 (2855P-20 Tool-Only) **Specifications:**

•	
Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 - 3,500
RPM	0 - 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 [™] 1/2" Compact Impact Wrench Kit
2659-22 (2659-20 Tool-Only)
Specifications:

opeenieatiene	
Fastening Torque	183 ft-lbs
Nut-Busting Torque	183 ft-lbs
IPM	0 - 3,350
RPM	0 - 2,450
Anvil Type	1/2" Pin Detent
Length / Weight	6.0" / 4.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case







M18FUEL

3/8["] Impact Wrench w/ Friction Ring w/ ONE-KEY[™] Kit

2758-22, 2758-22CT (2758-20 Tool-Only) Specifications:

specifications:	
Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 - 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	5.9" / 4.2 lbs

Includes: 2758-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2758-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL 3/8" Compact Impact Wrench

w/ Friction Ring Kit

2854-22, 2854-22CT (2854-20 Tool-Only)

Specifications:	
-----------------	--

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 - 3,500
RPM	0 - 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: 2854-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs: 2854-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18[™] 3/8[¶] Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only)

Sp	ecit	icat	lion	Si

Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 - 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

Includes: 2658-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2658-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit 2962P-22 (2962P-20 Tool-Only)

Specifications:

opeenieationei	
Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,500
RPM	0 - 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18 U U U 1/2" Mid-Tor w/ Friction F 2962-22 (2962-20 Tool	_
Specifications:	1
Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 - 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

™8 	que Impact Wrenc
w/ Friction F 2960-22, 2960-22CT (2	Ring Kit
Specifications:	• *
Fastening Torque	600 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.0 lbs

Includes: 2960-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2960-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs;

All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18 CUEU 1" D-Handle H Impact Wrence w/ ONE-KEY ^M 2868-22HD (2868-20 Too Specifications:	sh Kit	-
Fastening Torque	1,900 ft-lbs	
Nut-Busting Torque	2,000 ft-lbs	REDLI
IPM	0 - 1,440	HIGH OUT
RPM	0 - 1,200	
DRIVE CONTROL™	4-Mode (Customizable)	

Length / Weight 17.94" / 21 lbs Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery

Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag

M18 CUEU 1" D-Handle Torque Impa w/ ONE-KEY 2869-22HD (2869-20 T Specifications:	ool-Only)	
Fastening Torque	1,900 ft-lbs	
Nut-Busting Torque	2,000 ft-lbs	REDLITHIUM
IPM	0-1,440	HIGH OUTPUT HD120
RPM	0-1,200	(
DRIVE CONTROL™	4-Mode (Customizable)	
Length / Weight	23.2" / 27.2 lbs	

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



M18 FUEL **1" High Torque Impact** Wrench w/ ONE-KEY[™] Kit

2867-22 (2867-20 Tool-Only) **Specifications:**

•	
Fastening Torque	1,500 ft-lbs
Nut-Busting Torque	1,800 ft-lbs
IPM	0 - 2,450
RPM	0 – 1,650
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	10.9" / 13 lbs

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag

M18 FLEL

3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY[™] Kit

2864-22 (2864-20 Tool-Only)

Specifications:

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18[™] 3/4[¶] High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only) **Specifications:**

opeeniedlienei	
Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Lenath / Weight	9.0" / 6.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

MIBFUEL **1/2" Ext. Anvil Controlled Torque** Impact Wrench w/ ONE-KEY[™] Kit

2769-22 (2769-20 Tool-Only) **Specifications:**

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	10.1" / 5.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag











M18FUEL

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY[™] Kit

2862-22 (2862-20 Tool-Only) Specifications:

opeoinoutionsi	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.1" / 7.2 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



3

M18 FUEL 1/2" High Torque Impact



2766-22 (2766-20 Tool-Only)	
Specifications:	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18[™] 1/2[¶] High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only) Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case





2863-22 (2863-20 Tool-Only) **Specifications:**

1,000 ft-lbs
1,400 ft-lbs
0 – 2,100
0 – 1,750
4-Mode (Customizable)
8.4" / 7.6 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case





M18FUEL 1/2" High Torque Impact

Wrench w/ Friction Ring Kit 2767-22 (2767-20 Tool-Only)

Specifications: Fastening Torque

Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.4" / 7.5 lbs

1,000 ft-lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18[™] 1/2" High Torque Impact Wrench w/ Friction Ring Kit 2663-22 (2663-20 Tool-Only)

Specifications

specifications.	
Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 - 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 EUEL 7/16" Hex Utility High Torque Impact Wrench w/ ONE-KEY™ Kit

2865-22 (2865-20 Tool-Only)

Specifications	
Max Torque	750 ft-lbs
IPM	0 – 2,800
RPM	0 – 2,200
Bit Insertion	QUIK-LOK [™] Single-Handed Bit Insertion
DRIVE CONTROL™	4 Modes (Customizable)
High Voltage Rating	69kV
Length / Weight	8.2" / 7.4 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Lanyard Loop, 12V Inverter, Multi-Voltage Charger, Contractor Bag



SUPER SAWZALL® Reciprocating Saw Kit 2722-21HD (2722-20 Tool-Only)

Specifications:

SPM	0 – 3,000	RED
Stroke Length	1-1/4"	HIGH OU
Blade Clamp	QUIK-LOK [™] (Accepts all SAWZALL	® Blades)
Speeds	5-Speeds	
Orbital Action	Selectable; On/Off	
Anti-Vibration	Yes	
Weight	12.2 lbs	

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Rapid Charger, Contractor Bag

M18 EUEL SAWZALL® Reciprocating Saw Kit w/ ONE-KEY™

2822-22 (2822-20 Tool-Only) Specifications:

-	_	_	_	_		_	_
Cu	it F	Bra	ke S	Set	ttir	na	Yes

Out Drake Setting	163
Stroke Length	1-1/4"
Blade Clamp	QUIK-LOK [™] (Accepts all SAWZALL [®] Blades)
SPM	0-3,000
Adjustable Shoe	Yes
Hang Hook	Yes

Length / Weight	17.1" / 6.8 lbs	
ncludes: (2) M1	8™ REDLITHIUM™ XC5	5.0 Battery Packs,

Multi-Voltage Charger, Carrying Case

Specificatio	ns:
Stroke Length	1-1/4"
Blade Clamp	QUIK-LOK [™] (Accepts all SAWZALL [®] Blades)
SPM	0 – 3,000
Adjustable Shoe	Yes
Hang Hook	Yes
Length / Weight	17.1" / 6.8 lbs

Includes: 2821-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2821-21 (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Multi-Voltage Charger, Carrying Case

M18[™] SAWZALL[®] Reciprocating Saw Kit

2621-22, 2621-21 (2621-20 Tool-Only)	12
Specificatio	ns:	Ľ
SPM	0 – 3,000	
Stroke Length	1-1/8"	
Blade Clamp	Lever-Action QUIK-LOK™ (Accepts all SAWZALL [®] Blades)	
Anti-Vibration	Yes	
Weight	7.9 lbs	

Includes: 2621-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2621-21 (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack; All Kits Include: Multi-Voltage Charger, Carrying Case

Mre CUCL HACKZALL® One-Handed Reciprocating Saw Kit 2719-21 (2719-20 Tool-Only) Specifications: SPM 3,000

Stroke Length	7/8"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Weight	5.6 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



M18[™] HACKZALL[®] One-Handed Reciprocating Saw Kit

SPM	0 - 3.000
Stroke Length	3/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Anti-Vibration	Yes
Weight	5.6 lbs

Includes: 2625-21 (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack; 2625-21CT (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Multi-Voltage Charger, Contractor Bag



M18FUEL

7-1/4" Circular Saw Kit

2732-21HD (2732-20 Tool-Only) **Specifications:**

RPM	5,800
Bevel Capacity	50°
Cut Capacity	2-1/2" at 90°; 1-7/8 " at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	12.0 lbs



Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Circular Saw Blade, Wrench, Rapid Charger, Contractor Bag

MIBELEL 7-1/4" Rear Handle Circular Saw Kit

2830-21HD (2830-20 Tool-Only)

Specifications:

RPM	5,800
Bevel Capacity	53°
Cut Capacity	2-1/2" at 90°; 1-7/8 " at 45°
Arbor	Diamond
Blade Guards	Magnesium
Weight	10.0 lbs



HIGH OUTPUT HD120

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Circular Saw Blade, Wrench, Rapid Charger, Contractor Bag

M18[™] Brushless 7-1/4" Circular Saw Kit

2631-21 (2631-20 Tool-O	nly)
Specificationer	

Specifications:		
RPM	5,000	
Bevel Capacity	50°	
Cut Capacity	2-1/2" at 90°; 1-7/8" at 45°	
Arbor	5/8"	
Blade Guards	Magnesium	
Weight	8.8 lbs	

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag

M18 FUEL 6-1/2" Circular Saw Kit 2730-22, 2730-21 (2730-20 Tool-Only)

Specifications:

RPM	5,000
Bevel Capacity	50°
Cut Capacity	2-3/16" at 90°; 1-5/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.0 lbs

Includes: 2730-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2730-21 (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag









M18[™] 6-1/2[″] **Circular Saw Kit**

2630-22 (2630-20 Tool-Only) **Specifications:** 0 500

RPM	3,500
Bevel Capacity	50°
Cut Capacity	2-1/8" at 90°; 1-9/16" at 45°
Arbor	5/8"
Blade Guards	Plastic
Weight	8.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Circular Saw Blade, Rip Fence, Wrench, Multi-Voltage Charger, Contractor Bag

M18[™] Random Orbit Sander Kit

2648-21 (2648-20 Tool-Only) Specifications:

opcomoditional		
OPM	12,000	
Variable Speed	7,000 - 12,000 OPM	
Pad Size	5.0"	
Orbit Diameter	3/32"	
Weight	2.7 lbs	

Includes: (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, (2) Pieces of 80 Grit Sandpaper, Universal Hose Adapter, Universal Hook & Loop Pad, Multi-Voltage Charger, Contractor Bag

M18[™] 3-1/4[∥] Planer Kit

2623-21 (2623-20 Tool-Only)

Specifications:			
	RPM	14,000	
	Planing Width	3-1/4"	
	Max Planing Depth	5/64"	
	Rabbet Depth	27/64"	
	Length / Weight	12.4" / 7.8 lbs	

Includes: (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack. Bevel Edge Guide, (2) Double-Edged Carbide Blades, Multi-Voltage Charger, Contractor Bag

M18FUEL

Compact	Router
2723-20 Tool-Only	v

Specifications:

	-
RPM	10,000 - 31,000
Speeds	6
Collet Size	1/4"
Adjustable Range	1.5"
Height / Weight	6.9" / 3.0 lbs

Battery and Charger Sold Separately

Includes: Fixed Base, Straight Edge Guide, 5-3/4" Template Bushing Sub-base plate, Dust Shroud, 11/16" Collet Wrench, 7/16" Spindle Wrench **Related Accessories:** 48-10-5601 Compact Router Plunge Base

48-10-5602 Compact Router Offset Base



M18FUEL

D-Handle Jig Saw Kit 2737-21 (2737-20 Tool-Only) Specifications:

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	6.4 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, Wrench, Multi-Voltage Charger, Carrying Case



M18FUEL **Barrel Grip Jig Saw**

2737B-20 Tool-Only Specifications:	_
SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK [™] T-Shank
Orbital Settings	4
Weight	4.6 lbs

Battery and Charger Sold Separately

Includes: Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, LED Cover, Wrench



M18 FUEL

Oscillating Multi-Tool Ki 2836-21 (2836-20 Tool-Only)

Specifications:

-	
Speed Settings	12
OPM	10,000 - 20,000
Oscillation Angle	4.2°
Auto-Load Feature	Yes
LED Light	Yes
Length / Weight	14.5" / 4.2 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, (5) Sanding Sheets, Sanding Pad, Wood Cutting Blade, Charger, Contractor Bag

M18[™] Multi-Tool Kit

2626-22 (2626-20 Tool-Only)

Specifications: Speed Settings 12 OPM 11,000 - 18,000 Tool-Free Accessory Change Yes Length / Weight 14.0" / 4.2 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Multi-Voltage Charger, Contractor Bag

M18[™] Cut Out Tool Kit 2627-22, 2627-22CT (2627-20 Tool-Only)

Specifications:

-	
RPM	28,000
Tool-Free Depth Adjustment	Yes
LED Light	Yes
Belt Clip	Yes
Length / Weight	8.9" / 1.8 lbs

Includes: 2627-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2627-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; All Kits Include: Belt Clip, (2) 1/8" Drywall Bits, 1/8" Collet, " Collet, Wrench, Multi-Voltage Charger, Contractor Bag **Related Tool:** 2866-22 M18 FUEL[™] Drywall Screw Gun Kit Pg. 46

SYSTEM WIDE M18

M18[™] 10 oz Caulk and Adhesive Gun Kit

2641-21CT (2641-20 Tool-Only) **Specifications:**

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.8 lbs



Includes: (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack, 10 oz Carriage, M18[™] 10 oz Plunger Rod and Piston Assembly, Multi-Voltage Charger





Includes: (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M18[™] 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



M18[™] 20 oz Clear Barrel Sausage Style Caulk & Adhesive Gun Kit 2643-21CT

Specifications:	
Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	6.6 lbs

Includes: (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack, 20 oz Clear Sausage Style Barrel, M18[™] 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



Caulk Gun Accessories

Compatible with 2641-21CT, 2642-21CT, and 2643-21CT 31-12-0700 Caulk Gun Nozzle – Black 48-08-1076 M18[™] 10 oz Caulk and Adhesive Gun Conversion Kit 48-08-1091 20 oz Aluminum Barrel Kit 48-08-1093 M18[™] 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit 48-08-1094 M18[™] 20 oz Clear Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit 48-08-1095 M18[™] Quart Caulk and Adhesive Gun Conversion Kit 48-08-1096 20 oz Clear Barrel Kit







M18 FUEL 7-1/4" Dual Bevel Sliding **Compound Miter Saw Kit** 2733-21 (2733-20 Tool-Only) **Specifications:**

Blade Size	7-1/4"
No Load RPM	5,000
Max Bevel Angle	48° / 48°
Max Miter Angle	48° / 48°
Max Vertical Capacity	3-1/2"
Max Horizontal Capacity	2x8
Weight	28.0 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Blade Wrench, Blade, Clamp, Multi-Voltage Charger



39-21CT (2839-20 Too	ol-Only)
pecifications:	
Jail Diameter	15 Gauge
lail Size	1-1/4" – 2-1/2"
lagazine Capacity	110
lagazine Loading	Bottom Load
1ax Fire Rate	3 Nails per Second
lails Per Charge	750
iring Modes	Sequential & Contact Actuation

Ю



_	sh Nailer Kit
41-21CT (2841-20 pecification :	.,
Nail Diameter	16 Gauge
Vail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails per Charge	800
Firing Modes	Sequential & Contact Actuation



M18FUEL

21° Framing Nailer Kit 2744-21 (2744-20 Tool-Only) Specifications:

opcomoution	51
Collation Angle	21° Round Head Nail
Nail Size	2" - 3-1/2"
Nail Collation	20° – 22°
Magazine Capacity	45 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag **Related Accessory:** 48-08-2744 21° Framing Nailer Extended Capacity Magazine





w/ ONE-KEY[™] Kit 2736-21HD (2736-20 Tool-Only) Specifications: RPM 6,300 Blade Size 8-1/4" Arbor Size 5/8" 47° Max Bevel Cut Depth 2-1/2" at 90°; 1-3/4" at 45° Rip Capacity 24" Left of Blade; 12" Right of Blade Weight 45.0 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Blade, Wrench, Anti-Kickback Pawls, Guard, Riving Knife, Fence, Push Stick, Miter Gauge, Rapid Charger

M18 FUEL

12" Dual Bevel Sliding **Compound Miter Saw** w/ ONE-KEY™ Kit

2739-21HD (2739-20 Tool-Only)

8-1/4" Table Saw

Specifications:

Blade Size	12"
No Load RPM	3,500
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	6-3/4"
Max Horizontal Capacity	2x14
Weight	47.6 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Blade, Clamp, Handles, Rapid Charger

M18 EUEU 10" Dual Bevel Sliding Compound Miter Saw Kit 2734-21 (2734-20 Tool-Only) Specifications:		
Blade Size	10"	
No Load RPM	4,000	An other Dates
Max Bevel Angle	48° / 48°	
Max Miter Angle	50° / 60°	REDLITHIUM
Max Vertical Capacity	5-3/4"	HIGH OUTPUT XC80
Max Horizontal Capacity	2x12	
Weight	47.0 lbs	

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Blade Wrench, Carbide Tipped Blade, Clamp, Dust Bag, Rapid Charger







M18FUEL

30° Framing Nailer Kit

2745-21 (2745-20 Tool-Only) **Specifications:**

opcomoditorio	
Collation Angle	30° Clipped or Full Head Nail
Nail Size	2" - 3-1/2"
Nail Collation	30° – 34°
Magazine Capacity	57 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag **Related Accessory:** 48-08-2745 30° Framing Nailer Extended Capacity Magazine



M18 FUEL **18 Gauge Brad Nailer Kit**

2746-21CT (2746-20 Tool-Only) Specifications:

Nail Diameter
Nail Size
Magazine Capacity
Max Fire Rate
Magazine Loading
Firing Modes

18 Gauge 5/8" - 2-1/8" 110 Nails 3 Nails per Second Side Load Sequential or Contact Actuation

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag





M18 FUEL 18 Gauge 1/4" Narrow **Crown Stapler Kit** 2749-21CT (2749-20 Tool-Only) **Specifications:**

-	
Staple Diameter	18 Gauge
Staple Crown Size	1/4"
Staple Length	3/8" – 1-1/2"
Magazine Capacity	108 Staples
Max Fire Rate	4 Staples per Second
Magazine Loading	Front Load

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag



M18FUEL 16 Gauge Straight Finish Nailer Kit 2741-21CT (2741-20 Tool-Only)

Specifications:

Nail Diameter	16 Gauge
Nail Size	3/4" - 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag





54







M18[™] SWITCH TANK[™] 4-Gallon **Backpack Water Supply Kit** 2820-21WS

Specifications:

4 Gallon
Dual Diaphragm Pump
20 – 60 PSI (5 Modes)
0.16 – 1.13 Gal/Min
18.5 lbs

Includes: M18[™] SWITCH TANK[™] Powered Base, SWITCH TANK[™] 4 Gallon Water Supply Tank Assembly, (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, 10' Hose w/ Quick-Connect, Water Spray Nozzle, Multi-Voltage Charger



M18 FUEL **Deep Cut Band Saw Kit** 2729-22, 2729-21 (2729-20 Tool-Only) **Specifications:** SFPM 0 - 380 5" x 5" Cut Capacity Tool-Free Shoe LED Light Yes Hang Hook Yes Weight 15.9 lbs

Includes: 2729-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2729-21 (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Blade, Multi-Voltage Charger, Carrying Case



Deep Cut D	
Band Saw K	
2729S-22 (2729S-20 T Specifications :	37
SFPM	• 0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	Yes

Weight

Weight

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Set of Band Saw Blade Covers, Blade, Multi-Voltage Charger, Contractor Bag

13.8 lbs

M18 FUEL **Compact Band Saw Kit** 2829-22 (2829-20 Tool-Only)



Specifications:	
SFPM	0 – 540
Cut Capacity	3-1/4" x 3-1/4"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Vee



	SFPM	0 – 540
	Cut Capacity	3-1/4" x 3-1/4"
	Shoe	Tool-Free Locking
	LED Light	Yes
\	Hang Hook	Yes
)	Dual-Trigger Design	No

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] CP3.0 Battery Packs, Blade, Rapid Charger, Contractor Bag

7.7 lbs

M18FUEL **2 Gallon Compact Quiet Compressor** 2840-20 Tool-Only

Specifications: SCFM 1.2 @ 90 PSI Capacity 2 Gallon Sound Level 68 dB(a) 16.3" / 18.5" / 10.3" Dimensions $(L \times W \times H)$ Weight 31.2 lbs Regulator Single Turn

Oil Free

Battery and Charger Sold Separately

Pump Type



M18FUEL 9" Cut-Off Saw w/ ONE-KEY[™] Kit

2786-22HD (2786-20 Tool-Only) Specifications:

opeeniealiene		and the second se	
RPM	6,600		1
Blade Size	9"	F	REDL
Arbor Size	7/8"	HIG	HOU
Cut Depth	3.4"		
Load Indicator Light	Yes		
Blade Brake	RAPIDST	OP™	
Weight	10.6 lbs		

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Abrasive Blade, Diamond Blade, Wrench, Hex Key, Rapid Charger



M18[™] SWITCH TANK[™] 4-Gallon **Backpack Concrete Sprayer Kit** 2820-21CS

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.14 – 0.82 Gal/Min
Dry Weight	18.3 lbs



Includes: M18[™] SWITCH TANK[™] Powered Base, SWITCH TANK[™] 4 Gallon Concrete Sprayer Tank Assembly, (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger

SWITCH TANK[™] Accessories

Compatible with 2820-20

Related Accessories:

49-16-28WS SWITCH TANK[™] 4 Gallon Water Supply Tank Assembly **49-16-28CS** SWITCH TANK[™] 4 Gallon Concrete Sprayer Tank Assembly 49-16-28PS SWITCH TANK[™] 4 Gallon Sprayer Tank Assembly

TRADE FOCUSED M18



M18 FUEL **Compact Dual-Trigger** Band Saw Kit

2829S-22 Specifications:

specifications.		
SFPM	0 - 540	
Cut Capacity	3-1/4" x 3-1/4"	
Shoe	Tool-Free Locking	
LED Light	Yes	
Hang Hook	Yes	
Dual-Trigger Design	Yes	
Weight	7.7 lbs	



Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] CP3.0 Battery Packs, Set of Band Saw Blade Covers, Blade,

Rapid Charger, Contractor Bag

Band Saw Accessories Deep Cut Band Saw Accessory:

Compatible with 2729-20, 2729S-22 49-90-2729 Deep Cut Band Saw Blade Covers

Compact Band Saw Accessories:

Compatible with 2829-20, 2829S-20 49-90-2829 Compact Band Saw Blade Covers 49-90-2029 Compact Band Saw Reamer Attachment



M18 FUEL **Metal Cutting Circular Saw Kit**

2782-22 (2782-20 Tool-Only)

Specifications:			
RPM	3,900		
Blade Size	5-3/8" – 5-7/8"		
Arbor Size	20 mm		
Hang Hook	Yes		
Length / Weight	4.7" / 6.5 lbs		



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, 30T Blade, Multi-Voltage Charger, Contractor Bag





Specifications: Blade Cut Capacity 2-9/16' RPM 4.000 Arbor Size 5/8" Chip Collection Yes Yes Overload Indicator Light Electric Blade Brake Yes Length / Weight 15.5" / 12.1 lbs



Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Blade, Allen Key, Rapid Charger, Contractor Bag





M18FUEL

14" Abrasive Chop Saw Kit

2990-21HD (2990-20 To Specifications:	ol-Only)	A Jos
RPM	4,000	
RAPID STOP™ Blade Brake	Yes	B
Tool-Free Blade Adjust	Yes	
Tool-Free Fence Adjust	Yes	
Cut Capacity	5"	a constant of the second
Dimensions (L x W x H)	20.2" / 11.5" / 16.5"	1
Weight	38.1 lbs	REDLITHIUM HIGH OUTPUT HD12

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Rapid Charger

M18 FUEL

7" / 9" Large Angle Grinder Kit

	La ge Angle unit
2785-22HD,	2785-21HD (2785-20 Tool-Only)
Specific	ations:

RPM	6,600	
Switch Type	Dual-Action Trigger	
Overload Protection	Yes	
Electronic Clutch	Yes	
Tool-Free Accessory Change and Guard	Yes	
Length / Weight	18.5" / 11.9 lbs	

Includes: 2785-22HD (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs; 2785-21HD (1) M18[™] REDLITHIUM[™]

HIGH OUTPUT[™] HD12.0 Battery Pack; All Kits Include: 9" T27 Guard, Anti-Vibration Side Handle, Back Flange, Dust Vent Clip, FIXTEC[™] Nut, Spanner Wrench, Rapid Charger, Carrying Case



M18 FUEL **4-1/2" - 6" Braking Grinder Kit** Paddle Switch, No-Lock

2980-22, 2980-21 (298	0-20 Tool-Only)	
Specifications :	1	
RPM	9,000	1
Switch Type	Paddle, No-Lock	
Brake	Yes	
Overload Protection	Yes	RED HIGH C
Electronic Clutch	Yes	- пан с
Tool-Free Accessory Change and Guard	Yes	
Length / Weight	15.0" / 5.3 lbs	

Includes: 2980-22 (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs; 2980-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6 0 Battery Pack

All Kits Include: T27 Guard, Side Handle, Back Flange, 57 FIXTEC[™] Nut, Wrench; Rapid Charger, Contractor Bag

M18 FUEL

4-1/2" - 6" Braking Grinder Kit Slide Switch, Lock-On

2981-22, 2981-21 (2981-20 Tool-Only) **Specifications:**

•	
RPM	9,000
Switch Type	Slide, Lock-On
Brake	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 5.3 lbs



Includes: 2981-22 (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs; 2981-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™

XC6.0 Battery Pack; All Kits Include: T27 Guard, Side Handle, Back Flange, FIXTEC[™] Nut, Wrench, Rapid Charger, Contractor Bag



M18 FUEL **4-1/2" / 5" Grinder Kit Paddle Switch, No-Lock** 2780-22, 2780-21 (2780-20 Tool-Only)

Specifications:	
RPM	8,500
Switch Type	Paddle, No-Lock
Power to Grind	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 8.2 lbs

Includes: 2780-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2780-21 (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Multi-Voltage Charger, Carrying Case



M18 FUEL 4-1/2" / 5" Grinder Kit Slide Switch, Lock-On 2781-22, 2781-21 (2781-20 Tool-Only)

Specifications:

RPM	8,500	States .
Switch Type	Slide, Lock-On	
Power to Grind	Yes	
Overload Protection	Yes	
Electronic Clutch	Yes	
Tool-Free Accessory Change and Guard	Yes	
Length / Weight	15.0" / 8.2 lbs	

Includes: 2781-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; **2781-21** (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Multi-Voltage Charger, Carrying Case

M18FUEL	
4-1/2" / 5" E	Braking
Grinder Kit 2783-22 (2783-20 Tool Specifications:	
RPM	8,500
Switch Type	Paddle, No-Loc
Brake	Yes
Clutch	Yes

Switch Type	Paddle, No-Lock
Brake	Yes
Clutch	Yes
Overload Protection	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.3" / 8.2 lbs

Includes: T27 Guard, T1 Guard, Side Handle, Flange Nut, FIXTEC[™] Nut; 2783-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag

M18 FUEL

4-1/2" / 5" Variable Speed Braking **Grinder, Paddle Switch No-Lock** 2888-20 Tool-Only

necificatio .

Specifications:	
Wheel Diameter	4-1/2" / 5"
Switch Type	Paddle, No-Lock
No Load RPM	3,500 - 8,500
Spindle	5/8" – 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Tool-Free Accessory Change	Yes
Anti-Vibration Handle	Yes
Length / Weight	13.18" / 3.16 lbs

Battery and Charger Sold Separately

M18 FUEL

1/4" Die Grinder Kit 2784-22 (2784-20 Tool-Only)

2/04-22 (2/04-20 1	
Specification	IS:
Collet Size	1/4"
RPM	20,000
Switch Type	Slide, Lock-On
Length / Weight	18.0" / 4.6 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, 11/16" Wrench, 1/2" Wrench, Multi-Voltage Charger, Carrying Case











SYSTEM WIDE M18



5" Flathead Braking Switch No-Lock	Grinder, Paddle

2886-20 Tool-Only Specifications:

-	
Wheel Diameter	5"
Switch Type	Paddle, No-Lock
No Load RPM	3,500-8,500
Spindle	5/8" – 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Fool-Free Guard Change	Yes
Tool-Free Accessory Change	No
Anti-Vibration Handle	Yes
_ength / Weight	14.02" / 3.1 lbs

Battery and Charger Sold Separately



M18 FUEL

5" Flathead Braking Grinder, Slide Switch Lock-On

2887-20 Tool-Only Specifications

specifications:	1
Wheel Diameter	5"
Switch Type	Slide, No-Lock
No Load RPM	8,500
Spindle	5/8" – 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Tool-Free Accessory Change	No
Anti-Vibration Handle	Yes
Length / Weight	14.02" / 3.1 lbs

Battery and Charger Sold Separately

M18[™] 4-1/2[″] **Cut-Off / Grinder Kit**

2680-22 (2680-20 Tool-Only)

Specifications:		2
RPM	9,000	
Switch	Paddle	
Guard Adjustment	Tool-Free	
Overload Protection	Yes	
Weight	5.9 lbs	

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Type 1 Guard, Type 27 Guard, Spanner Wrench, Side Handle, Multi-Voltage Charger, Contractor Bag

MIBELEL 4-1/2" / 5" Variable Speed Braking **Grinder, Slide Switch Lock-On** 2889-20 Tool-Only

Specifications:	4	and and a	
Wheel Diameter	4-1/2" / 5"	1	
Switch Type	Slide, Lock-On		
No Load RPM	3,500 - 8,500		
Spindle	5/8" – 11		
E-Clutch / Kickback Protection	Yes		
Overload Protection	Yes		
Tool-Free Guard Change	Yes		
Anti-Vibration Handle	Yes		
Length / Weight	Yes		

Battery and Charger Sold Separately





M18[™] Compact Heat Gun Kit 2688-21 (2688-20 Tool-Only)

Specifications:

Temperature

Ladder Hook

Guarded Nozzle

Length / Weight

1
1000

	Co -

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, 3/8" Concentrator Nozzle, Hook Nozzle, Multi-Voltage Charger, Carrying Case

6.4" / 3.3 lbs

750°F

Yes

Yes



M18 [™] 18 Gauge
Double Cut Shear Kit
2635-22 (2635-20 Tool-Only)

Specifications:

Head	18 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 5.6 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18[™] 14 Gauge Double Cut Shear Kit 2636-22 (2636-20 Tool-Only) **Specifications:**



Head	14 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 6.2 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag





18 Gauge Single Cut Head 360° Tool-Free Yes Rotating Head Variable Speed Trigger Yes

Length / Weight	18.0" / 5.8 lbs
ncludes: (2) M18™	[∉] BEDLITHIUM [™] XC3.0 Battery F

Battery Packs, Hex Key, Inc Belt Clip, Multi-Voltage Charger, Contractor Bag



)		(

M18 FUEL **7" Variable Speed Polisher Kit**



2738-22, 2738-21 (2738-20 Tool-Only) **Specifications:**

Capacity	7" Maximum
RPM	0 - 2,200
Variable Speed Dial and Trigger	Yes
Lock-On / Lock-Off	Yes
Length / Weight	19.8" / 6.4 lbs

Includes: 2738-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Backing Paci; **2738-21** (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack; All Kits Include: Screen Cover, Side Handle, Bail Handle with (2) Bolts, Rapid Charger



M18[™] 2-Speed **Grease Gun Kit**

2646-22CT, 2646-21CT (2646-20 Tool-Only) Specifications:

	Output Pressure	Up to 10,000 PSI (690 BAR)	<
	Run-Time	Up to 10 Cartridges Per Charge	-
-	Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction	
	Air Bleeder Valve	Yes	
	Weight	8.5 lbs	

Includes: 2646-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; **2646-22CT** (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: 48" Flex Hose with Spring Guard, High Pressure Grease Coupler, Shoulder Strap, Multi-Voltage Charger, Carrying Case Related Accessories: 49-16-2646 M18[™] Grease Gun 400g Clear Barrel

49-16-2647 M18[™] Replacement Grease Gun Hose with High Pressure Coupler 49-16-2648 M18[™] Right Angle Grease Gun Coupler 49-16-2649 M18[™] High Pressure Grease Coupler (2 pk)







M18 [™] Brushless Rod Cutter Kit 2872-21 (2872-20 Tool-Only)		
Specifications:		• 1
Cutting Capacity	1/4", 3/8" and 1/2"	
Replacement Cutting Dies	Yes	
Dimensions (L x W x H)	10.0" x 5.0" x 6.3"	
Weight	7.7 lbs	

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Cutting Dies, Allen Key, Multi-Voltage Charger, Carrying Case **Related Accessory:** 48-44-2872 1/4", 3/8", 1/2" Replacement Cutting Die Set



60



M18[™] FORCE LOGIC[™] **6T Utility Crimper Kits**



(2678-20 Tool-Only)

w/ BG-D3 Jaw 2678-22BG









w/ Snub Nose Jaw 2678-22 (2678-20 Tool-Only)



2678-22K (2678-20 Tool-Only)

Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY [™] Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	5.4" / 14.0"

Includes: 2678-22BG 6T Fixed BG Crimping Jaw; 2678-22O 6T Fixed O Crimping Jaw; 2678-22 6T Snub Nose Crimping Jaw; 2678-22K 6T Kearney Crimping Jaw; All Kits Include: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag

M18[™] FORCE LOGIC[™] **6T Linear Utility Crimper Kits**



w/ O-D3 Jaw 2978-220, 2978-OKIT (2978-20 Tool-Only)

w/ Kearnev Jaw

2978-22K

(2978-20 Tool-Only)



w/ Snub Nose Jaw 2978-22

(2978-20 Tool-Only) **Specifications:**

Output Force 6 Tons

Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.5 Seconds
Head Rotation	340°
Height / Length	5.1" / 19.9"

Includes: 2978-22BG 6T Fixed BG Crimping Jaw; 2978-BGKIT 6T Fixed BG Crimping Jaw, 750 MCM Cu/Al Cutting Jaw, 477 ACSR Cutting Jaw; 2978-220 6T Fixed O Crimping Jaw; 2978-OKIT 6T Fixed O Crimping Jaw, 750 MCM Cu/Al Cutting Jaw, 477 ACSR Cutting Jaw: 2978-22 6T Snub Nose Crimping Jaw: 2978-22K 6T Kearney Crimping Jaw; All Kits Include: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag

M18[™] FORCE LOGIC[™] **6T Pistol Utility Crimper Kits**



w/ BG-D3 Jaw 2977-22BG (2977-20 Tool-Only)

Specifications:

•	
Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	12.3" / 17.3"

Includes: 2977-22BG 6T Fixed BG Crimping Jaw; 2977-220 6T Fixed O Crimping Jaw:

All Kits Include: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag



M18[™] FORCE LOGIC[™] 6T Utility **Crimper Accessories**

Compatible with 2678-20, 2977-20, 2978-20

6T Utility Crimper Jaws 49-16-BGD3 6T Fixed BG Crimping Jaw 49-16-10D3 6T Fixed O Crimping Jaw

49-16-11D3 6T Snub Nose Crimping Jaw 49-16-KEAR 6T Kearney Crimping Jaw

Cutter Jaws

Also Compatible with 2672-21, 2672-21S, and 2672-21F

49-16-2772 750 MCM Cu/Al Cutting Jaw 49-16-2773 477 ACSR Cutting Jaw 49-16-2777 1/2" EHS Guy Wire Cutting Jaw 49-16-2778 Fine-Stranded Wire Cutting Jaw

Cutter Replacement Blades

48-44-0411 Replacement Copper Blades 48-44-0412 Replacement Steel Blades 48-44-2777 1/2" EHS Guy Wire Replacement Blades 48-44-2778 Fine-Stranded Wire Replacement Blades

W Style Dies

49-16-WBG0 W Style Die: "W-BG" 49-16-WO00 W Style Die: "W-O" 49-16-WC00 W Style Die: "W-C" 49-16-W161 W Style Die: "W-161" 49-16-W162 W Style Die: "W-162" 49-16-W163 W Style Die: "W-163" 49-16-W164 W Style Die: "W-164" 49-16-W165 W Style Die: "W-165" 49-16-W166 W Style Die: "W-166" 49-16-W237 W Style Die: "W-237" 49-16-W239 W Style Die: "W-239" 49-16-W243 W Style Die: "W-243" 49-16-W247 W Style Die: "W-247" 49-16-W249 W Style Die: "W-249" 49-16-W840 W Style Die: "W-K840"



2977-220 (2977-20 Tool-Only)



2679-350A, 2679-600C

Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	350°
Height / Length	5.4" / 13.3"

Includes: 2679-750C 750 MCM Cu/Al Crimping Jaw, All Copper U Style Dies (49-16-KITC Die Kit and 49-16-750C Die Kit); 2679-750A 750 MCM Cu/Al Crimping Jaw, All Aluminum U Style Dies (49-16-KITA Die Kit and 49-16-750A Die Kit); 2679-350A 49-16-KITA Die Kit; 2679-600C 49-16-KITC Die Kit:

All Kits Include: 2679-22 600 MCM Commercial U Crimping Jaw, (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case

FORCE LOGIC[™] 600 MCM **Crimper Accessories**

Compatible with 2679-22, 2679-750C, 2679-750A, 2679-350A, 2679-600C

Related Accessories:

49-16-U000 600 MCM Crimping Jaw 49-16-U111 750 MCM Cu/Al Cable Crimping Jaw 49-16-2780 750 MCM Cu/Al Cable Cutting Jaw

Cutter Replacement Blades 48-44-0411 750 MCM Cu/Al Cable Cutting Blades

Accessory Kits

49-16-KITA #8 AWG - 350 MCM Aluminum U Style Die Kit 49-16-750A 400 - 750 MCM Aluminum U Style Die & Jaw Kit 49-16-KITC #8 AWG - 600 MCM Copper U Style Die Kit 49-16-750C 750 MCM Copper U Style Die & Jaw Kit

Copper U Style Dies

49-16-U001C #1 Copper U Style Die 49-16-U002C #2 Copper U Style Die 49-16-U004C #4 Copper U Style Die 49-16-U006C #6 Copper U Style Die 49-16-U008C #8 Copper U Style Die 49-16-U01AC 1/0 Copper U Style Die 49-16-U02AC 2/0 Copper U Style Die 49-16-U03AC 3/0 Copper U Style Die 49-16-U04AC 4/0 Copper U Style Die 49-16-U250C 250 MCM Copper U Style Die 49-16-U300C 300 MCM Copper U Style Die 49-16-U350C 350 MCM Copper U Style Die 49-16-U400C 400 MCM Copper U Style Die 49-16-U500C 500 MCM Copper U Style Die 49-16-U600C 600 MCM Copper U Style Die 49-16-U750C 750 MCM Copper U Style Die

Aluminum Dual-Rated U Style Dies

49-16-U001 #1 Aluminum U Style Die 49-16-U002 #2 Aluminum U Style Die 49-16-U004 #4 Aluminum U Style Die 49-16-U006 #6 Aluminum U Style Die 49-16-U008 #8 Aluminum U Style Die 49-16-U01A 1/0 Aluminum U Style Die 49-16-U02A 2/0 Aluminum U Style Die 49-16-U03A 3/0 Aluminum U Style Die 49-16-U04A 4/0 Aluminum U Style Die 49-16-U250 250 MCM Aluminum U Style Die 49-16-U300 300 MCM Aluminum U Style Die 49-16-U350 350 MCM Aluminum U Style Die 49-16-U400 400 MCM Aluminum U Style Die 49-16-U500 500 MCM Aluminum U Style Die 49-16-U600 600 MCM Aluminum U Style Die 49-16-U750 750 MCM Aluminum U Style Die







2877-22 Specifications:

Crimping Capacity	#6 – 750 MCM Cu & Al
Adaptive Distance Control	Yes; Auto Distance Control
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Dimensions (L x W x H)	18.9" x 3.3" x 6.5"
Weight	9.0 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18[™] FORCE LOGIC[™] **12T Utility Crimper Kit** 2778-22 (2778-20 Tool-Only)

Specifications:

opoonioalionoi			
	Output Force	12 Tons	1
	Head Rotation	350°	
	Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible	1
	Length / Weight	16.0" / 11.9 lbs	

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack. (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag







M18[™] FORCE LOGIC[™] **750 MCM Crimper Kit** 2779-22, 2779-750A, 2779-750C

Specifications:

Output Force 12 Tons Head Rotation 350° Reporting and Built-In; **Tool Diagnostics** ONE-KEY[™] Compatible Length / Weight 16.0" / 11.5 lbs

Includes: 2779-750A 49-12-KITA; 2779-750C 49-12-KITC; All Kits Include: 2779-22 (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Related Accessories:

Accessory Kits

49-12-KITC EXACT™ #6 AWG - 750 MCM Cu 12T U Style Die Kit **49-12-KITA** EXACT[™] #6 AWG – 750 MCM AI 12T U Style Die Kit

EXACT[™] 12T Copper U Style Dies

49-12-U001C #1 Copper 12T U Style Die
49-12-U002C #2 Copper 12T U Style Die
49-12-U004C #4 Copper 12T U Style Die
49-12-U006C #6 Copper 12T U Style Die
49-12-U008C #8 Copper 12T U Style Die
49-12-U01AC 1/0 Copper 12T U Style Die
49-12-U02AC 2/0 Copper 12T U Style Die
49-12-U03AC 3/0 Copper 12T U Style Die
49-12-U04AC 4/0 Copper 12T U Style Die
49-12-U250C 250 MCM Copper 12T U Style Die
49-12-U300C 300 MCM Copper 12T U Style Die
49-12-U350C 350 MCM Copper 12T U Style Die
49-12-U400C 400 MCM Copper 12T U Style Die
49-12-U500C 500 MCM Copper 12T U Style Die
49-12-U600C 600 MCM Copper 12T U Style Die
49-12-U750C 750 MCM Copper 12T U Style Die

EXACT[™] 12T Aluminum U Style Dies

49-12-U001 #1 Aluminum 12T U Style Die 49-12-U002 #2 Aluminum 12T U Style Die 49-12-U004 #4 Aluminum 12T U Style Die 49-12-U006 #6 Aluminum 12T U Style Die 49-12-U008 #8 Aluminum 12T U Style Die 49-12-U01A 1/0 Aluminum 12T U Style Die 49-12-U02A 2/0 Aluminum 12T U Style Die 49-12-U03A 3/0 Aluminum 12T U Style Die 49-12-U04A 4/0 Aluminum 12T U Style Die 49-12-U250 250 MCM Aluminum 12T U Style Die 49-12-U300 300 MCM Aluminum 12T U Style Die **49-12-U350** 350 MCM Aluminum 12T U Style Die **49-12-U400** 400 MCM Aluminum 12T U Style Die 49-12-U500 500 MCM Aluminum 12T U Style Die 49-12-U600 600 MCM Aluminum 12T U Style Die 49-12-U750 750 MCM Aluminum 12T U Style Die

M18[™] FORCE LOGIC[™] **15T Crimper Kit**

2879-22 (2879-20 Tool-Only) Specifications:

Crimping Capacity	#8 - 1500 MCM Cu, #8 - 1250 MCM AI
Output Force	15 Tons
Adaptive Pressure Control	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Dimensions (L x W x H)	23.3" x 3.1" x 5.5"
Weight	16.1 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, P-to-U Die Adapter, Carabiner, Multi-Voltage Charger, Contractor Bag **Related Accessories:**

49-15-PUAD P-to-U Die Adapter

49-15-P750 15T 750 MCM A P-Die 49-15-P800 15T 800 MCM AI P-Die 49-15-P000 15T 1000 MCM AI P-Die 49-15-P750C 15T 750 MCM Cu P-Die 49-15-P800C 15T 800 MCM Cu P-Die



M18[™] FORCE LOGIC[™] 10,000 PSI **Hydraulic Pump Kit**

2774-21HD (2774-20 Tool-Only)

Specifications:

Operating Pressure	10,000 psi / 700 bar
Usable Oil Capacity	1.4 qts
Flow Rate at Low Pressure	125.0 in ³ /min
Flow Rate at High Pressure	25.6 in ³ /min
Ingress Protection	IP54
Dimensions (L x W x H)	15.8" x 11.5" x 13.9"
Weight	29.7 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Rapid Charge **Related Accessories:** 49-12-2776 Bucket Hanger





M18[™] FORCE LOGIC[™] Cable Cutter Kit w/ 750 MCM Cu Jaws

Specifications:	
Cut Capacity	750 MCM Cu, 1000 MCM Al
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack. 750 MCM Cable Cutter Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case

M18[™] FORCE LOGIC[™] Cable Cutter Kit w/ 477 ACSR Jaws

2672-21S Sp

Specifications:		_
Cut Capacity	477 HEN ACSR	
Average Cut Speed	3 Seconds	
Head Rotation	350°	
Auto Posot	Voc	

Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, 477 ACSR Cutting Jaw, Carabiner, Allen Wrench, Multi-Voltage Charger and Inverter, Bucket Bag

M18[™] FORCE LOGIC[™] Cable Cutter Kit w/ Fine-Stranded Wire Jaws 0670 01E

2672-21F	
Specifications:	3
Cut Capacity	777.7 MCM Fine-Stranded Wire
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Fine-Stranded Wire Cutting Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case

M18[™] FORCE LOGIC[™] **Cable Cutter Accessories**

Compatible with 2672-21, 2672-21S and 2672-21F

Cutter Jaws

49-16-2772 750 MCM Cu/AI Cutting Jaw 49-16-2773 477 ACSR Cutting Jaw 49-16-2777 1/2" EHS Guy Wire Cutting Jaw 49-16-2778 Fine-Stranded Wire Cutting Jaw

Cutter Replacement Blades

48-44-0411 Copper Replacement Blades 48-44-0412 ACSR Replacement Blades 48-44-2777 1/2" EHS Guy Wire Replacement Blades 48-44-2778 Fine-Stranded Wire Replacement Blades

2672-21

SYSTEM WIDE M18













Specifications:

Cut Capacity	1500 MCM Cu 15kV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	12.4" / 20.8"
Weight	15.8 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Remote, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag **Related Accessory:** 49-16-2774 3" Underground Replacement Blades





Spec	ifica	tions:

Cut Capacity	1500 MCM Cu 15kV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	12.4" / 20.8"
Weight	15.8 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag **Related Accessory:** 49-16-2774 3" Underground Replacement Blades

M18[™] FORCE LOGIC[™] **1590 ACSR Cu**

2777-21 **Specifications:**

Cut Capacity

Tool Diagnostics

Height / Length

Weight

utter Kit	
Up to 1590 Falcon ACSR	2 V
Built-In; ONE-KEY™ Compatible	
10.6" / 16.8"	
11.8 lbs	

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Carabiner, Side Handle, Multi-Voltage Charger and Inverter, Utility Bag **Related Accessory:**

49-16-2775 1590 ACSR Replacement Blades







M18[™] FORCE LOGIC[™] **6 Ton Knockout Tool Kit**

2677-23, 2677-21 (2677-20 No Punches or Dies) **Specifications:**

4" in 14 Gauge Mild Steel Capacity Stainless Steel Capacity 2" in 14 Gauge Output Force 6 Tons Quick-Connect Yes Draw Stud Rapid Reset Yes Height / Weight 4.5" / 4.3 lbs

Includes: 2677-23 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT[™] 1/2" - 4" Conduit Punches and Dies; 2677-21 (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, EXACT[™] 1/2" - 2" Conduit Punches and Dies; 2677-20 (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack (No Punches or Dies Included); All Kits Include: (2) Draw Studs, Quick Connect Alignment System, Multi-Voltage Charger, Carrying Case



M18[™] FORCE LOGIC[™] **10 Ton Knockout Tool Kit**

2676-23, 2676-22 (2676-20 No Punches or Dies) Specifications:

opeenieanenei	
Mild Steel Capacity	6" in 12 Gauge
Stainless Steel Capacity	6" in 14 Gauge
Output Force	10 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height / Weight	5.5" / 7.1 lbs

Includes: 2676-23 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, EXACT[™] 1/2" - 4" Conduit Punches and Dies; 2676-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, 1/2" - 2" EXACT[™] Conduit Punches and Dies; 2676-20 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs (No Punches or Dies Included); All Kits Include: (3) Draw Studs, Quick-Connect Alignment System, Multi-Voltage Charger, Carrying Case



EXACT[™] Accessory Kits 49-16-2692 1/2" - 1-1/4" Knockout Set 49-16-2693 1/2" - 2" Knockout Set

49-16-2694 1/2" - 2" Hand Ratchet Knockout Set 49-16-2695 2-1/2" - 4" Knockout Set

EXACT[™] Punches and Dies

49-16-2660* 1/2" Die 49-16-2660S 1/2" Die 49-16-2661* 1/2" Punch 49-16-2661S 1/2" Punch 49-16-2662 3/4" Die 49-16-2663 3/4" Punch 49-16-2664 1" Die 49-16-2665 1" Punch 49-16-2666 1-1/4" Die 49-16-2667 1-1/4" Punch 49-16-2668 1-1/2" Die 49-16-2669 1-1/2" Punch 49-16-2670 2" Die 49-16-2671 2" Punch 49-16-2672 2-1/2" Die 49-16-2673 2-1/2" Punch 49-16-2674 3" Die 49-16-2675 3" Punch 49-16-2676 3-1/2" Die 49-16-2677 3-1/2" Punch 49-16-2678 4" Die 49-16-2679 4" Punch 49-16-2686 5" Die 49-16-2687 5" Punch 49-16-2688 6" Die 49-16-2689 6" Punch *These items are intended only for Mild Steel.

EXACT[™] Sink Punches & Dies

49-16-2705 7/8" Sink Die 49-16-2706 7/8" Sink Punch 49-16-2700 1-3/8" Sink Die 49-16-2701 1-3/8" Sink Punch

Rapid Reset Draw Studs

49-16-2703 Rapid Reset 3/4" Draw Stud 49-16-2704 Rapid Reset 1-1/8" Draw Stud 49-16-2708 Rapid Reset 1-1/8" Long Draw Stud

Draw Studs

49-16-2621 3/8" Ball Bearing Draw Stud 49-16-2622 3/4" Ball Bearing Draw Stud 49-16-2680 7/16" Draw Stud 49-16-2681 3/4" Draw Stud 49-16-2682 1-1/8" Draw Stud 49-16-2707 1-1/8" Long Draw Stud

Adapters

49-16-2684 3/8" Adapter for EXACT™ 2-1/2" - 4" Dies to 3/4" Draw Studs 49-16-2685 Adapter for M18[™] FORCE LOGIC[™] Knockout Tool to other major brands of punches and dies



M18[™] Cable Stripper Kit

2935CU-21S, 2935AL-21, 2935X-21 (2935-20 Tool-Only) **Specifications:**

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.5" x 2.8" x 11.3"
Weight	3.8 lbs

Includes: 2935CU-21S 1/0 AWG - 750 MCM Cu THHN / XHHW Bushings; 2935AL-21 1/0 AWG – 750 MCM AI THHN / XHHW Bushings; 2935X-21 1/0 AWG - 500 MCM Cu RHW / RHH / USE Bushings; All Kits Include: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Cable Stripper Accessories

Compatible with 2935-20, 2435-20

Bushing Kits

49-16-BKITC 1/0 AWG - 750 MCM Cu THHN / XHHW Bushing Kit 49-16-BKITA 1/0 AWG - 750 MCM AI THHN / XHHW Bushing Kit

Bushings - Cu THHN / XHHW

49-16-B01AC 1/0 AWG Cu THHN / XHHW Bushing 49-16-B02AC 2/0 AWG Cu THHN / XHHW Bushing 49-16-B03AC 3/0 AWG Cu THHN / XHHW Bushing 49-16-B04AC 4/0 AWG Cu THHN / XHHW Bushing 49-16-B250S 250 MCM Cu THHN / XHHW S Bushing 49-16-B250C 250 MCM Cu THHN / XHHW Bushing 49-16-B300S 300 MCM Cu THHN / XHHW S Bushing 49-16-B300C 300 MCM Cu THHN / XHHW Bushing 49-16-B350S 350 MCM Cu THHN / XHHW S Bushing 49-16-B350C 350 MCM Cu THHN / XHHW Bushing 49-16-B400S 400 MCM Cu THHN / XHHW S Bushing 49-16-B400C 400 MCM Cu THHN / XHHW Bushing 49-16-B500S 500 MCM Cu THHN / XHHW S Bushing 49-16-B500C 500 MCM Cu THHN / XHHW Bushing 49-16-B600S 600 MCM Cu THHN / XHHW S Bushing 49-16-B600C 600 MCM Cu THHN / XHHW Bushing 49-16-B750C 750 MCM Cu THHN / XHHW Bushing

Bushings - AI THHN / XHHW 49-16-B01A 1/0 AWG AI THHN / XHHW Bushing 49-16-B02A 2/0 AWG AI THHN / XHHW Bushing 49-16-B03A 3/0 AWG AI THHN / XHHW Bushing 49-16-B04A 4/0 AWG AI THHN / XHHW Bushing 49-16-B250 250 MCM AI THHN / XHHW Bushing 49-16-B300 300 MCM AI THHN / XHHW Bushing 49-16-B350 350 MCM AI THHN / XHHW Bushing 49-16-B400 400 MCM AI THHN / XHHW Bushing 49-16-B500 500 MCM AI THHN / XHHW Bushing 49-16-B600 600 MCM AI THHN / XHHW Bushing 49-16-B750 750 MCM AI THHN / XHHW Bushing

Bushings - Cu RHW / RHH / USE

49-16-B01AX 1/0 AWG Cu RHW / RHH / USE Bushing 49-16-B02AX 2/0 AWG Cu RHW / RHH / USE Bushing 49-16-B03AX 3/0 AWG Cu RHW / RHH / USE Bushing 49-16-B04AX 4/0 AWG Cu RHW / RHH / USE Bushing 49-16-B250X 250 MCM Cu RHW / RHH / USE Bushing 49-16-B300X 300 MCM Cu RHW / RHH / USE Bushing 49-16-B350X 350 MCM Cu RHW / RHH / USE Bushing 49-16-B500X 500 MCM Cu RHW / RHH / USE Bushing

Replacement Blade for Bushings

48-44-2935 Replacement Blade for Cable Stripper Bushings





(4) #10 Wires

Feed & Retract

13.2" x 6.0" x 17.7" 19.1 lbs (2873B)

16.2 lbs (2873A),

8.3 lbs (2873-20)

M18FUEL **ANGLER[™]** Pulling **Fish Tape Kit**

2873A-22, 2873B-22 (2873-20 Tool-Only) Specifications:

Pull Force

Dimensions (L x W x H)

Powered Feed

& Retract

Weight



Includes: 2873A-22: ANGLER[™] 120' x 1/8" Steel Pulling Fish Tape; 2873B-22: ANGLER[™] 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge; All Kits Include: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger **Related Accessories:** 48-44-5176 M18 FUEL" ANGLER 120' x 1/8" Steel Pulling Fish Tape Replacement Cartridge 48-44-5178 M18 FUEL[™] ANGLER[™] 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge 48-44-5195 M18 FUEL[™] ANGLER[™]

100' Non-Conductive Polyester Pulling Fish Tape Replacement Cartridge







M18 FUEL **Pipe Threader** W/ ONE-KEY™ Kit

2874-22HD	? (
Specifications:	

Capacity	1/8" – 2"	REDLITHIUM
Kickback Control	AUTOSTOP™	HIGH OUTPUT HD120
Threading Support Arm	Yes	
Trigger	Variable Speed	
Die Head Retention Lock	Yes	
Die Head Compatibility	RIDGID [®] 12R, Ree	d R12+

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Threading Support Arm, Rapid Charger Carrving Case



M18[™] FORCE LOGIC **Press Tool Kit** w/ ONE-KEY with 1/2" - 2" CTS Jaws

2922-22 (2922-20 No Jaw Kit) **Specifications:**

Capacity	1/2" - 4" (Varies by Material)
Calibration Interval	50,000 Cycles
Approx Cycle Time	4 Seconds
Press Force	7,200 lbs
ONE-KEY [™] Compatible	Report. Track. Manage.
Performance Reporting	Wireless, Mobile, Desktop
Length/Weight	14.1" / 6.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, (6) CTS Jaws (1/2", 3/4", 1", 1-1/4", 1-1/2", 2"), Multi-Voltage Charger, Carrying Case; 2922-20 No Jaws Included



M18[™] FORCE LOGIC[™] **Long Throw Press Tool Kit** 2773-22L (2773-20L No Jaw Kit) Specifications:

Length / Weight	20.1" / 10.1 lbs
Press Force	7,200 lbs
Approximate Cycle Time	4 Seconds, 8 Seconds at Extended Stroke
Calibration Interval	50,000 Cycles (LED Indicator)
Capacity	1/2" – 4" (Varies by Material)

Battery Packs, (3) Jaws (1/2", 3/4", 1"), Multi-Voltage Charger, Carrying Case; 2773-20L No Jaws Included

M18[™] Short Throw Press Tool w/ PEX Crimp Jaws Kit 2674-22C, 2674-20C

Specifications: Capacity Up to 1" Cycle Time 3 Seconds Auto Cycle Yes

Length / Weight



Includes: 2674-22C (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger; 2674-20C Battery and Charger Sold Separately; All Kits Include: (3) PEX Crimp Jaws (1/2", 3/4", 1"), Carrying Case

FORCE LOGIC[™] Press Tool Accessories

Compatible with 2922-20 and 2773-20L Accessory Kits

49-16-2696 1/2" – 1" IPS-P Press Jaw Kit **49-16-2690** 2-1/2" – 4" CTS-Vr1 Press Ring Kit 49-16-2691* 1-1/4" - 2" IPS-Ar1 Press Ring Kit 49-16-2697 1/2" - 2" IPS-P Press Ring Kit 49-16-2698* 2-1/2" - 4" IPS-Pr2 Press Ring Kit

CTS Jaws & Rings

49-16-2650 1/2" CTS-V Press Jaw 49-16-2651 3/4" CTS-V Press Jaw 49-16-2652 1" CTS-V Press Jaw 49-16-2653 1-1/4" CTS-V Press Jaw 49-16-2654 1-1/2" CTS-V Press Jaw 49-16-2655 2" CTS-V Press Jaw 49-16-2656 2-1/2" CTS-Vr1 Press Ring 49-16-2657 3" CTS-Vr1 Press Ring 49-16-2658 4" CTS-Vr1 Press Ring

IPS Jaws & Rings

49-16-2650B 1/2" IPS-P Press Jaw 49-16-2651B 3/4" IPS-P Press Jaw 49-16-2652B 1" IPS-P Press Jaw 49-16-2653B 1-1/4" IPS-Pr1 Press Ring 49-16-2654B 1-1/2" IPS-Pr1 Press Ring 49-16-2655B 2" IPS-Pr1 Press Ring 49-16-2656B* 2-1/2" IPS-Pr2 Press Ring 49-16-2657B* 3" IPS-Pr2 Press Ring **49-16-2658B*** 4" IPS-Pr2 Press Ring 49-16-2650S 1/2" IPS-IA Press Jaw 49-16-2651S 3/4" IPS-IA Press Jaw 49-16-2652S 1" IPS-IA Press Jaw 49-16-2653S 1-1/4" IPS-IAr2 Press Ring 49-16-2654S* 2" IPS-IAr2 Press Ring 49-16-2655S* 2" IPS-IAr2 Press Ring

PEX Jaws & Rings

49-16-2651C 1/2" PEX-CRIMP Jaw 49-16-2653C 3/4" PEX-CRIMP Jaw 49-16-2654C 1" PEX-CRIMP Jaw 49-16-2655C 1-1/4" PEX-CRIMP Jaw 49-16-2656C 1-1/2" PEX-CRIMP Jaw 49-16-2657C 2" PEX-CRIMP Jaw

*Compatible with 2773-20L only.

ACR Jaws & Rings

49-16-2650M 1/4" Streamline™ ACR Press Jaw 49-16-2652M 3/8" Streamline[™] ACR Press Jaw 49-16-2653M 1/2" Streamline™ ACR Press Jaw 49-16-2654M 5/8" Streamline™ ACR Press Jaw 49-16-2655M 3/4" Streamline[™] ACR Press Jaw 49-16-2656M 7/8" Streamline™ ACR Press Jaw 49-16-2651M 1-1/8" Streamline™ ACR Press Ring 49-16-2661M 1/4" - 7/8" Streamline™ ACR Press Jaw Kit 49-16-2650R 1/4" RLS® Press Jaw 49-16-2652R 3/8" RLS® Press Jaw 49-16-2653R 1/2" RLS® Press Jaw 49-16-2654R 5/8" RLS® Press Jaw 49-16-2655R 3/4" RLS® Press Jaw 49-16-2656R 7/8" RLS® Press Jaw 49-16-2657R 1-1/8" RLS® Press Jaw 49-16-2658R 1-3/8" RLS® Press Jaw 49-16-2660R 1/4" - 1-3/8" RLS® Press Jaw Kit



M18[™] Short Throw Press Tool w/ Viega® PureFlow® Jaws Kit

2674-22P, 2674-20P

Specifications		
Capacity	Up to 1"	
Cycle Time	3 Seconds	
Auto Cycle	Yes	
Length / Weight	13.5" / 4.8 lbs	

Includes: 2674-22P (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Multi-Voltage Charger; 2674-20P Battery and Charger Sold Separately; All Kits Include: (3) Viega® PureFlow® Jaws (1/2", 3/4", 1"), Carrying Case

Short Throw Press Tool Accessories

Compatible with 2674-20C and 2674-20P 49-16-2630C 3/8" PEX Crimp Jaw **49-16-2631C** 1/2" PEX Crimp Jaw **49-16-2632C** 5/8" PEX Crimp Jaw 49-16-2633C 3/4" PEX Crimp Jaw 49-16-2634C 1" PEX Crimp Jaw 49-16-2630P 3/8" Viega® PureFlow® Jaw 49-16-2631P 1/2" Viega® PureFlow® Jaw 49-16-2632P 5/8" Viega® PureFlow® Jaw 49-16-2633P 3/4" Viega® PureFlow® Jaw 49-16-2634P 1" Viega® PureFlow® Jaw



M18[™] FORCE LOGIC[™] 2" - 3" **ProPEX® Expansion Tool Kit**

2633-22HD

Specifications:

Capacity	2", 2-1/2" and 3"
Auto-Rotation	Built-In
Auto-Cycle	Built-In
Dimensions (L x W x H)	14.5" x 11.8" x 4.8"
Weight	13.1 lbs



Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, (3) ProPEX® Expansion Heads (2", 2-1/2", 3"), Side Handle, Grease, Multi-Voltage Charger, Carrying Case **Related Accessories:** 49-08-2401 150g ProPEX® Expander Cone Grease

49-16-2614 2" ProPEX® Expansion Head 49-16-2616 2-1/2" ProPEX® Expansion Head 49-16-2618 3" ProPEX® Expansion Head

M18 FUE	2" ProPEX®
Expande	er Kit w∕ ONE-KEY™
with 1-1/4	
ProPEX ®	Expander Heads
2932-22XC	

Specifications:

Capacity	3/8" – 2"
Auto-Rotation	Built-In
Dimensions (L x W x H)	9" x 4.3" x 13.6"
Weight	10.9 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, (3) ProPEX® Expansion Heads (1-1/4", 1-1/2", 2"), 150g Expander Grease, Multi-Voltage Charger, Carrying Case **Related Accessories:** 49-16-2608 1" ProPEX® Expansion Head 49-16-2610 1-1/4" ProPEX® Expansion Head 49-16-2612 1-1/2" ProPEX® Expansion Head 49-16-2613 2" ProPEX[®] Expansion Head for M18 FUEL[™] Expander

49-08-2403 150g ProPEX® Expander Cone Grease w/ 2" Applicator Head





M18[™] ProPEX[®] **Expansion Tool Kit** 2632-22XC (2632-20 Tool-Only)

Specifications:

-	
Capacity	3/8" - 1-1/2"
Auto-Rotation	Built-In
Dimensions (L x W x H)	8.7" x 4.4" x 10.8"
Weight	9.2 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, (3) ProPEX® Expansion Heads (1", 1-1/4", 1-1/2"), Grease, Multi-Voltage Charger, Carrying Case **Related Accessories:** 49-08-2400 ProPEX® Expander Cone Grease 49-16-2608 1" ProPEX® Expansion Head 49-16-2610 1-1/4" ProPEX[®] Expansion Head 49-16-2612 1-1/2" ProPEX® Expansion Head







M18 FUEL

Sewer Sectional Machine Kit w/ CABLE DRIVE for 7/8" & 1-1/4" Cable

2871A-22, 2871-22 **Specifications:** Maximum Drain Line 2" - 8" up to 200'

Capacity	
Cable Capacity	7/8" and 1-1/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	700 RPM
Height / Length	23" / 35"
Weight	74 lbs

Includes: 2871A-22 (7) 1-1/4" x 15' All Purpose Open Wind Cables, (2) Cable Containers, Straight Auger, Funnel Auger, Small Opening Tool, Medium Opening Tool, 3" Grease Cutter, 3" Root Cutter, 4" Root Cutter, Pin Key, Head Attachment Case:

All Kits Include: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Rear Guide Hose, Rapid Charger



M18 FUEL **Sectional Machine for** 5/8" & 7/8" Cable 2818-21, 2818A-21, 2818B-21

Specifications:

Cable Feed & Retract Manual

Maximum Drain Line

Capacity

Weight

Cable Capacity

Cable Spin Speed

Height / Length

LITHIUM

2818A-21: Large Rear Guide Hose, Medium Cable Container, (5) 7/8" x 15' All Purpose Open Wind Sectional Cables, - 4" Head Attachment Kit: 2818B-21: Small Rear Guide Hose, Small Cable Container, (6) 5/8" x 7-1/2' All Purpose Open Wind Sectional Cables, ' Head Attachment Kit:

All Kits Include: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Carry Strap, Rapid Charge

1-1/4" – 6" out to 150'

5/8" and 7/8

650 RPM

27.3 lbs

Includes: 2818-21: Large Rear Guide Hose;

15.1" / 14.6"





Related Accessories: 47-53-2871 Cable Container 47-53-2872 Rear Guide Hose

47-53-2874 Small Rear Guide Hose 47-53-2873 Large Rear Guide Hose 47-53-2869 Small Cable Container 47-53-2870 Medium Cable Container 48-08-0555 Carrying Strap

Compatible with 2818-20

5/8"

48-53-2680 5/8" x 7.5' All Purpose Sectional Cable 48-53-3811 Drop Head Bulb Auger w/ RUST GUARD™ for 5/8" Sectional Cable 48-53-3812 Drop Head Straight Auger w/ RUST GUARD™ for 5/8" Sectional Cable 48-53-3813 Flexible Funnel Auger w/ RUST GUARD™ for 5/8" Sectional Cable 48-53-3814 Flexible Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable

- 48-53-3815 2" Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable 48-53-3820 1-1/4" - 2" Head Attachment Kit w/ RUST GUARD™
- for 5/8" Sectional Cable
- Compatible with 2818-20 and 2871-20

7/8"

48-53-2852 7/8" x 15' All Purpose Sectional Cable 48-53-3829 Flexible Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3830 Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3828 Flexible Funnel Auger w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3831 Funnel Auger w/ RUST GUARD™ for Sectional Cable 48-53-3825 2" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3832 3" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3833 4" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3834 6" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3827 2" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3835 3" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3836 4" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3837 3" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3838 4" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable 48-53-3839 2" - 4" Head Attachment Kit w/ RUST GUARD" for 7/8" Sectional Cable

48-53-3840 3" - 6" Head Attachment Kit w/ RUST GUARD™ for 7/8" Sectional Cable

Compatible with 2871-20 1-1/4"

48-53-2851 1-1/4" x 15' All Purpose Sectional Cable

48-53-2854 1-1/4" x 15' Heavy Duty Sectional Cable 48-53-4830 Straight Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4831 Funnel Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4832 3" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4833 4" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4834 6" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4835 3" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4836 4" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4837 3" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4838 4" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable 48-53-4840 3" - 8" Head Attachment Kit w/ RUST GUARD" for 1-1/4" Sectional Cable

44-60-0005 Pin Key for Drain Cleaning 48-53-2839 Head Attachment Case





Medium Drop Head), Pin Key: 2775E-211: 5/8" x 50' Open Wind Coupling Cable w/ RUST GUARD™ Plating. (4) Cable Head Attachments w/ RUST GUARD™ Plating (1" Spade Bit, C-Cutter, Small Bulb Head, Small Drop Head), Pin Key;

All Kits Include: 2775-211: SWITCH PACK™ Powered Base, SWITCH PACK[™] Drum w/ Anchor Cable, (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Multi-Voltage Charger

Related Accessories: 47-53-2775 SWITCH PACK[™] Drum w/ Anchor Cable 47-53-2774 CABLE DRIVE[™] Assembly

47-53-2773 Mounting Plate 47-53-2776 Guide Hose

M18 FUEL

Drain Snake w/ CABLE DRIVE™ Kit for 1/4" - 3/8" Cable

2772A-21 (2772A-20 Tool-Only), 2772B-21XC

Specifications:

1-1/4" – 3" up to 50' Maximum Drain Line Capacity Drum Capacity 1/4" x 50', Best for 1-1/4" - 2" drain lines; 5/16" x 50', Best for 1-1/4" - 2-1/2" drain lines; 3/8" x 35', Best for 2" - 3" drain lines Yes. CABLE DRIVE™ Powered Cable Feed & Retract Variable Feed Speed 0 – 8" Per Second Variable Spin Speed 0 - 600 RPM Feed Lock Yes. Twist Lock Cable Lock Yes, Twist Lock LED Light Yes Length / Weight 19.5" / 8.2 lbs

Includes: 2772A-21 (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating; 2772B-21XC (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, 1/4" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, 3/8" x 35' Inner Core Coupling Cable w/ RUST GUARD[™] Plating. (4) Cable Attachments (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key; 2772A-20 Only Includes 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD[™] Plating, Battery and Charger Sold Separately; All Kits Include: Multi-Voltage Charger, Storage Bucket



SYSTEM WIDE M18

Drain Cleaning Accessories Compatible with MILWAUKEE® and other professional brand

drain cleaning machines **RUST GUARD[™] Plated Cables** 48-53-2563 1/4" x 25' Inner Core Bulb Head Handheld Cable 48-53-2564 1/4" x 25' Inner Core Drop Head Handheld Cable 48-53-2671 1/4" x 35' Inner Core Bulb Head Handheld Cable 48-53-2672 1/4" x 50' Inner Core Bulb Head Handheld Cable 48-53-2561 5/16" x 25' Inner Core Bulb Head Handheld Cable 48-53-2562 5/16" x 25' Inner Core Drop Head Handheld Cable 48-53-2673 5/16" x 35' Inner Core Bulb Head Handheld Cable 48-53-2674 5/16" x 50' Inner Core Bulb Head Handheld Cable 48-53-2772 5/16" x 75' Inner Core Drop Head Cable 48-53-2676 3/8" x 25' Inner Core Handheld Cable 48-53-2675 3/8" x 35' Inner Core Handheld Cable

RUST GUARD[™] Plated Cable Attachments

Compatible with MILWAUKEE [®] Coupling Cables
48-53-2681 Small Bulb Head
48-53-2682 Small Drop Head
48-53-2683 1" Spade Bit
48-53-2684 1" C-Cutter
48-53-2685 2" – 3" Head Attachment Kit
48-53-2786 Medium Funnel Head
48-53-2787 Medium Drop Head
48-53-2788 1-1/2" Spade Bit
48-53-2789 1-1/2" C-Cutter
48-53-2790 2" – 3" Head Attachment Kit










M18[™] 200¹ Stiff Pipeline **Inspection System Kit** 2974-21 (2974-20 Reel-Only)

Specifications:



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, 200' Stiff Pipeline Inspection Reel, M18[™] 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 34 mm Camera, Small Camera Head Skid for 34 mm Camera, Rapid Charger

creen	8" Daylight Readable
esolution	800 × 600
/ireless Range	200'
/eight	4 lbs

Specification	is:	
Line Capacity	2" - 6"	N ==
Push Cable	10 mm, 120'	L/
Camera Head	25 mm, Self-Leveling, Sapphire Lens	
Camera Resolution	1080P	
Internal Storage	500GB	
Sonde Frequency	512kHz, 33kHz	
Line Trace Frequency	33kHz, 83kHz	

M18[™] 120¹ Pipeline Inspection

120' Mid-Stiff Pipeline Inspection Reel, M18™ 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 25 mm Camera, Small Camera Head Skid for 25 mm Camera, Rapid Charger **Related Accessories:** 2971-20 M18™ Wireless Monitor



Pump Kit
.9
480
144
18'
75'
Yes
Yes
3/4" Brass Inlet and Outlet
7.5 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, (2) 3/4" Brass Fittings, Multi-Voltage Charger



0 ---

OUTDOOR POWER EQUIPMENT M18 = = [**DRIVEN TO OUTPERFORM**











M18FUEL

16" Chainsaw Kit

2727-21HD (2727-2 Specificatio	27	
Bar Length	16"	
Chain Gauge	.043"	REDLITHIUM
Chain Pitch	3/8" Low Profile	HIGH OUTPUT HD1
RPM	6,600	
Length / Weight	33.0" / 13.9 lbs	

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, 16" Oregon® Bar and Chain, Scrench, Scabbard, Rapid Charger

M18FUEL

14" Chainsaw 2727-20C Tool-Only **Specifications:**



LITHIUM

Bar Length 14" Chain Gauge .043" Chain Pitch 3/8" Low Profile **RPM** 6,600 Length / Weight 31.0" / 10.4 lbs

Battery and Charger Sold Separately

Includes: 14" Oregon® Bar and Chain, Scrench, Scabbard

M18FUEL String Trimmer Kit w/ QUIK-LOK™ 2825-21ST (2825-20ST Tool-Only)



Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 - 4,900 / 0 - 6,200
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	73.6" / 12.3 lbs

Includes: M18 FUEL[™] Power Head w/ QUIK-LOK[™], M18 FUEL[™] QUIK-LOK[™] String Trimmer Attachment, (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Rapid Charger





M18 FUEL

Pole Saw Kit w/ QUIK-LOK™

2825-21PS (2825-20PS Tool-Only)

Specifications:

RPM 0-4.600 Bar Length 10" .043" Chain Gauge Chain Pitch 3/8" Low Profile Length / Weight 84.0" / 12.7 lbs

Includes: M18 FUEL[™] Power Head w/ QUIK-LOK[™], M18 FUEL[™] QUIK-LOK[™] 10" Pole Saw Attachment, QUIK-LOK[™] 3' Attachment Extension, (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Oregon® Bar and Chain, Scrench, Rapid Charger

LITH

M18 FUEL **QUIK-LOK**TM Attachments

Compatible with M18 FUEL[™] Power Head w/ QUIK-LOK™ (2825-20) 49-16-2717 M18 FUEL™ String Trimmer Attachment **49-16-2718** M18 FUEL[™] Edger Attachment **49-16-2719** M18 FUEL[™] Articulating Hedge Trimmer Attachment **49-16-2720** M18 FUEL[™] 10" Pole Saw Attachment 49-16-2721 M18 FUEL™ 3' Attachment Extension



49-16-2721



M18[™] Brushless **String Trimmer Kit** 2828-21 (2828-20 Tool-Only)

Length / Weight

Specifications: Cutting Swath 14" – 16" Line Diameter .080" / .095" RPM 0-4,600/0-6,200 Variable Speed Trigger Feed System Bump Feed

73.6" / 11.5 lbs Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC6.0 Battery Pack, Multi-Voltage Charger



M18FUEL 24" Hedge Trimmer Kit

2726-21HD (2726-20 Tool-Only)

ns:		
24"		
3/4"		R
3,400		HIG
All Metal		
45.5" / 11.1 lb:	3	
	24" 3/4" 3,400 All Metal	24" 3/4" 3,400

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Scabbard, Rapid Charger

3001-20 Tool-Onl	e Trimme v
Specificatio	ons:
Blade Length	18"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All Metal
Length / Weight	36.5" / 8.4 lbs







DLITHIU

M18FUEL **Blower Kit**

2724-21HD (2724-20 Tool-Only) Specifications:



Max Air Volume	450 CFM
Max Air Speed	120 MPH
Noise Rating (db)	62 (ANSI B175)
Lock On Button	Yes
Length / Weight	36.9" / 7.3 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Rapid Charger

M18[™] SWITCH TANK[™] 4-Gallon **Backpack Sprayer Kit**

2820-21PS (2820-20PS Tool-Only) Specifications:

-	
Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.10 – 0.51 Gal/Min
Dry Weight	18.3 lbs



Includes: M18[™] SWITCH TANK[™] Powered Base, SWITCH TANK[™] 4 Gallon Sprayer Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger

Related Accessories:

49-16-28WS SWITCH TANK[™] 4 Gallon Water Supply Tank Assembly 49-16-28CS SWITCH TANK[™] 4 Gallon Concrete Sprayer Tank Assembly 49-16-28PS SWITCH TANK™ 4 Gallon Sprayer Tank Assembly





M18[™] ROCKET[™] Dual Pack **Tower Light w/ ONE-KEY[™] Kit**

2120-22HD (2120-20 Tool-Only)

Specifications:

1
-
7 🔜

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Shoulder Strap, Rapid Charger





POWERED BY

M18[™] RADIUS[™] Compact Site Light w/ Flood Mode 2144-20 Tool-Only

Specification	S:
Lumens (Area)	2,200 / 1,100 / 550
Lumens (Flood)	1,000 / 500 / 250
Modes	High, Medium, Low
Hands-Free	Self-Centering Metal Hook
Height / Weight	10.4" / 4.4 lbs

Battery and Charger Sold Separately



M18[™] PACKOUT[™] **Light/Charger**

2357-20 Tool-Only

Specifications:

Lumens	3,000 / 1,500 / 1,000
Modes	High, Medium, Low
Battery Charger	Charges all M18 [™] Batteries
USB Charger	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed

Battery and Charger Sold Separately



M18[™] ROVER[™] **Mounting Flood Light**

2365-20 Tool-Only **Specifications:**

-	
Lumens	1,500 / 650 / 300
Modes	High, Medium, Low
Water & Dust Rating	IP54
Rotating Head	Horizontal and Vertical
Hands-Free	Integrated Magnet, Spring Loaded Clamp
Length / Weight	6.3" / 3.2 lbs







M18[™] ROVER[™] **Dual Power Flood Light** 2366-20 Tool-Only

Specifications:		
Lumens	4,000 / 2,000 / 1,200	
Modes	High, Medium, Low	
Hands-Free	Keyholes for Hanging	
Length / Weight	9.7" / 5.8 lbs	

Battery and Charger Sold Separately





M18[™] ROCKET[™] Tower Light/Charger Kit 0126 01 (0126 00 Teel Only)

1

USB

 \bigcirc

POWERED BY

2136-21 (2136-20	31	*
Specificatio	ns:	Ĭ
Lumens	6,000 / 3,200 / 1,700	
Modes	High, Medium, Low	+
Battery Charger	Charges M18 [™] Batteries and USB Devices	
Height	40" Collapsed, 7' Fully Extended	Y
Weight	21 lbs	L
Includes: (1) M HIGH OUTPUT™ XC M18™ ROCKET™ Tor	8.0 Battery Pack,	
		POWERED BY

M18[™] ROCKET[™] Dual Power **Tower Light**

2131-20 Tool-Only Specifications:		
Lumens	2,500 / 1,100 / 700	
Modes	High, Medium, Low	
Height	40" Collapsed, 7' Fully Extended	
Neight	15.3 lbs	



Battery and Charger Sold Separately

M18[™] RADIUS[™] Site Light

2151-20 Tool-Only

Lumens

Modes Height / Weight

Specifications:



M18[™] RADIUS[™] Compact Site Light w/ ONE-KEY™

2146-20 Tool-Only



Battery and Charger Sold Separately Includes: Security Cable; 2147-20 Equipped with NEMA L5-20 Twistlock Outlets Also Available



M18™ RADIUS™ Compact Site		
2145-20 Tool-Only		
Specifications:		
Lumens	4,400 / 2,100 / 1,000	
Modes	High, Medium, Low	
Water & Dust Rating	IP54	
Hands-Free	Self-Centering Metal Hook	
Daisy Chain Compatible	Yes	
Weight	10.6 lbs	

Includes: Security Cable





Specifications:

	Modes	High, Medium, Low
	Water & Dust Rating	IP54
	Hands-Free	Self-Centering Metal Hook
	Daisy Chain Compatible	Yes
	Weight	10.6 lbs





4	
2	





CHARGES

9,000 / 4,800 / 2,500

High, Medium, Low

29.5" / 23.2 lbs

TRADE FOCUSED M18

M18[™] ROVER[™] Flood Light

2361-20 Tool-Only **Specifications:**

Lumens	1,500 / 780
Modes	High, Low
Water & Dust Rating	IP54
Hands-Free	(1) EMT Hanger
Length / Weight	8.8" / 3.1 lbs

Battery and Charger Sold Separately



M18[™] Stick Light

2352-20 Tool-Only Specifications

specifications.	
Lumens	300 / 150
Modes	High, Low
Water & Dust Rating	IP54
Pivoting Head	45°
Hands-Free	2 Stainless Steel Hooks
Length / Weight	11.6" / 1.1 lbs



Battery and Charger Sold Separately



M18[™] Trouble Light w/ USB Charging

2363-20 Tool-Only onificati

	Specifications:			
	Lumens	700 / 350 / 70 / 700		
	Modes	High, Medium, Low, Strobe		
	Run-Time	Up to 100 Hours		
	Beam Pattern	Adjustable Task – Area		
	Water & Dust Rating	IPX4		
	Hands-Free	2 Stainless Steel Hooks		
	USB Charger	2.1A USB Charging Port for External Devices		
	Length / Weight	11.5" / 1.2 lbs		





Battery and Charger Sold Separately



M18 [™] Search	Light	Kit
2354-21 (2354-20 Tool-O	nlv)	

Specifications: 1,250 / 1,200 / Lumens 600 / 1.200 Spot/Flood, Flood, Modes Spot, Strobe Beam Distance 730 yd / 668 m IP54 Water & Dust Rating 198° Head Rotation 11.5" / 3.1 lbs Length / Weight



Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Shoulder Strap, Multi-Voltage Charger







M18[™] Utility Bucket Light Kit

2122-22HD, 2122-21HD (2122-20 Tool-Only) **Specifications:**

•		
Lumens	2,500 / 2,200 / 800	
Modes	Flood, Spot/Flood, Spot	
Hands-Free	Patented Spring-Loaded Bucket Clamp	
Water & Dust Rating	IP56	
Length / Weight	13.8" / 8.3 lbs	
Includes: 2122-221 HIGH OUTPUT™ XC8.0 F	HD (2) M18 [™] REDLITHIUM [™] Packs:	
2122-21HD (1) M18 [™] REDLITHIUM [™] HIGH OUTPUT [™] XC8.0 Pack;		

All Kits Include: Rapid Charger, Storage Bag

M18[™] Utility Remote Control **Search Light** 2123-21HD (2123-20 Tool-Only)

Specifications:		0.0.0
Lumens	4,250 / 3,500 / 1,250 / 1,500	1
Modes	Flood, Spot/Flood Low	
Water & Dust Rating	IP56 Built For Outdoor Use	
Mounting	Portable Magnetic Base or 12V DC Permanent Base	

Includes: 2123-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger, 12V DC Permanent Base, M18[™] Portable Base, Remote Control, Dash Mount, Carry Bag

2123-20 12V DC Permanent Base, M18[™] Portable Base, Remote Control, Dash Mount, Lanyard, Carry Bag

Related Accessory:

49-16-2123B M18™ Utility Remote Control Search Light Magnetic Base w/ Carry Bag

M18[™] Work Light 2725 20 Tool On

2735-20 Tool-Only	
Specifications:	

Lumens	100	
Hands-Free	Integrated Hook	
Head Rotation	90°	

Battery and Charger Sold Separately

M18[™] Compact Blower

0884-20 Tool-Only - 161

Specifications:			
Max Air Volume	100 CFM		
Max Air Speed	160 MPH		
Switch	3-Speed Electronic		
Length / Weight	20.5" / 2.6 lbs		

Battery and Charger Sold Separately

Includes: Flexible Nozzle, 9" Extension, Universal Inflator/Deflator



Max Air Speed	15 MPH
Max Air Volume	600 CFM
Speed Settings	3
RPM (3 Settings)	1,370 / 1,900 / 2,350
Head Rotation	120°
Length / Weight	10.3" / 5.2 lbs
Additional Features	Key Holes, Pass-Through Holes

Battery and Charger Sold Separately

Includes: AC Adapter

LITHIUM

0.9.9

M18 FUEL **3-in-1 Backpack Vacuum Kit** 0885-21HD (0885-20 Tool-Only)

Specifications:

Air Volume

Run-Time

(w/ M18"

Battery)

Capacity

Inlet Diameter

Sealed Suction

HIGH OUTPUT™ XC8.0



Weight Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Telescoping Extension

Wand, Flexible Hose, HEPA Filter, Crevice Tool, Dust Extraction Adapter and Floor Tool, Rapid Charger **Related Accessories:** 49-90-1963 HEPA Filter





M18 FUEL **Compact Vacuum** 0940-20 Tool-Only Specifications: 32 CFM Air Volume Sealed Suction 80" H₂O

Run-Time (w/ M18™ Up to 28 Min XC5.0 Battery) Capacity .25 Gallon Inlet Diameter 1-1/4" Weight 4.4 lbs

Battery and Charger Sold Separately

Includes: Powered Floor Tool, Floor Tool, HEPA Filter, Foam Pre-Filter, Extension Wand, 6' Flexible Hose, Accessory Holder, Brush Tool, Utility Tool, Crevice Tool

Related Accessory: 49-90-1951 HEPA Dry Filter Kit (2 pk) 49-90-2012 HEPA Filter 49-90-2017 1-1/4" Round Brush Tool 49-90-2018 Vacuum Power Tool Adapter



POWERED BY

SOLUTION

CERTIFIED

FILTER

CERTIFIED

HEPA

ILTER



M18 FUEL PACKOUT[™] 2.5 Gallon Wet/Dry Vacuum

0970-20 Tool-Only

Specifications:

Air Volume	50 CFM
Sealed Suction	47" H ₂ O
Run-Time (w/ M18™ HIGH OUTPUT™ XC8.0 Battery)	Up to 50 Min
Capacity	2.5 Gallons
Inlet Diameter	1-1/4"
Weight	11.3 lbs

Battery and Charger Sold Separately

Includes: HEPA Filter, 6' Flexible Hose, Utility Nozzle,

Crevice Tool, Vacuum Power Tool Adapter **Related Accessories:** 49-90-1900 HEPA Filter 49-90-2015 Foam Wet Filter 49-90-2016 3 pk Fleece Dust Bags 49-90-2017 1-1/4" Round Brush Tool

49-90-2018 Vacuum Power Tool Adapter

M18[™] 2 Gallon **Wet/Dry Vacuum** 0880-20 Tool-Only

Specifications

specifications:	
Air Volume	45 CFM
Sealed Suction	32" H ₂ O
Run-Time (w/ M18™ HD9.0 Battery)	30 min
Capacity	2 Gallons
Inlet Diameter	1-1/4"
Weight	11.3 lbs

Battery and Charger Sold Separately

Includes: HEPA Filter, 6' Flexible Hose, Crevice Tool, Utility Nozzle **Related Accessories:**

49-90-1900 HEPA Filter 49-90-2015 Foam Wet Filter 49-90-2017 1-1/4" Round Brush Tool 49-90-2018 Vacuum Power Tool Adapter

M18[™] Compact Vacuum 0882-20 Tool-Only **Specifications:** Air Volume 40 CFM Sealed Suction 38" H₂O

000100 0001011	00 1120
Run-Time (w/ M18™ XC5.0 Battery)	25 min
Capacity	36 oz
Inlet Diameter	1-1/4"
Weight	4.3 lbs

Battery and Charger Sold Separately

Includes: 4' Flexible Hose, (2) Extension Tools, Crevice Tool, Floor Tool, Removable HEPA Filter **Related Accessories:** 49-90-1951 HEPA Filter (2 pk) 49-90-2017 1-1/4" Round Brush Tool 49-90-2018 Vacuum Power Tool Adapter









SYSTEM WIDE M18



M18[™] PACKOUT[™] Radio + Charger 2950-20 Tool-Only Specifications:





Bluetooth[®] 4.2, AM/FM, AUX Modes Battery Charger Charges all M18[™] Batteries Bluetooth® Range 100 ft USB Charging Port 2.1A USB Charging Port for External Devices Device Storage Weather Sealed

Battery Sold Separately

Includes: 3.2 mm Auxiliary Input Cord, (2) AAA Batteries (For Memory Backup)





Bluetoot

2792-20 Tool-Only	ite Radio/Charg	
Specification	e.	
Modes	AM, FM, AUX, Bluetooth®	
Battery Charger	Charges all M18 [™] Batteries	
Bluetooth® Range	100 ft	
USB Charging Port	2.1A USB Charging Port for External Devices	
Device Storage	Weather Sealed Auxiliary Compartment	Bluetooth
Battery Sold Separate	ely	
Includes: 3.2 mr Input Cord, (2) AAA B (For Memory Backup)	atteries CHARGI	
M18 [™] Jobsi 2890-20 Tool-Only Specification		
Modes	AM, FM, AUX	
USB Charging Port	2.1A USB Charging Port for External Devices	
Device Storage	Weather Sealed Auxiliary Compartment	
Battery and Charger	Sold Separately	
(2) AAA Batteries (For	in a an	RGES POWERED BY
M18 [™] / M12 Jobsite Sp 2891-20 Tool-Only		
Specification	s:	
Modes	Bluetooth [®] , AUX (Cable Not Included)	Bluetooth
Bluetooth® Range	100 ft	
USB Charging Port	2.1A USB Charging Port for External Devices	

Battery and Charger Sold Separately

External Devices

Includes: AC Adapter



















M18[™] Power Source

49-24-2371	
Specifications:	
USB Charging Port	2.1A USB Charging Port for External Devices
Run-Time	Up to 18 Hours

Run-Time All M18[™] Batteries Powered By

Battery Sold Separately

Powers all MILWAUKEE[®] M12[™] Heated Gear





M18[™] TOP-OFF[™] **175W Power Supply** 2846-20 Tool Only

Specifications	•	
Continuous Watts	175W	- 1
Power Source	Any M18 [™] Battery	
DC Output	(1) USB-A Port, (1) USB-C PD Port	
AC Output	(1) AC Outlet	

Battery Sold Separately

M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 **System Starter Kit** 48-59-1200

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Rapid Charger

M18[™] REDLITHIUM[™] **HIGH OUTPUT™ XC8.0** System Starter Kit

48-59-1880

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Pack, Rapid Charger

M18[™] REDLITHIUM[™] XC5.0 System Starter Kit

48-59-1850

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Multi-Voltage Charger

M18[™] REDLITHIUM[™] HIGH OUTPUT[™] CP3.0 **System Starter Kit** 48-59-1835

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] CP3.0 Battery Pack, Multi-Voltage Charger

Charge Speed	Charges up to 4X Faster,	
	Charges All HIGH OUTPUT [™] Batteri in One Hour Or Less	ies
On-Board Indicator Light	Yes	
Integrated Hang-Holes	Yes	
Cell Voltage Monitoring	Yes	
Batteries Sold Separately		
M18 [™] Six-Pac		
Sequential Cl	narger 🕋 🕋	
48-59-1806	1000	Ż
Specifications:		1
Compatibility	All M18 [™] Batteries	~
Charge Sequence	Sequential (Counter-Clockwise Rotation)	
Skip Button	Manually Designate which Battery Charges First	
Integrated Hang-Holes	Yes	
Cell Voltage Monitoring	Yes	
Pass-Through Plug	Yes	
Batteries Sold Separately M18 [™] & M12 [™] I 48-59-1807 Specifications:	Pass-Through Plug	
M18 [™] & M12 [™] I 48-59-1807 Specifications: Compatibility	Rapid Charge Stat	
M18 [™] & M12 [™] I 48-59-1807 Specifications:	Rapid Charge Stat	
M18 [™] & M12 [™] I 48-59-1807 Specifications: Compatibility	All M18 [™] and M12 [™] Batteries Charges 3 Batteries	
M18 [™] & M12 [™] I 48-59-1807 Specifications: Compatibility Charge Sequence	All M18 [™] and M12 [™] Batteries Charges 3 Batteries Simultaneously Charges Individual Batteries	ti
M18 [™] & M12 [™] 48-59-1807 Specifications: Compatibility Charge Sequence Charge Speed	All M18 [™] and M12 [™] Batteries Charges 3 Batteries Simultaneously Charges Individual Batteries up to 40% Faster	ti
M18 [™] & M12 [™] I 48-59-1807 Specifications: Compatibility Charge Sequence Charge Speed Capacity	All M18 [™] and M12 [™] Batteries Charges 3 Batteries Simultaneously Charges Individual Batteries up to 40% Faster Holds (3) M18 [™] and (3) M12 [™] Batter	ti
M18 [™] & M12 [™] 48-59-1807 Specifications: Compatibility Charge Sequence Charge Speed Capacity Integrated Hang-Holes	All M18 [™] and M12 [™] Batteries Charges 3 Batteries Simultaneously Charges Individual Batteries up to 40% Faster Holds (3) M18 [™] and (3) M12 [™] Batter Yes	ti

M18[™] & M12[™] Super Charger

All M18[™] and M12[™] Batteries

Sequential (First In, First Charged)

48-59-1811

Compatibility

Specifications:

Charge Sequence

M18[™] & M12[™] Rapid Charger 48-59-1808

Specifications:

LITHIUM

specifications:	
Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Batteries Sold Separately	







MILWAUKEE® is committed to improving productivity by providing performance-driven and trade-focused solutions so users can perform an entire day's work on one battery system. *Due to the physical size increase of the M18" REDLITHIUM" HIGH OUTPUT" HD12.0, it does not fit the following tools prior to a 6/1/2018 manufacturing date without applicable service part: 2787-20, 2788-20, 2771-20, 2122-20, 2130-20, 2135-20, 2145-20, 2145-20, 2360-20. MILWAUKEE" is committed to protecting end user's investments, offering FREE service upgrades for the listed products to any customer that purchases a HIGH OUTPUT" HD12.0 battery pack (starting summer 2018 you will be able to visit eService to request your service upgrade).





M18[™] & M12[™] Vehicle Charger

Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

80



					2	PIEC KITS	E					3 - 4 Ki	PIECE TS		LARGI KITS	
M18™ COMBO KITS	2996-22	2997-22	2893-22CX	2893-22	2697-22CT	2892-22CT	2691-22	2694-22	2992-22	2999-22	2897-22CT	2695-24	2696-24	2998-25	2696-26	2997-27
Kit Tool Total	2	2	2	2	2	2	2	2	2	2	2	4	4	5	6	7
M18 FUEL [™] 1/2″ Hammer Drill/Driver w/ ONE-KEY [™]																
M18 FUEL [™] 1/2" Hammer Drill/Driver																
M18 [™] 1/2" Brushless Hammer Drill/Driver																
M18 [™] 1/2" Compact Hammer Drill/Driver																
M18 [™] 1/2" Compact Brushless Drill/Driver																
M18 [™] 1/2" Compact Drill/Driver						_										
M18 FUEL [™] Drywall Screw Gun																
M18 FUEL [™] 1/4" Hex Impact Driver w/ ONE-KEY™																
M18 FUEL [™] SURGE [™] 1/4" Hex Hydraulic Driver																
M18 FUEL [™] 1/4" Hex Impact Driver																
M18 [™] 1/4" Hex Brushless Impact Driver																
M18 [™] Brushless 1/4" Hex 3-Speed Impact Driver																
M18 [™] 1/4" Hex Impact Driver*																
M18 FUEL [™] 1/2" Mid-Torque Impact Wrench w/ Friction Ring																
M18 FUEL [™] SAWZALL [®] Reciprocating Saw																
M18 [™] SAWZALL® Reciprocating Saw																
M18 [™] HACKZALL [®] One-Handed Reciprocating Saw																
M18 FUEL [™] 6-1/2" Circular Saw																
M18 [™] 6-1/2" Circular Saw																
M18 [™] Brushless 7-1/4" Circular Saw																
M18 FUEL [™] 4-1/2" / 5" Grinder Paddle Switch, No-Lock																
M18 [™] 4-1/2" Cut-Off / Grinder																
M18 [™] Work Light																
Also Includes																
M18 [™] and M12 [™] Multi-Voltage Charger																
M18 [™] REDLITHIUM [™] CP1.5 Battery Pack					2		2									
M18 [™] REDLITHIUM [™] CP2.0 Battery Pack			1			2					2					
M18 [™] REDLITHIUM [™] XC3.0 Battery Pack												2	2		2	
M18 [™] REDLITHIUM [™] XC4.0 Battery Pack			1	2					2							
M18™ REDLITHIUM™ XC5.0 Battery Pack	2	2						2		2				2		2
Carrying Case																
Contractor Bag																2

*M18[™] 1/4" Hex Impact Driver is the single, variable speed model





1•.

· 🔺 `

2

= }

SED













ALL MX FUEL BATTERIES FIT ALL MX FUEL EQUIPMENT









MX FUEL[™] Handheld Core Drill MXF301-2CP



MX FUEL[™] CARRY-ON[™] 3600W/1800W Power Supply MXF002-2XC

MX FUEL[™] Vibratory Screed MXF381-2CP





Most Advanced System of Equipment Electronics in the Industry Protects Equipment with Best-In-Class Thermal and Overload Monitoring Delivers In-Application Communication, **Optimizing Equipment Performance**

EQUIPMENT REDEFINED.

The MX FUEL[™] Equipment System revolutionizes the light equipment market by delivering the performance, run-time and durability demanded by the trades without the hazards associated with emissions, noise, vibration and the frustrations of gas maintenance. This completely compatible system goes beyond the limitations of gasoline and power cord units, utilizing the industry's most advanced batteries, motors and electronics to deliver a best-in-class experience for users. This is Equipment Redefined.

REDLITHIUM[™] **BATTERY PACK** Industry Leader in LITHIUM-ION Technology Patented Designs Protect Against Drops,

- Water and Harsh Environments
- Robust Electronics Optimize Performance for Every Equipment and Battery Combination





ukee









POWERSTATE™ BRUSHLESS MOTOR

Engineered Uniquely for the Demands of Each Piece of Equipment Optimized for the Perfect Combination of Performance, Portability and Productivity Built with Maximum Copper Content and Top-Grade Rare Earth Magnets



EQUIPMENT REDEFINED TRADE FOCUSED SYSTEM WIDE





MX FUEL[™] 14" Cut-Off Saw Kit



MX FUEL[™] **Breaker Kit**



MXF314-2XC **Specifications:** Blade Dia

Blade Diameter	14"	
Cut Depth	5"	
Blade Arbor	1" / 20 mm	
RPM	5,350	
On-Board Water Delivery	Yes	
Weight w/ Battery	32.1 lbs	
Push Button Start	Yes	
ONE-KEY [™] Compatible	Track and Manage.	\sim
Battery Compatibility	Fits All MX FUEL [™] Battery Packs	(
Warranty	2 Year Equipment, Battery & Charger	\mathcal{L}

Includes: (2) MX FUEL[™] REDLITHIUM[™] XC406 Battery Packs, MX FUEL[™] Charger, Wrench, Hex Key, Quick Connect, Contractor Bag

Available Accessories: Additional Equipment: (Not Included) (Not Included)

49-94-1475 14" x 1/8" x 1" Cutting Wheel

49-93-7540 14" Diamond Ultra Segmented Blade

> astest Cutting. laximum



Water Supply Kit

MXF368-1XC Specifications:

opeomoutionsi		1.
Chuck Size	1-1/8" Hex	
Blows per Minute	1,300	
Impact Energy (ft/lbs)	50	<u>?</u>
Vibration	4.9 m/s ²	
Soft Start	Yes	- P
Weight w/ Battery	63.9 lbs	
Push Button Start	Yes	
ONE-KEY [™] Compatible	Track and Manage.	
Battery Compatibility	Fits All MX FUEL [™] Bat	tery Packs
Warranty	2 Year Equipment, Ba	ttery & Charger

Includes: (1) MX FUEL[™] REDLITHIUM[™] XC406 Battery Pack, MX FUEL™ Charger, Cart, (3) Chisels

Available Accessories:

(Not Included) 8960-20 8 Gallon Dust Extractor

5321-DE

Attachment

Dust Extraction

Moil Point 48-62-4006

1-1/8" Hex 16"

48-62-4001

1-1/8" Hex 16" Narrow Chisel



SAFER HANDHELD POWER TO CORE HOLES 6" IN REINFORCED CONCRETE EASIEST CORING ANYWHERE PA

MX FUEL[™] Handheld Core Drill Kit



EQUIPMENT REDEFINED

//XF301-2CXS	
specifications:	
Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" – 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Stand Included	Yes
Weight: Machine w/ CP Battery	21.6 lbs
Weight: Stand Only	29.0 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL [™] Battery Packs
Warranty	2 Year Equipment, Battery & Charger

MX

Includes: (1) MX FUEL[™] REDLITHIUM[™] XC406 Battery Pack, (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack, MX FUEL[™] Charger, Compact Core Drill Stand, Trigger Lock, 5/8" - 11 Bit Adapter, Quick Connect, Hard Case with Wheels



MXF301-2CP **Specifications:**

Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" – 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Weight w/ Battery	21.6 lbs
Push Button Start	Yes
ONE-KEY [™] Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL [™] Battery Packs
Warranty	2 Year Equipment, Battery & Charger

Includes: (2) MX FUEL[™] REDLITHIUM[™] CP203 Battery Packs, MX FUEL[™] Charger, Trigger Lock, 5/8" - 11 Bit Adapter, Quick Connect, Hard Case with Wheels

Available Accessories for MXF301-2CP & MXF301-2CXS:

(Not Included)

2820-21WS M18[™] SWITCH TANK[™] 4-Gallon Backpack Water Supply Kit

8960-20 8 Gallon Dust Extractor

5319-DE Dry Coring Dust Extractor Attachment





48-17-5030 3" Diamond Ultra Wet Core Bit

48-17-0130 3" Diamond Ultra Dry Core Bit



Fastest Drilling, Maximum Run-Time





MX FUEL[™] CARRY-ON[™] 3600W/1800W **Power Supply Kit**



MXF002-2XC Specifications:		11 Milwauke
Peak Watts	3,600W	
Running Watts	1,800W	
Outlets	(2) 120V 15A Outlets	Constanting of the
Inverter Output	Pure Sine Wave	
Integrated Charger	Yes	
Push Button Start	Yes	
ONE-KEY [™] Compatible	Track and Manage.	
Ground Fault Isolated	Yes	
Intended For	One 15 Amp Tool	
Battery Compatibility	Fits All MX FUEL [™] Bat	tery Packs
Warranty	2 Year Equipment and	d Battery

XC406 Battery Packs, Detachable Charger Cord



Car In

MX FUEL[™] ROCKET[™] Tower Light/Charger Kit



91

MXF041-1XC Specifications: Max Lumens 27,000 High / Medium / Low Modes Collapsed Height 44" Extended Height 10' Width 20.8"

Weight w/ Battery110 lbsIngress RatingOutdoor UsePush Button StartYesONE-KEY™ CompatibleCustomize. Track. Manage.	Warranty	2 Year Equipment and Battery
Weight w/ Battery 110 lbs Ingress Rating Outdoor Use Push Button Start Yes ONE-KEY™ Compatible Customize.	Battery Compatibility	
Weight w/ Battery 110 lbs Ingress Rating Outdoor Use	ONE-KEY [™] Compatible	Odotonnieon
Weight w/ Battery 110 lbs	Push Button Start	Yes
	Ingress Rating	Outdoor Use
Depth 24.8"	Weight w/ Battery	110 lbs
	Depth	24.8"

Includes: (1) MX FUEL[™] REDLITHIUM[™] XC406 Battery Pack

w/ POWERTREDZ[™] Kit LIFT ASS POWER TO CLEAR ROOTS AT 200' MESS CONTAINED

MX FUEL[™] Sewer Drum Machine Accessories

Compatible with MXF501-1CP, MXF500-1CP

Machine Accessories 47-53-5001 6-1/2" Guide Hose 47-53-5002 Load Wheel

5/8" Inner **Core Cables** 48-53-2325 - 25' **48-53-2350** - 50' 48-53-2310 - 100'



48-53-2425 - 25' 48-53-2450 - 50' 48-53-2410 - 100'

Leader Cables &

48-53-2802 Leader Cable 48-53-2902 Leader Cable 48-53-2905 Anchor Cable **Cable Head** Attachments 48-53-2830 Straight Auger 48-53-2831 Funnel Auger 48-53-2835 Small Opening Tool 48-53-2836 Medium Opening Tool 48-53-2832 3" Root Cutters 48-53-2833 4" Root Cutters 48-53-2834 6" Root Cutters 48-53-2837 3" Grease Cutters 48-53-2838 4" Grease Cutters 48-53-2829 Pin Key 48-53-2839 Case 48-53-2840 9 pc Cable Head Attachment Kit

Anchor Cable

TRADE FOCUSED

MX FUEL[™] Sewer Drum Machine

MXF501-1CP Specifications:		
Drain Line Capacity	3" – 8" up to 200'	
Drum Capacity	100'	
Cable Capacity	5/8" and 3/4"	10 C 16
Powered Cable Feed & Retract	Yes, CABLE DRIVE™	
Cable Spin Speed	200 RPM	~<
Height / Length	47" / 32.5"	
Weight w/ Battery	125 lbs	
Lift Assist	Yes, POWERTRE	DZ™
Push Button Start	Yes	
ONE-KEY [™] Compatible	Track and Manag	je.
Battery Compatibility	Fits All MX FUEL	Battery Packs
Warranty	2 Year Equipmen	t, Battery & Charger

Includes: (1) MX FUEL[™] REDLITHIUM[™] CP203 Battery Pack, MX FUEL[™] Charger, 3/4" Anchor Cable

Also Available:

MX FUEL[™] Sewer Drum Machine Kit MXF500-1CP Specifications

Specifications:		
Drain Line Capacity	3" – 8" up to 200'	
Drum Capacity	100'	100
Cable Capacity	5/8" and 3/4"	and the
Powered Cable Feed & Retract	Yes, CABLE DRIVE™	1. 1. 1.
Cable Spin Speed	200 RPM	~<
Height / Length	47" / 32.5"	
Weight w/ Battery	110 lbs	
Lift Assist	No	
Push Button Start	Yes	
ONE-KEY [™] Compatible	Track and Manag	e.
Battery Compatibility	Fits All MX FUEL™	Battery Packs
Warranty	2 Year Equipmen	t, Battery & Charger

Includes: (1) MX FUEL[™] REDLITHIUM[™] CP203 Battery Pack, MX FUEL[™] Charger, 3/4" Anchor Cable





MX FUEL[™] Backpack Concrete Vibrator Kit



MX FUEL[™] Vibratory Screed Kit



MXF371-2XC **Specifications:** Maximum Head Size 2-1/2" 21 ft Maximum Shaft Length Yes Quick Connect Weight w/ Battery 34.5 lbs Push Button Start Yes Removable Harness Yes ONE-KEY[™] Compatible Track and Manage. Fits All MX FUEL[™] Batteries Battery Compatibility Wireless Remote Included Yes Compatible w/ Oztec Yes 2 Year Equipment, Battery & Charger Warranty

Includes: (2) MX FUEL[™] REDLITHIUM[™] XC406 Battery Packs, MX FUEL[™] Charger, MX FUEL[™] Concrete Vibrator Remote

Available Accessories: (Not Included)

48-37-5015 48-37-7007 1-1/2" Head 48-37-5020 2" Head

7' Shaft 48-37-7014 14' Shaft

MXF381-2CP Spacifications

Specifications:	
VPM	4,000 - 9,000
Bar Range	4 – 16 ft
Adjustable Handlebars	Yes
Kickstand	Yes
Weight w/ Battery	37 lbs
Push Button Start	Yes
ONE-KEY [™] Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL [™] Battery Packs
Compatible w/ MBW Bars	Yes
Warranty	2 Year Equipment, Battery & Charger

Includes: (2) MX FUEL[™] REDLITHIUM[™] CP203 Battery Packs, MX FUEL™ Charger, (1) 9/16 Wrench

Available Accessories: Not Included)

48-38-2016 16 ft Screed Bar 48-38-2014 14 ft Screed Bar 48-38-2012 12 ft Screed Bar 48-38-2010 10 ft Screed Bar 48-38-2008 8 ft Screed Bar 48-38-2006 6 ft Screed Bar 48-38-2004 4 ft Screed Bar



MX FUEL[™] Batteries and Charger



MX FUEL[™] REDLITHIUM[™] XC406 **Battery/Charger Expansion Kit**

Includes: (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL[™] Charge

MXFC-2XC



DOWNLOAD THE FREE APP NOW!

GET IT ON

Google Play



93



MX FUEL[™] REDLITHIUM[™] XC406 Battery

MXFXC406

Specification	IS:
----------------------	-----

Specifications:

Compatibility	Fits All MX FUEL [™] Equipment
Charge Duration	90 min
Capacity	6.0 Ah
Fuel Gauge	Yes
REDLINK [™] Intelligence	Yes
ONE-KEY [™] Compatible	Yes
Warranty	2 Year

MX FUEL[™] REDLITHIUM[™] **CP203 Battery** MXFCP203



opcomoutionsi	
Compatibility	Fits All MX FUEL [™] Equipment
Charge Duration	45 min
Capacity	3.0 Ah
Fuel Gauge	Yes
REDLINK [™] Intelligence	Yes
ONE-KEY [™] Compatible	No
Warranty	2 Year

MX FUEL[™] Charger MXFC



Specifications: Charges All MX FUEL[™] Batteries Compatibility Charge Speed Charges MX FUEL™ CP203 Battery in 45 min Charges MX FUEL™ XC406 Battery in 90 min REDLINK[™] Intelligence Yes On-Board Fan Yes Cell Voltage Monitoring Yes On-Board Yes Indicator Light Warranty 2 Year

NEW **ONE-KEY**[®] **BLUETOOTH** TRACKING TAG



The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Milwaukee Tool is under license. Other trademarks and trade names are those of their respective owners.



94



PORTABLE POWER TOOL

(including cordless product - tool, battery pack(s) & battery charger and Work Lights - cordless flashlights) LIMITED WARRANTY

Every MILWAUKEE® **power tool*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an electric power tool which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **five (5) years**^{**} after the date of purchase unless otherwise noted. Return of the power tool to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many power tools need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, chucks, brushes, cords, saw shoes, blade clamps, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, and bumper cover washers.

*This **warranty** does not cover Air Nailers & Staplers; Airless Paint Sprayer; Cordless Battery Packs; Gasoline Driven Portable Power Generators; Hand Tools; Hoist – Electric, Lever & Hand Chain; M12[™] Heated Gear; Reconditioned Product; and Test & Measurement Products. **There are separate and distinct warranties** available for these products.

**The warranty period for Job Site Radios, M12[™] Power Port, M18[™] Power Source, Jobsite Fan and Trade Titan[™] Industrial Work Carts is one (1) year from the date of purchase. The warranty period for the M18 FUEL[™] 1" D-Handle High Torque Impact Wrenches, Drain Cleaning Cables, AIRSNAKE[™] Drain Cleaning Air Gun Accessories, REDLITHIUM™ USB Laser Levels. TRAPSNAKE™ 25' Auger w/ CABLE DRIVE™ and FORCE LOGIC[™] Press Tool Accessories is two (2) years from the date of purchase. The warranty period for the M18™ Compact Heat Gun, 8 Gallon Dust Extractor, M18™ Framing Nailers, M18 FUEL[™] 1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY[™], M18 FUEL[™] 1" High Torque Impact Wrench w/ ONE-KEY[™], M18 FUEL[™] 2 Gal. Compact Quiet Compressor, M12[™] Laser Levels, 165' Laser Detector, M12[™] 23GA Pin Nailer, M18 FUEL[™] ¼" Blind Rivet Tool w/ ONE-KEY[™], M12 FUEL[™] Low Speed Tire Buffer, M18 FUEL[™] Random Orbital Polishers, and the M18[™] Utility Fencing Stapler is three (3) years from the date of purchase. The warranty period for the LED in the LED Work Light and the LED Upgrade Bulb for the Work Light is the lifetime of the product subject to the limitations above. If during normal use the LED or LED Bulb fails, the part will be replaced free of charge.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE power tool product. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARBANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE: TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a MILWAUKEE electric power tool.

CORDLESS BATTERY PACK LIMITED WARRANTY

Every MILWAUKEE® battery pack (sold with cordless product and/or as a replacement battery pack) is warranted to the original purchaser only to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a battery pack which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **stated** warranty period from date of purchase. Return of the battery pack to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MII WAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Battery Pack Cat. No.	Chemistry	Warranty Period (from date of purchase)	
48-11-1812 48-11-1828 (Serial number prefix "B41E" and later) 48-11-1840 48-11-1850 48-11-1850 48-11-1860 48-11-1860 48-11-1880 48-11-2402 48-11-2400 48-11-2400 48-11-2400 (Serial number prefix "C71")	LITHIUM-ION	Three (3) Years	\bigcirc
48-11-0490 48-11-1815 48-11-1820 48-11-1835 48-11-2001 48-11-2401 48-11-2420 48-11-2430	LITHIUM-ION	Two (2) Years	\bigcirc
48-11-1828 (Serial number prefix "B41D" and earlier) 48-11-1830 (Serial number prefix "A95") 48-11-2830 (Serial number prefix "A71")	LITHIUM-ION	Two (2) Years – plus, Three (3) Years Pro-Rata (prorated)*	
48-11-0100 48-11-1024 48-11-1830 (Serial number prefix "E95") 48-11-1970 48-11-2230	Nickel-Cadmium (Ni-Cd), Nickel-Metal- Hydride (Ni-MH), LITHIUM-ION	One (1) Year	

*The warranty period for MILWAUKEE M18[™] 48-11-1828 (with the serial number prefix "B41D" and earlier), V18[™] 48-11-1830 (with the serial number prefix "A95"), and V28[™] 48-11-2830 (with the serial number prefix "A71") is five (5) years / 2000 charges from the date of purchase, whichever first occurs. The first 1000 charges or 2 years of the warranty, whichever first occurs, are covered through free replacement of the defective battery. This means that for the earlier of the first 1000 charges or two (2) years from the date of purchase/first charge, a replacement battery will be provided to the customer for any defective battery free of charge. Thereafter, the remaining charges up to a total of 2000 or the remainder of the five (5) year period from the date of purchase, whichever first occurs, will be covered on a pro rata basis. This means that every customer gets an additional 1000 charges or three (3) years of pro rata warranty on the these battery packs, depending upon the amount of use. MILWAUKEE M18[™] 48-11-1828 (with the serial number prefix "B41E" and later), V18[™] 48-11-1830 (with the serial number prefix "E95"), and M28[™] 48-11-2830 (with the serial number prefix "C71") have different warranty periods, as listed.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE battery pack. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES. INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the **'Service Center Search'** in the **Parts & Service** section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **battery pack**.

HEATED GEAR LIMITED WARRANTY

Every MILWAUKEE® **Heated Gear product** (including its battery holder/ controller) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a Heated Gear product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **one (1) year*** after the date of purchase. Return of a Heated Gear product to a MILWAUKEE *factory* Service Center location, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE personnel, misuse, alterations, abuse, normal wear and tear, or accidents.

*This warranty does not cover a M12[™] LITHIUM-ION Battery Pack, a M12[™] Charger, or a REDLITHIUM[™] USB battery; **there are separate and distinct warranties** available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION. YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARBANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE..

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service
section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.
SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE factory
Service Center location.



OUTDOOR POWER EQUIPMENT LIMITED WARRANTY

Every MILWAUKEE[®] outdoor power equipment product* (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an outdoor power equipment product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **three (3) years**** after the date of purchase unless otherwise noted. Return of the outdoor power equipment to a MILWAUKEE factory Service Center location or participating MILWAUKEE Authorized Service Station freight prepaid and insured is required A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance or accidents

Normal Wear: Many outdoor power equipment products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to mower blades, trimmer head, trimmer head spool, cutting lines, blades, chains, blower tubes, brushes, o-rings, and seals.

*This warranty does not cover Cordless Battery Packs or Reconditioned Product. There are separate and distinct warranties available for these products

**The warranty period for SWITCH TANK[™] tank assemblies, hoses, handles, and wands are one (1) year from the date of purchase.

MILWAUKEE does not cover freight or labor charges associated with the inspection and testing of **outdoor power equipment products** which are found by MILWAUKEE **not** to be a valid warranty claim. A valid warranty claim must be substantiated by the discovery of defective material or workmanship by MILWAUKEE.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and nonwarranty service on a MILWAUKEE electric power tool.

REDLITHIUM USB LIMITED WARRANTY

Every MILWAUKEE® REDLITHIUM USB battery and charger* is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace repair a REDLITHIUM USB battery or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase unless otherwise noted. Return of the REDLITHIUM USB battery or charger to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station freight prepaid and insured is required For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to charging cables, and wall plugs.

*This **warranty** does not cover any cordless product sold with the REDLITHIUM USB battery and/or charger. There are separate and distinct warranties available for these products

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL, TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES. INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW. SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Find a Service Center' search in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800. SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE factory Service Center location.



PERSONAL LIGHTING

(A) 2010R Milwaukee® Rechargeable 250L Penlight w/ Laser, 2011R Milwaukee® Rechargeable 500L Everyday Carry Flashlight w/ Magnet, and 2012R Milwaukee® Rechargeable Magnetic Headlamp and Task Light 2 YEAR LIMITED WARRANTY

Every MILWAUKEE® MX FUEL™ product, battery pack, and charger is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a MX FUEL™ product, battery pack, or charger which, The rechargeable personal lighting products referenced above are after examination, is determined by MILWAUKEE to be defective in material warranted to the original purchaser only to be free from defects in or workmanship for a period of **two (2) years** after the date of purchase. material and workmanship. Subject to certain exceptions, MILWAUKEE Return of the MX FUEL[™] product, battery pack, or charger to a MILWAUKEE will repair or replace any part on the above Rechargeable Personal factory Service Center location or MILWAUKEE Authorized Service Station, Lighting Products which, after examination, is determined by MILWAUKEE freight prepaid and insured, is required. For the proper shipping procedure to be defective in material or workmanship for a period of two (2) years of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www. after the date of purchase. milwaukeetool.com. A copy of the proof of purchase should be included (B) All other MILWAUKEE® Personal Lighting Products with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, All other MILWAUKEE personal lighting products* (see exceptions normal wear and tear, lack of maintenance, or accidents.

LIMITED LIFETIME WARRANTY

below) are warranted to the original purchaser only to be free from defects in material and workmanship. Subject to certain exceptions MILWAUKEE will repair or replace any part on a personal lighting product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **lifetime** of such personal lighting products.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to clips, straps, charging cables, wall plugs, and rubber gaskets. This warranty does cover the **LED** in the personal lighting products, subject to the limitations herein

*This warranty does not cover Cordless Battery Packs or Chargers. There are separate and distinct warranties available for these products.

Return of all personal lighting products to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. The above warranties do not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, accidents, or caused by alkaline batteries.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OF LIMITATION OF INCIDENTAL OF CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THE ABOVE WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES. WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES. INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTIES AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS. SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THESE WARRANTIES GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Find a Service Center' search in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800. SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE factory Service Center location.

MX FUEL[™] PRODUCT, BATTERY PACKS, AND CHARGERS LIMITED WARRANTY

Normal Wear: Many MX FUEL[™] products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, assist & drive belts, pulleys, blade flanges, vacuum gaskets, tool free handles, set pins, skis, drive couplers, rubber boots, auto feed, stabilize blocks, wheels, carrier wheels, cords, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, tool holder, and bumper cover washers.

Warranty Registration is not necessary to obtain the applicable warranty on a MX FUEL product, battery pack, or charger

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU, THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW. MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800. SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a MILWAUKEE MX FUEL™ product, battery pack or charger.





LIGHTNING MAX REPAIR

MILWAUKEE® understands the unpredictability of the jobsite and the need for fast, reliable repairs and replacements. Through our Lightning Max Repair Program we are committed to providing you the best service so you can minimize downtime and get the job done.

SPEED: Repair of your tool in 7 – 10 days

PAY LESS, NOT MORE: Guaranteed to never pay more than the guoted Lightning Max Repair price **RELIABILITY:** All repairs are serviced by experienced, certified factory technicians QUALITY: Only genuine MILWAUKEE® parts used

WHERE TO GO FOR LIGHTNING MAX REPAIRS

eSERVICE

Solution for quick, convenient repairs, best for smaller tool quantities.

- FedEx shipping to MILWAUKEE[®] repair facility
- Your tool returned directly to you no need to pick it up
- Go to www.milwaukeetool.com/eService

FACTORY SERVICE CENTERS

Factory Service Centers also carry the widest variety of MILWAUKEE® Tools and Accessories for all your needs. 1-800-SAWDUST (1-800-729-3878)

Anaheim

1130 N Magnolia Anaheim, CA 92801

Atlanta 6155 Jimmy Carter Blvd Suite F2 Norcross, GA 30071

Boston 375 University Avenue Westwood, MA 02090

Chicago 6310 Gross Point Road Niles, IL 60714

Cleveland 8200 Sweet Valley Drive Valley View, OH 44125

Dallas 1625 W Mockingbird Ln Unit 205 Dallas, TX 75235

Denver 2500 W 8th Avenue, Unit E Denver, CO 80204

Houston 3566 West T.C. Jester Blvd Houston, TX 77018

Las Vegas 5580 S Decatur Blvd Unit 110 Las Vegas, NV 89118 Miami 3311 NW 82nd Avenue Miami, FL 33122

Minneapolis/St. Paul 9705 Valley View Road Eden Prairie, MN 55344

Milwaukee 13145 W Lisbon Road Brookfield, WI 53005

New York City 3068 Whitestone Expressway Flushing, NY 11354

Philadelphia 711 West Chester Pike Havertown, PA 19064

San Antonio 14329 San Pedro Avenue, Suite D San Antonio, TX 78232

San Diego 7849 - 7851 Clairemont Mesa Blvd. San Diego, CA 92111

San Francisco/Oakland 2341 Lincoln Avenue Hayward, CA 94545

Seattle 5963 Corson Avenue South Suite 104 Seattle, WA 98108

Washington D.C.

11900 Baltimore Ave Suite B Beltsville, MD 20705

CANADA

1-800-268-4015 Edmonton

14506 – 115th Avenue NW Edmonton AB T5M 3B9

Halifax Unit 102 50 Akerley Blvd Dartmouth NS B3B 1R8

Saskatoon Unit 630 3530 Millar Ave Saskatoon SK S7P 0B3

Vancouver 9000 Bill Fox Way, Unit 103A Burnaby BC V5J 5J3

Vaughan 140 Fernstaff Court, Unit 4 Vaughan ON L4K 3L8

Winnipeg 675 Berry St, Unit H Winnipeg MB R3H 1A7



